

Contents

AutoDoc:AutoDoc:BlueSpiceExpiry

Contents

1	DescriptionMsg	
2	License	
3	Requirements	
4	IntegratesInto	
5	SpecialPages	
6	Permissions	
6.1	Permissions	3
7	Config	
7.1	Configuration	
8	ApiModules	
8.1	API Modules	
9	Hooks	
9.1	Hooks	4

DescriptionMsg

Pages can be marked as expired.

License

GPL-3.0-only

Requirements

- MediaWiki: 1.35.0
- BlueSpiceFoundation: 4.0
- BlueSpiceReminder: 4.0

IntegratesInto

- BlueSpiceEchoConnector
- BlueSpiceReminder
- BlueSpiceSMWConnector

SpecialPages

- Expiry

Permissions

Permissions

Name	Description	Role
expirearticle	Expire pages	admin, editor, maintenanceadmin
expiry-delete	Remove expiration from pages	admin, editor, maintenanceadmin

Config

Configuration

Name	Value
ExpiryEnablePDFWatermark	true

Name	Value
ExpiryEnablePageWatermark	true
ExpiryEnablePrintWatermark	true

ApiModules

API Modules

- [bs-expiry-store](#)
- [bs-expiry-tasks](#)

Hooks

Hooks

- [BSUEModulePDFBeforeAddingStyleBlocks](#)
- [BSUEModulePDFgetPage](#)
- [BeforePageDisplay](#)
- [BlueSpiceDiscoveryTemplateDataProviderAfterInit](#)
- [ChameleonSkinTemplateOutputPageBeforeExec](#)
- [LoadExtensionSchemaUpdates](#)
- [MWStakeCommonUIRegisterSkinSlotComponents](#)
- [SkinTemplateNavigation::Universal](#)
- [StandardDialogsRegisterPageInfoPanelModules](#)
- [wgQueryPages](#)