

Contents

| | |
|--|----|
| 1. Manual:Extension/BlueSpiceConfigManager | 2 |
| 2. Manual:Extension/BlueSpiceArticleInfo | 22 |
| 3. Manual:Extension/BlueSpiceAuthors | 25 |
| 4. Manual:Extension/BlueSpiceDiscovery/Main navigation | 27 |
| 5. Manual:Extension/BlueSpiceExpiry | 32 |
| 6. Manual:Extension/BlueSpiceExtendedSearch | 34 |
| 7. Manual:Extension/BlueSpiceRating | 45 |
| 8. Manual:Extension/BlueSpiceReaders | 48 |
| 9. Manual:Extension/FlaggedRevs | 50 |
| 10. Manual:Extension/FlexiSkin | 57 |
| 11. Manual:Extension/VisualEditor/Insert images | 65 |
| 12. Manual:Preferences | 75 |
| 13. Reference:BlueSpiceConfigManager | 91 |

Config manager

Contents

| | |
|---|----|
| 1 Layout | 3 |
| 1.1 Filter options | 3 |
| 1.2 Searching for settings | 3 |
| 2 Settings by extension | 4 |
| 2.1 EventBus | 4 |
| 2.2 EnhancedUpload v4.3+ | 4 |
| 2.3 BlueSpiceFoundation | 4 |
| 2.3.1 Updating logo and favicon | 4 |
| 2.3.2 System | 6 |
| 2.4 BlueSpiceArticleInfo | 6 |
| 2.5 BlueSpiceAuthors | 7 |
| 2.6 BlueSpiceAvatars | 7 |
| 2.7 BlueSpiceBookshelf | 8 |
| 2.8 BlueSpiceChecklist | 9 |
| 2.9 BlueSpiceExtendedSearch | 10 |
| 2.10 BlueSpiceExtendedStatistics | 12 |
| 2.11 BlueSpiceInsertCategory | 12 |
| 2.12 BlueSpiceInsertLink | 12 |
| 2.13 BlueSpicePageTemplates | 13 |
| 2.14 BlueSpicePermissionManager | 14 |
| 2.15 BlueSpiceRSSFeeder | 14 |
| 2.16 BlueSpiceReaders | 14 |
| 2.17 BlueSpiceSaferEdit | 15 |
| 2.18 BlueSpiceUEModuleBookPDF | 15 |
| 2.19 BlueSpiceUEModuleHTML | 15 |
| 2.20 BlueSpiceUEModulePDF | 16 |
| 2.21 BlueSpiceUniversalExport | 16 |
| 2.22 BlueSpiceVisualEditorConnector | 16 |
| 2.23 BlueSpiceWholsOnline | 17 |
| 2.24 BlueSpiceExpiry | 17 |
| 2.25 BlueSpiceFlaggedRevsConnector | 17 |
| 2.26 BlueSpiceSocial | 19 |
| 2.27 BlueSpiceSocialBlog | 19 |
| 2.28 BlueSpiceSocialTopics | 20 |
| 3 BlueSpiceDiscovery | 20 |
| 3.1 Deactivating the Entrypoint links | 20 |
| 3.2 Positioning of skin elements | 21 |
| 3.3 Content Stabilization v4.3+ | 21 |


With the Config manager, a wiki user with *sysop* rights can manage wiki-wide settings in one place. In the [navigation](#), it is located at *Global navigation > Management > Configuration*. This link loads the page *Special:BluespiceConfigManager*.

Layout

Filter options

All settings can be accessed through the following filter options:

- **Feature:** group by type of functionality the setting belongs to (search, administration...)
- **Extension:** group by extension name
- **Package:** group by BlueSpice edition and services (BlueSpice free, BlueSpice pro, Matomo)




All settings are available in any type of grouping. Changing the grouping type does not add or remove setting options. It just groups them differently. After settings are adjusted, they can be saved by clicking *Save*, or cancelled by clicking *Reset*.

Note: If a server administrator has configured a setting to no longer be writable, it will be shown as greyed-out in the config manager. You will have to talk to your server administrator about changing such a setting.

Searching for settings

A search bar is located above the list of settings. Type in a keyword such as "logo" to find the corresponding setting. The search returns settings regardless of the currently selected group.

Note: The search field has to be empty if you want to see the filter menu instead of the search.



logo

BlueSpiceFoundation

Logo path:

`/w/skins/BlueSpiceCalumma/resources/images/common/logo/bs3_logo.png`

Config manager search box


Settings by extension

EventBus

Eventbus sends notifications to external urls in case something happens in the wiki. For example, if a page is created, an external service could then be started and create a pdf of that page. See the extension's page on mediawiki.org.

EnhancedUpload v4.3+

Sets the defaults for the [advanced image settings](#) when uploading and embedding an image into the wiki via drag-and-drop functionality. The default settings determine the orientation, type, and size of the image. These can be adjusted after embedding via the "Advanced settings" of the image on the page.



Extension: |

☐ EventBus

☒ EnhancedUpload

☐ BlueSpiceProDistributionConnect...

☐ ContentStabilization

☐ BlueSpiceFoundation

☐ BlueSpiceArticleInfo

☐ BlueSpiceAuthors

☐ BlueSpiceAvatars

☐ BlueSpiceBookshelf

☐ BlueSpiceChecklist

Editor

Image alignment: ⓘ

Image type: ⓘ

Image height: ⓘ

Image width: ⓘ

Configuration settings for the Enhanced upload

BlueSpiceFoundation


Updating logo and favicon

Note: Since BlueSpice 4.2, the logo and favicon can also be managed via the page [Special:Flexiskin](#) together with further skin customizations.


- **Logo path:** The logo image should be stored in the `/images` folder of your installation. If you store it in the `/skins` folder of your BlueSpice installation, it could be overwritten with an upgrade.

To upload the logo directly in the wiki:

1. **Upload** the logo on the page from the menu *Global actions > File list (Special:ExtendedFilelist)*.
2. **Click** on the thumbnail image of the logo. This opens the logo on a separate page.



3. **Copy** the relative logo path from the address bar. In a typical Wiki configuration, this path starts with */w/....*.



4. **Paste** the logo path into the text field for the logo.

| | |
|--|---|
| Extension | |
| <input checked="" type="checkbox"/> BlueSpiceFoundation <input type="checkbox"/> BlueSpiceAbout <input type="checkbox"/> BlueSpiceArticleInfo <input type="checkbox"/> BlueSpiceAuthors | Skinning Logo path: <input type="text" value="/w/nsfr_img_auth.php/6/68/LASERLINE_Logo_2016.png"/> Favicon path: <input type="text"/> |

5. **Click Save.**

6. **Refresh** the page (Strg+F5).

If the uploaded logo is too large, you can add the following code snippet to the page *MediaWiki:Common.css*. This automatically adjusts the image to the height of the main toolbar:

```
.bs-logo a {background-size: contain;}
```

- **Favicon path:** The favicon image should be stored in the */images* folder of your installation. If you store it in the */skins* folder of your BlueSpice installation, it could be overwritten with an upgrade. [Favicon images](#) have the file extension *.ico*.

System

- **Allowed file extensions:** For security reasons, the types of files that users can upload are restricted. Here, you can allow additional file formats. If a file format is blacklisted in the server configuration, adding this file extension here will not allow this file type to be uploaded. See [mediawiki.org/wiki/Manual:\\$wgFileExtensions](https://mediawiki.org/wiki/Manual:$wgFileExtensions) for more info.

XML file type: v4.x++

The *xml* file type is blacklisted since MW 1.39 and has to be allowed in *LocalSettings.php*:


```
$GLOBALS['wgProhibitedFileExtensions'] = array_diff( $GLOBALS['wgProhibitedFileExtensions'] ?? [], [ 'xml' ] );  
$GLOBALS['wgMimeTypeExclusions'] = array_diff( $GLOBALS['wgMimeTypeExclusions'] ?? [], [ 'application/xml', 'text/xml' ] );
```


- **Allowed image extensions:** The standard web image types are listed here. In general, you want to restrict image uploads to web images. See developer.mozilla.org/en-US/docs/Web/Media/Formats/Image_types for more on browser-supported image types.

BlueSpiceArticleInfo

BlueSpiceArticleInfo, together with *BlueSpiceAuthors*, *BlueSpiceReaders*, and *BlueSpiceExtendedSearch* is part of the *Page information* in the quality management tools.

- **Update interval in seconds:** Sets the refresh rate for the "Last edit" value. By default, this date is updated every 10 seconds via JavaScript.






BlueSpiceAuthors

BlueSpiceAuthors, together with *BlueSpiceArticleInfo* and *BlueSpiceReaders*, is part of the *Page information* in the quality management tools.


- **Display authors:** Show or hide authors on the page information page.




BlueSpiceAvatars

An avatar image is automatically generated if the user does not upload a profile picture or if the user decides to create an avatar image in the preferences.

- **Generator**
 - **InstantAvatar:** Generates an avatar image based on using the initials of the Real name or the Username
 - **Identicon:** Generates an avatar image based on parts of the user's IP address.





User image:

Change profile picture

Change profile picture

Identicon

Change profile picture

Picture upload

Browse Upload Reset


Picture from wiki or picture URL

Auto generate avatar

Generate new avatar

BlueSpiceBookshelf

- **Show book chapter pager after content:** Displays previous/next book page navigation at the end of each book page. (1)
- **Show book chapter pager before content:** Displays previous/next book page navigation at the beginning of each book page. (2)



User manual

< Previous 1 Next >

Login and preferences

Last edited 3 months ago by MLR Unwatch No status information

Login

To work with your BlueSpice wiki, you need to log in. Click on the login button in the top right corner of the screen.

In the following window, enter your user name and password. Click Log in and you're ready to go.

Log in

Username

Password

Keep me logged in

Log in

Help with logging in


Forgot your password?

< Previous 2 Next >

Book navigation


- **Use the display title from book source on article:** Shows the title from the book navigation as page title instead of the page name.





Note: If the page additionally contains a `{{DISPLAYTITLE}}` tag, the display title of the page is shown instead of the book title.

- **Prepend article table of contents and headlines with book numeration:** The page TOC does not start with the main heading 1, but with the actual number from the book chapter (see screenshot). If users have activated in their [user preferences](#) to "auto-number headings", the numbering system is matched accordingly.



- **Supress namespace prefix of book articles in output:** The namespace prefix of an article is not shown in PDFs.

BlueSpiceChecklist

- **Mark checklist changes as minor edit:** If this setting is active, changes to a checklist (for example, checking a checkbox) in view mode are logged as minor edits. If this setting is inactive, a change to the checklist is recorded as a regular version in the page history.

• (cur | prev) @ 12:01, 2019 December 5 ML Mlink-rodrigue (talk | contribs | block) m
(2,820 bytes) (+9) .. (Unchecked checkbox #1) (rollback 6 edits | undo) (Tag: Checklist change)


minor edit

BlueSpiceExtendedSearch

- **External file paths:** External locations to scan for and index files from. These locations are entered in key/value pairs of Physical path and URL prefix.
 - *Physical path:* Storage path. For mounted drives, for example: *X:\Documents*
 - *URL prefix:* All files indexed from the indexed physical location are prefixed in the search results. It should be used if files are available from a web server. By default, the URL prefix is set to the same value as *Physical path*.

Examples for external file paths

| Example file | Phys. Path | URL Prefix | Link in results list |
|--|---|--|--|
| S:\Sales\Info\glossaryy.pdf | S:\ | file:///S:/ | file:///S:/Sales/Info/glossary.pdf |
| | | https://sharepoint /Sales/ documents/ | https://sharepoint/Sales/ documents/Sales/Info /glossary.pdf |
| | | https://intranet /showdocs inline.aspx?path= | https://intranet/showdocsinline. aspx? path=/Sales/Info/glossary.pdf |
| /var/www/bluespice/w /mounted_ share/Sales/Info /glossary.pdf | /var/www /bluespice/w/ mounted_share/ | | https://wiki.company.local/w /mounted_ share/Sales/Info/glossary.pdf |



Feature

- ☐ System
- ☐ Skinning
- ☐ Data analysis
- ☐ Personalization
- ☐ Book
- ☐ Export
- ☐ Content structuring
- ☐ Quality assurance
- ☒ Searching and Navigation
- ☐ Editor
- ☐ Administration

BlueSpiceExtendedSearch

External file paths

No values set!

Add new entry

Physical path: S:\ * URL prefix: file:///S:/ ✓ 1

☐ Use simple autocomplete

☐ Automatically set language filter

Exclude patterns


No values set!

Add new entry

Physical path: * Exclude regular expression pattern: * ✓

Add an external file path: (1) confirm the checkmark and (2) save the settings.

- **Use simple autocomplete:** forces a more compact autocomplete (1-column Sales thumbnail preview).



Configu

Configure search

Configuration

Getting started - Login and configuration

Robot Configuration

Create and configure articles


ExtendedSearch configuration

Setup:Installation Manual/System Configuration/Apache Tomcat

+ Create page "Configu"

Search full text

compact autocomplete



Configu

Configure search

Configuration

Getting started - Login and configuration

Robot Configuration

Create and configure articles

ExtendedSearch configuration

Setup:Installation Manual/System Configuration/Apache Tomcat

VisualEditor configuration

+ Create page "Configu"

Search full text

Salesautocompletey

- **Automatically set language filter:** The search only returns pages whose language (PageLanguage) is identical to the user language (Language). Users can set their language in their [preferences](#). By default, the language of content pages is the same as the installation language (ContentLanguage) of the wiki. Some extensions can set the language of individual pages independently of the content language of the wiki.. (See: https://www.mediawiki.org/wiki/Manual:Language#Page_content_language). In many wikis, activating this filter has little effect.
- **Exclude patterns:** Files at external file locations can be excluded from search based on regular expression patterns.

BlueSpiceExtendedStatistics

- **Exclude these users:** Some user groups, like WikiSysop can skew the statistics, for example the statistics for search queries or because they complete automated maintenance tasks. These types of user groups can be excluded from the statistical results.
- **Maximum number of interval steps:** Sets the size of the x-axis for the results. For a few days, select the interval *Day* or *Calendar Week*, for periods over one year, select *Year* or *Month*. If you do not get any results for your query, try to adjust the interval accordingly.

BlueSpiceInsertCategory

- Insert category with its parent categories
- Preset categories of a page in the upload dialog

BlueSpiceInsertLink

- **Allow unmapped links:** if there is no prefix in the map, the link will still be inserted. Example: S:\HR. If this setting is unchecked, the link will not be inserted.
- **Allowed locations for external files:**

| Example file | Filesystem prefix | Web accessible Prefix | Link output |
|-----------------------------------|-------------------|--|--|
| S:\Sales\Info\glossaryy.pdf | S:\ | file:///S:/ | file:///S:/Sales/Info/glossary.pdf |
| | | https://sharepoint/Sales/documents/ | https://sharepoint/Sales/documents/Sales/Info/glossary.pdf |
| | | https://intranet/showdocs inline.aspx?path= | https://intranet/showdocsinline.aspx? path=/Sales/Info/glossary.pdf |
| /var/www/bluespice/w /mounted_ | | | |

| Example file | Filesystem prefix | Web accessible Prefix | Link output |
|-------------------------------|---|-----------------------|--|
| share/Sales/Info/glossary.pdf | /var/www /bluespice/w/ mounted_share/ | | https://wiki.company.local/w/mounted_ share/Sales/Info/glossary.pdf |

When a new entry is added, it has to be confirmed by clicking the checkmark next to it before saving the page.

InsertLink configuration options

BlueSpicePageTemplates

- **Force target namespace:** The page is always created in the target namespace that is associated with the template, even if the user provided a different namespace prefix. In the screenshot below, the user wants to create the page "NewPage" and then selects a template for the QM namespace. The page is, therefore, created as "QM:NewPage" if this setting is activated.

force the namespace of the template

- **Hide default templates:** Hides the default *Empty page* template.


- **Hide template if the page is not to be created in the target namespace:** Depending on the namespace prefix of the page to be created, templates that are associated with other namespaces will not be shown to the user for selection.

BlueSpicePermissionManager

- **Backup limit:** Sets the number of backups for the permissions manager. Each time the page *Special:PermissionManager* is saved, a backup is created. If the backup limit is set to 5, the last five versions of the permissions configuration are saved as backups.

BlueSpiceRSSFeeder


- **URL whitelist:** RSS feeds need to be whitelisted here by an administrator before they can be displayed in a wiki page.
- **Maximum number of allowed redirects:** If there are URL redirects for any of the whitelisted URLs, the number of redirects needs to be adjusted (usually to 1 or 2).



The screenshot shows the 'Administration' section of the BlueSpice configuration manager. It contains a 'URL whitelist' section with a text input field containing two URLs: 'https://blog.bluespice.com/feed/' and 'https://blog.hallowelt.com/feed/'. Below this is a 'Maximum number of allowed redirects' section with a numeric input field set to '0'. The entire configuration box is titled 'RSS Feed settings' at the bottom.

BlueSpiceReaders

- **Number of readers to display:** Sets the number of readers that are displayed on the Page information in the Quality management tools.



The screenshot shows a dialog box titled 'Page information for "Manual:Extension/BlueSpiceReaders"'. It has a sidebar with several tabs: 'General', 'Last edit', 'Properties', 'Expiry of page', 'Authors of this page', 'Readers of this page' (which is highlighted in blue), and 'Reminder'. The main content area is currently empty. At the bottom of the dialog, there is a pagination bar showing 'Page 0 of 0' and navigation icons.

displays readers of the page

BlueSpiceSaferEdit

- **Interval for lookup for concurrent editings:** Sets the time in seconds for checking if another person is editing the page.
- **Show name of current editor:** Shows or hides the name of the user who is currently editing the page.

BlueSpiceUEModuleBookPDF

- Table of Contents
 - *Only article titles (indent by grade):* Only shows the article titles in the main contents table of the PDF.

| Table of contents | |
|------------------------------|----|
| 1 Introduction | 3 |
| 2 Wiki pages model | 4 |
| 3 User rights | 7 |
| 3.1 Group manager | 15 |
| 3.2 Permission manager | 18 |
| 3.3 User manager | 24 |
| 4 Namespace manager | 28 |

PDF table of contents without article TOCs

- *Embed article TOCs (No indent of article titles):* Shows the table of contents for each article in the main contents table of the PDF.

| Table of contents | |
|---|----|
| 1 Introduction | 5 |
| 2 Wiki pages model | 6 |
| 1 The pages modell | 6 |
| 2 Page types | 6 |
| 2.1 Special page | 6 |
| 2.2 Content page | 7 |
| 2.3 Wiki page | 7 |
| 2.4 Category page | 8 |
| 2.5 File / image (description) page | 8 |
| 3 User rights | 9 |
| 3.1 Group manager | 17 |
| 1 Accessing the group manager | 17 |
| 2 Functionality | 18 |
| 3 Assigning roles and users to groups | 18 |

Embed article TOCs


BlueSpiceUEModuleHTML

- **Hide namespace prefix in HTML:** If activated, the namespace is shown in the HTML main heading.

Note: If the page contains a "displaytitle" tag in the page source, the page display title is shown and this setting has no effect.

BlueSpiceUEModulePDF

- **Hide namespace prefix in PDF:** If activated, the namespace is shown in the PDF main heading for a page.



Note: If the page contains a "displaytitle" tag in the page source, the page display title is shown and this setting has no effect.

BlueSpiceUniversalExport

- **Metadata (standard, JSON):** Additional data to be passed to the rendering template in JSON format. This data can be used in the export template. The template itself is maintained server-side.
- **Metadata (override, JSON):** Allows overriding standard data sent to the rendering template in JSON format. Values that are set by default can be overridden with this option.

BlueSpiceVisualEditorConnector


- **Enable VisualEditor for BlueSpice extensions**
- **Configuration variable to use a simplified save process**
- **Upload type**
 - Original (Here a confirmation of the rights of use/upload is obtained, file name and namespace of the file can be changed, a category can be assigned and a description of the file **MUST** be given).
 - Simple (No confirmation of required rights is obtained here, the name and namespace of the file can be changed, a description and a category can be assigned, but does not have to be specified)
 - One click (No confirmation about required rights is obtained here, the image cannot be renamed and no category can be assigned. Only the namespace can, but does not have to be adjusted before uploading)

BlueSpiceWholsOnline

- **Time in seconds until a user is marked as offline:** The system checks every x seconds if a user logged out and no longer displayed as online. This can be less frequent than the update interval for newly logged-in users.
- **Update interval in seconds:** The system checks every x seconds for users.

BlueSpiceExpiry

- **Show watermark for expired pages in PDF:** Shows the watermark for expired pages in PDFs.
- **Show watermark for expired pages in print version:** Shows the watermark for expired pages when a page is printed.
- **Show watermark for expired pages:** Shows a watermark on the page itself.



BlueSpiceFlaggedRevsConnector




BlueSpiceFlaggedRevsConnector is available up to BlueSpice 4.2.

Export

The export settings affect how the pages of a book are generated in the PDF export.

- **Bookshelf: List approved revisions log:** Shows a log of stable page versions of pages in the PDF and when these pages were put into accepted status. If editors did not provide a comment when accepting the page, the *Stable comment* field for a revision is empty.



| Stable date | Page | Stable comment |
|-------------|--------------------|----------------|
| 18.11.2019 | Permission matrix | |
| 18.11.2019 | Permission matrix | |
| 15.11.2019 | Wiki pages model | |
| 14.11.2019 | Permission manager | |
| 14.11.2019 | Group manager | |

accepted revisions log

- **Bookshelf: List pages without stable revision:** Displays a list of PDF pages at the beginning of the PDF that only exist as a first draft and have no released version.

| |
|--|
| <p>Not stable pages</p> <hr/> <p>QM:Checklists</p> <hr/> <p>Pages without acceptance feature</p> |
|--|

- **Bookshelf: List pages without FlaggedRevs:** Displays a list of PDF pages that do not have a release mechanism at the beginning of the PDF.

| |
|---|
| <p>Not FlaggedRevs namespace</p> <hr/> <p>Introduction</p> <p>Wiki pages model</p> <p>User rights</p> <p>Group manager</p> <hr/> <p>Pages with no FlaggedRevs feature.</p> |
|---|

- **UEModulePDF: Show FlaggedRevs info below main heading:** Prints the latest revision dates (last acceptance and last edit date) below the heading.

| |
|--|
| <p>Introduction</p> <hr/> <p><i>Stable: 06.12.2019 - 12:00 / Revision: 06.12.2019 - 11:43</i></p> <hr/> <p>FlaggedRevs info below heading</p> |
|--|

Quality assurance

- **Include handling:** If resources are embedded in a page and those resources are located in namespaces with approval mechanism, then the following settings can be selected. For example: If an approved page contains a template or a file that has been changed after the page itself has been approved, the page will not get another draft version, but instead one of two configurations applies:
 - Current versions: Always show the latest version of the embedded resource.
 - Stable versions: Always show the stable (=approved) version of a resource.
- **Show unstable pages for following groups:** If the group *user* is removed from the *BlueSpiceFlaggedRevs* configuration, users in this group will not be able to see draft versions when they are added as reviewers in a review process. When the group *user* is removed, only *sysop* and *reviewer* users can access drafts. If you want other groups, for example *editor*, to see draft versions, you need to add them to the configuration. If no user groups are specified in the configuration field, not even reviewers and sysops users will see a visual status indication of a page. They will have access to drafts through the revision history for the page instead.

Searching and Navigation

- **Indexing only stable versions:** Draft versions are excluded from the search results. If a page does not have a stable version, it is not shown as a search result.

BlueSpiceSocial

- **Show endpoint "Timeline":** Shows a link to the page *Special:Timeline* in the main navigation.

BlueSpiceSocialBlog

- **Use teaser text for blog entries in the timeline:** When you create a blog entry, you can create a teaser text for it by clicking the cogwheel symbol in the blog entry form. If this setting is active, the teaser text will be shown on the page *Special:Timeline* instead of the first part of the content.

Title
ISO 7010 Symbole

Content

Please makes sure to adhere to the ISO 2010 graphics standards¹ when using symbols in your manuals.
We still see a lot of outdated images throughout the company and will flag documents as expired if they contain the wrong images.
For questions, please contact your documentation team. Thank you!

ISO 7010 M002

Teaser

Pages in violation of ISO 2010 graphics standards will be expired

× Main Page


⚙ Cancel Post

blog teaser text


- **Show endpoint "Blog":** Shows a link to the page *Special:Blog* in the main navigation.

BlueSpiceSocialTopics

- **Automatically create all discussion pages.** If a user creates the first discussion topic for a page using the link in the page footer of a wiki page, the needed discussion page is automatically created first.




A message "This discussion page was created automatically" is inserted on the discussion page.



If this setting is deactivated, the user is directed to the "Create page" default page first.

BlueSpiceDiscovery

Deactivating the Entrypoint links



Positioning of skin elements

Elements below the page title

page-sentence X

Elements below the page content

categories X rating X recommendations X

positioning skin elements

- page-sentence: display of page status ([Approval status](#), [Expiry](#))
- categories: display of [page categories](#)
- rating: display of [page ratings](#)
- recommendations: display of [page recommendations](#)

Content Stabilization v4.3+

The following configuration options are available for page approvals:

- **Include handling (1):** Wenn Ressourcen in eine Seite eingebettet sind **und sich diese Ressourcen in Namensräumen mit Freigabe befinden**, können die folgenden Einstellungen ausgewählt werden. Es gibt zwei mögliche Einstellungen:

| | Verhalten |
|--|--|
| Stable versions of included pages | Shows the approved (stable) version of a resource, even if it was approved after the page that includes the resource was approved. (This works only if the resource is located in a namespace with active approval feature). |
| Versions that were current at the time of approval | Shows the version of the resource which was embedded at the time of the last approval of the wiki page where it is embedded. (This works only if the resource is located in a namespace with active approval feature). |

For example, if an approved page contains a template that was modified after the page itself was approved, the page will not show a draft version. Approvals work directly via the embedded resource.

- **Allow viewing of first draft version (2):** If this setting is activated, then all users with read rights can view the first draft. When disabled, only groups from the "Show unstable pages for following groups" setting can see first drafts.
- **Update semantic properties from stable pages only (3):** The property value of the page is read from the stable version of the page and not from the draft version.
- **Entwurfseiten für folgende Gruppen anzeigen (4):** If the group `user` has been removed from the configuration, users in this group will not be able to see draft versions when they are added as reviewers in a review process. In this case, only users with the roles `sysop` and `reviewer` can access drafts unless other groups are specified. These system groups can only access drafts through the site's version history.

➔ [Technical Reference: BlueSpiceConfigManager](#)

Page information


BlueSpiceArticleInfo contains meta information about a content page.

Contents

| | |
|--------------------------------------|----|
| 1 Viewing the page information | 23 |
| 2 Configuration | 23 |
| 2.1 Output | 24 |
| 3 Related info | 24 |

Viewing the page information

The list of meta information about a page is displayed in the page information of the [page tools](#).




The following information is available:

- Last edit
- Properties
- Assignments
- Expiry of the page
- Authors
- Readers
- Reminder

Configuration

In the [config manager](#), you can change the update frequency for this information. Here, you choose *Extension* from the select menu and then *BlueSpiceArticleInfo*.






Output

BlueSpiceArticleInfo, together with *BlueSpiceAuthors*, *BlueSpiceReaders*, and *BlueSpiceExtendedSearch* is part of the *Page information* in the quality management tools.

- **Update interval in seconds:** Sets the refresh rate for the "Last edit" value. By default, this date is updated every 10 seconds via JavaScript.



Related info

- [Reference:BlueSpiceArticleInfo](#)

➔ [Technical Reference: BlueSpiceArticleInfo](#)

Page info: authors


BlueSpiceAuthors displays the profile images of the users who have contributed to a wiki page.

Contents

| | | |
|-----|------------------------|----|
| 1 | Page information | 26 |
| 2 | Configuration | 26 |
| 2.1 | Output | 27 |
| 3 | Related info | 27 |


Page information

Authors of a page are listed on the *Page information* in the [page tools](#). .



Configuration


In the [Config manager](#) you can change if authors are shown on the Page information or not.



Output

BlueSpiceAuthors, together with *BlueSpiceArticleInfo* and *BlueSpiceReaders*, is part of the *Page information* in the quality management tools.

- **Display authors:** Show or hide authors on the page information page.



Authors are listed in their role of original author or subsequent editor.

Related info

- [Reference:BlueSpiceAuthors](#)



Technical Reference: [BlueSpiceAuthors](#)

Manual:Extension/BlueSpiceDiscovery/Main navigation

Contents

1 Overview 29

2 Editing the main navigation 29

2.1 Menu editor 29

2.2 Source edit mode 31

3 Deactivating standard links 31


4 Group-specific navigation 31

5 Additional customizations 32

6 Related info 32

Overview

By default, some links are provided as entry points to the wiki. Wiki administrators can deactivate these links in the [configuration manager](#) if needed. In addition, you can also add new links below the entrypoints (admin permissions required). Please note that no hierarchical links can be created. Therefore, it makes sense to mainly set up links to the most important topics and to portal pages that contain additional links or page lists.



Editing the main navigation

To open the menu editor:

1. **Click** *Edit sidebar* at the bottom of the navigation menu. If the page does not exist yet, you will see a notice on the page.

Menu editor

* Visual menu editor is available from BlueSpice 4.2.

To add a new menu header using the menu editor:

1. **Click** *Add new element* to create a new menu header.

+ Add new element

Add a new menu heading

2. **Enter** the text for your menu header. In a multilingual wiki, you can also enter a [message key](#).

Cancel

Edit element

Done

Node type
Text or message key

Edit text or message key
Text or a message key

Topics *

Enter a heading name

3. **Click** Done.

To add links:

1. **Select** *Add new subitem* from the dropdown menu of the menu header.

Quicklinks

Edit node

Remove

Add new subitem

add a link as a new subitem

2. Enter the page name as the link target and the label that you want to show:

Cancel

Edit element

Done

Edit link
Link target

IMS:Process descriptions *

Link label

Processes *

enter link info

3. **Click** Done.
4. **Repeat** steps 1-3.
5. **Click** *Save changes*.

Note: If you use the parser function `{{#ifingroup:...` to display navigation elements in the source code, you must always edit the main navigation in the source code. In visual editing mode, saving removes any parser function or semantic queries.

Source edit mode

To add new links:

1. **Change** to source editing mode.
2. **Create** one or more navigation links (with or without section heading). The following example shows a link to the page "Company" with the label "Our company" and an external link to the BlueSpice website with the label "Website". The links are grouped together under the section heading "Quicklinks":

```
*Quicklinks
**Company|Our company
**https://www.bluespice.com/de|Website
```

3. **Save** the page. The links are now shown in the main navigation.

Link labels may collide with system messages. If this is the case, simply append the HTML-code for an empty space to the description:

```
**Portal|Portal&#160;
```

Deactivating standard links

The standard links can be deactivated in the [configuration manager](#). The following settings are available under *Feature > Skinning*:

BlueSpiceBookshelf:

- Show entrypoint "Bookshelf"

BlueSpiceDiscovery:

- Show entrypoint "Mainpage"
- Show entrypoint "All pages"
- Show entrypoint "Recent changes"

BlueSpiceSocial:

- Show entrypoint "Timeline"

BlueSpiceSocialBlog:

- Show entrypoint "Blog"

Group-specific navigation

It is possible to show navigation elements for specific user groups only. Please note that the pipe symbol (|) between the page name and its label has to be escaped as `{{!}}` within this function.

This syntax is defined in the extension [UserFunctions](#).

```
{{#ifingroup:sysop,widgeteditor |
*Test2
**somepage{{!}}Some page
|}}
```

Note: Anytime the page is saved using the visual menu editor, the parser function will be overwritten and no longer works!

Additional customizations

- [Alignment for navigation with long link labels](#)
- [Display icons with navigation links](#)
- [Multi-language navigation](#)

Related info

- [Custom menu](#)
- [User menu](#)

Expiry

An article can be marked as "expired" after a certain date and is the ideal basis for an archiving system.

Contents

| | | |
|---|--|----|
| 1 | Setting an expiration date | 34 |
| 2 | Unexpiring a page | 34 |
| 3 | List of expired pages | 34 |
| 4 | Archiving obsolete pages | 34 |
| 5 | Expiration log | 34 |

| | |
|-----------------------|----|
| 6 Configuration | 34 |
|-----------------------|----|

Setting an expiration date

To set the expiration date for an article:

1. **Click** *Set expiry* in the page tools.
2. **Enter** an expiration date. It could be today or any day in the future.
3. **Enter** an expiration comment (optional).
4. **Click** *Save*

When the expiration date is reached, the page shows the expiration marker "expired" in the title area. Additionally a watermark is shown on the article by default.

Unexpiring a page

To remove the expiration marker from an article, click the drop-down arrow next to the "expired"-marker in the title area and unexpire the page.

List of expired pages

To view all pages that have an expiration date, you can go to *Global settings > Tools > Expired pages*. From there, users can remove the expiration marker of any page.

Archiving obsolete pages

Administrators can create an *Archive namespace* if obsolete pages should be archived rather than deleted. Users can then [move](#) articles to this namespace.

Expiration log

Administrators can view a log with all expiration activities from the page *Special:Log*.

1. **Select** the log type *Expiry* from the drop-down menu.
2. **Click** Show.

Configuration

You can set the following options in the Config manager.

Additionally, the display of the expiry status can be moved after the page content in the [Config manager](#).



[Technical Reference: BlueSpiceExpiry](#)

Search

ExtendedSearch replaces the default MediaWiki search engine. It is based on the [OpenSearch](#) (up to BlueSpice 4.3 the Elasticsearch) engine. Pages and files are indexed immediately and available for searching in real-time.

Contents

| | |
|---|----|
| 1 Usage | 36 |
| 2 Quick search | 36 |
| 2.1 Recently viewed v4.4.1+ | 36 |
| 2.2 Title search | 36 |
| 2.3 Namespace and subpage "pills" | 37 |
| 2.4 Dates as search terms | 38 |
| 3 Search Center (extended search) | 38 |
| 3.1 Search operators | 39 |
| 3.1.1 AND | 39 |
| 3.1.2 " (apostrophes) | 39 |
| 3.1.3 NOT | 39 |
| 3.1.4 OR | 40 |
| 3.1.5 * (wildcard) | 40 |
| 3.2 Elements | 40 |
| 3.2.1 Results relevance | 42 |
| 3.2.2 Exporting search results | 42 |
| 4 Configuration | 42 |
| 5 SearchAdmin | 44 |

Usage

Extended search offers two ways of searching for content:

1. **Title search** using the [Quick search](#)
2. **Fulltext search** using the [Search center](#)


By default, the search indexes:

- **wiki pages**: all content pages, except for pages in the MediaWiki namespace
- **special pages**: all pages in the namespace *Special*
- **repo files**: files uploaded to the wiki - for text files like Word documents and PDFs, this includes content and metadata
- **external files**: files from arbitrary locations from accessible storage paths (e.g., mounted drives)
- **social entities**: entities (=pages) created by the [BlueSpiceSocial](#) extension, such as blog posts and user profiles

Quick search

Recently viewed v4.4.1+

When you place the cursor in the search field, it returns a list of pages that you have found and accessed through a recent search. Any suggested pages that you are not interested in, you can remove from this view by clicking on the to the right of the page name. Once you start typing, the default suggestions disappear.



Title search

The most prominent search feature is the search box in the header of the wiki. If a user has not switched to the search center yet, this field simply looks for a page name or display title that contains the exact search term. The title search does not do a full-text search. You have to switch to the full-text search (= [Search center](#)) for that. This can be done by simply pressing the key after entering a search term in the Quick Search field.

What users should know about this search field (- you can try the following searches in this helpdesk):


1. It is **not case-sensitive**: "qual" or "Qual" return the same results.

2. The search term needs to be at the **beginning of a word**: the search term "ards" will not return pages that contain "cards".
3. Search results are **limited to 7 page titles**. This is important to understand to have the right expectations. In most cases, the search field is simply used as a springboard to pages that are known to the user (e.g., to jump to a team page or to the page "Processes" or any other known page the user wants to reach quickly).
4. **Spelling mistakes** will not return any results: "Qality" does not return "Quality".
5. Multiple search terms can be in **any order** to produce results ("toc download" finds pages just like "download toc").
6. **Search operators** such as `" "`, `OR`, `AND` are not supported. However, they are supported in the [full-text search](#).
7. The **sort order** for the results are based on a combination of best title match and last edit date of the page. (You can find the technical details on the [reference page for the extension ExtendedSearch](#). Some configuration changes are possible if the wiki is hosted on premise. There are no configuration options in Cloud wikis.)



Namespace and subpage "pills"


The search bar supports pills for namespaces and subpages.



If a user types `Manual:` and clicks "Enter", a pill for the namespace "Manual" appears and the search for the following term is limited to this namespace. . Subpage pills work in the same way. If the user types in `PageName/`, any term after that is matched in the context of that page. If you search for "TestPage/Te", for example, the search will match only subpages of "TestPage" that contain "Te" in the title, like "TestPage/Test" and "TestPage/TestSubpage".


Dates as search terms


The search recognizes certain date formats. In the search center, these date formats are treated with surrounding quotation marks.



Search Center (extended search)

As soon as you trigger the full-search with the magnifying glass symbol or the *Enter* key, the wiki switches to the Search Center. This is a special page that offers the full functionality of the search. The search in the Search Center is carried out using the same search bar that is also used for autocomplete. Here, the search engine carries out a full text search, which also includes the metadata of documents. It does not index the wikitext of a wiki page, but rather the rendered content, that is the output by the browser.





Search operators

Important! Search operators only work in the search center (fulltext search). You cannot use search operators in the title search.

If you are **searching for contiguous words**, they should be enclosed in quotation marks (") for performance reasons and to support a unique search.

Search operators have to be written in **all-caps**.

AND

- `admin AND docu`: Returns pages that contain the **exact term** `admin` **as well as the exact term** `docu`.
- `admin* AND docu`: If the term `administration` should be found, you need to provide a wildcard asterisk (`*`).

Compare: The search `admin docu` automatically is a wildcard search. It returns pages that contain **both** `admin*` **and** `docu*`. This search normally finds more results than the search `admin* AND docu` (because in the second case, the exact term `docu` is returned).

" (apostrophes)

Apostrophes around a search term triggers an `AND` search for **all terms** in the query:

- `"admin" docu`: same result as `admin AND docu` (i.e., also the precise term `docu` will be searched).

NOT

- `admin* NOT docu*`: Returns pages that contain words that start with `admin`, but that don't contain words that start with `docu`.

OR


- `admin OR docu` : Returns pages that contain **either the exact term** `admin` **or the exact term** `docu` .

***** (wildcard)


- `admin*` : Returns pages that contain words that begin with `admin` .


Elements

- **Hit count** - shows how many matches a search has returned. It may be exact or approximate. Approximation is due to dynamic check for permissions to view each page in the results, some results may not be shown to the user with no adequate permissions event if it matches the search term.
- **Tools** - these are located in the top right as a set of buttons:
 - Create a page - represented by a "plus" button - will create a page with current search term as a title (only visible if user has permission to create pages)
 - Add filters - represented by a "funnel" icon - opens a dialog where users can select the type of filter to apply to the search.




- Search options - represented by a "gear" icon - opens a dialog where users can change settings for the current search. It provides options like the number of results per page, sorting field and order.





- Export search - represented by the "export" icon - opens a dialog to export current search results to a dedicated page (only visible to authorized users, by default admin users).
- **Filter:** Filters are displayed in form of pills below the results counter. Each filter pill represents a different attribute. Filter values can be changed by clicking on the filter pill and selecting the desired options from the popup that will open. Filter can be removed by clicking on the "x" button in each pill.



- **Results:** If current search criteria field any results, a list of results is displayed. The information available in the results is depending on the result type):
 - Main title of the result (page title, file name...)
 - Result type
 - Size and extension (for files)
 - Thumb image (for images) or file type icon (for other file types)
 - Redirect information
 - Original name (for wikipages, if the page display title is different than the actual page title)
 - Secondary information like page categories, modification and creation date, author, etc.

- Snippet of the matches in the content of the page (if there are matches in the page content),
- Sections with matches in the content (for wikipages)

In case there is an exact match for a given search term, the result that matches exactly is displayed as a "featured" result. Such a result displays a preview image of the page and always displays the content snippet, regardless of whether there are matches in the content or not.


Results relevance

All logged-in users can mark certain results as "favorites" by clicking on the star symbol in the right corner of each result. Files marked as "favorite" will score higher in future searches - this is not visible immediately, however, but happens over time. One user's relevance settings won't affect other user's searches. Results can be unmarked as "favorite" by clicking on the "star" symbol again.

Exporting search results

After executing the search, administrators can export (save) the results to a specific page using the "Export" command from the "Tools" menu. The list is exported to *MediaWiki:PageCollection /LISTENNAME*.

Only valid wikipages are exported. The pages contained in a list can be included in a book in the book function via *Mass add> Source: Page collection*.




Configuration

In the [BlueSpiceConfigManager](#), under settings for the extension *BlueSpiceExtendedSearch*, the following configuration options are available:

- **External file paths:** External locations to scan for and index files from. These locations are entered in key/value pairs of Physical path and URL prefix.
 - *Physical path:* Storage path. For mounted drives, for example: *X:|Documents*
 - *URL prefix:* All files indexed from the indexed physical location are prefixed in the search results. It should be used if files are available from a web server. By default, the URL prefix is set to the same value as *Physical path*.

| Example file | Phys. Path | URL Prefix | Link in results list |
|--|---|--|--|
| S:\Sales\Info\glossaryy.pdf | S:\ | file:///S:/ | file:///S:/Sales/Info/glossary.pdf |
| | | https://sharepoint /Sales/ documents/ | https://sharepoint/Sales/ documents/Sales/Info /glossary.pdf |
| | | https://intranet /showdocs inline.aspx?path= | https://intranet/showdocsinline. aspx? path=/Sales/Info/glossary.pdf |
| /var/www/bluespice/w /mounted_ share/Sales/Info /glossary.pdf | /var/www /bluespice/w/ mounted_share/ | | https://wiki.company.local/w /mounted_ share/Sales/Info/glossary.pdf |

- **Use simple autocomplete:** forces a more compact autocomplete (1-column Sales thumbnail preview).



- **Automatically set language filter:** The search only returns pages whose language (PageLanguage) is identical to the user language (Language). Users can set their language in their [preferences](#). By default, the language of content pages is the same as the installation language (ContentLanguage) of the wiki. Some extensions can set the language of individual pages independently of the content language of the wiki.. (See: https://www.mediawiki.org/wiki/Manual:Language#Page_content_language). In many wikis, activating this filter has little effect.
- **Exclude patterns:** Files at external file locations can be excluded from search based on regular expression patterns.

SearchAdmin

Special:SearchAdmin is a special page for wiki admins and shows the number and types of indexed documents. `{{Box Links-en|Topic1=`

➔ [Technical Reference: BlueSpiceExtendedSearch](#)

Ratings and recommendations

The extension **BlueSpiceRating** allows users to rate a page with up to five stars or to recommend the page.

Contents

| | | |
|-----|--|----|
| 1 | Rate or recommend a page | 46 |
| 1.1 | Rating | 46 |
| 1.2 | Recommendation | 46 |
| 2 | Enable ratings or recommendations in a namespace | 46 |
| 3 | Special pages | 47 |
| 4 | Deactivate ratings on a page | 48 |
| 5 | Related info | 48 |

Rate or recommend a page

Before a user can rate or recommend a page, [each feature needs to be activated](#) by an administrator.

Rating

A user simply selects the amount of stars for a rating at the end of a wiki page. The number of stars are then highlighted in yellow during the selection process. A mouse-click confirms the rating. Only one rating per user is counted. New votes only change the average evaluation, but not the number of ratings. Users can change their rating at any time by choosing less or more stars.

The display of the ratings and recommendation features can be [moved to the title area in the Config manager](#).

Recommendation

To recommend a page, a user clicks on the link "Recommend" at the end of the page. To retract the recommendation, the user clicks on the link again.

The screenshot shows the 'Sandbox' page in BlueSpice. At the top, there's a 'Related files' section with a table listing files. Below this, there are two sections: 'Ratings and recommendations'. The 'Ratings' section shows a star rating of 5 stars (1) with a green checkmark. The 'Recommendations' section shows a blue flame icon, 'Recommended (1)' with a green checkmark. Both the star rating and the recommendation status are circled in orange in the original image.

| File | Latest version | Editor |
|-----------------|----------------|--------|
| Regensburg.docx | 12. July 2022 | Vhoesi |


No categories assigned

★★★★★ (1) ✓

Recommended (1) ✓

Enable ratings or recommendations in a namespace

Administrators can activate both features for individual namespaces. To enable or disable them, go to *Global actions > Namespace manager* and edit the namespace settings:



Cancel
Edit namespace
Done

Namespace name: (Pages)

Alias:

☒ Subpages

☒ Content namespace

☐ CategoryCheck

☐ Secured page assignments

☒ PageTemplates

☒ Visual editor

☒ Rating

☒ Recommendations

☐ Read Confirmation

☒ Semantic MediaWiki


☐ Approval

Special pages

The special page `Special:Rating` lists all pages that have been rated.

The special page `Special:Recommendations` lists all pages that have been recommended.

Both pages can be accessed from the Global actions menu.



Deactivate ratings on a page

Users can also exclude individual pages from the rating system. For this, insert the following behavior switch at the bottom of the page in source view:

```
__NORATING__
```

Related info

- Reference:BlueSpiceRating

➔

Technical Reference: BlueSpiceRating

➔

Technical Reference: BlueSpiceRating

Page info: readers

The extension **Readers** displays the readers of a wiki page.

Contents

1

Viewing the readers of a page

49

2

Configuration

49


3

Related info

49

Viewing the readers of a page


Users must have admin rights to see the readers of a page. The list of readers is shown on the page information, which can be accessed from the [page tools](#).



Admin users can also access the page *Special:Readers/Page_Name*. This special page shows the list of all readers of a page with the date of their last visit.

Configuration

In the [Config manager](#), wiki admins can change the settings for this feature. Here, the number of readers to be shown in the flyout can be changed (defaults to 10).




Related info

- [Reference:BlueSpiceReaders](#)

[➔ Technical Reference: BlueSpiceReaders](#)

Manual:Extension/FlaggedRevs

 FlaggedRevs is available up to BlueSpice 4.2.

FlaggedRevs is a MediaWiki extension that activates an approval mechanism. New versions of a page are initially marked as drafts and remain so until a user with *review* rights approves the page.

Contents

1

Activating the acceptance feature

51

1.1

Existing pages

51

1.2

New pages

52

2

Accepting a page

52

3

Setting read permissions for drafts

53

4

Changes to embedded templates and files

55

4.1

Ignoring changes to embedded resources

55

5

Effects on Semantic MediaWiki properties

56

6

Quality management overview

56


7

Related info

57


Activating the acceptance feature

Activating the acceptance feature is done on the namespace level. A user with admin permissions activates the feature in *Global actions > Management > Namespace manager* for individual namespaces. The dialog window opens after clicking the edit icon (wrench) in the *Actions* column. Select *Approval* and click *Done*.



Existing pages

After activating *Approvals* for a namespace, all pages in the namespace are set into *first draft* mode.



Each page in the namespace now displays the acceptance status in the title area.

The display of the acceptance status can be moved after the page content in the [Config manager](#).

New pages

When a new page is created and first saved, it will automatically be visible to all users. Subsequent page edits will be collected in the draft version of the page. If a page is edited and saved multiple times while in draft mode, each edit gets logged in the version history:



The screenshot shows a list of draft revisions for the page 'WikiSysop'. The revisions are listed in a table-like format with columns for actions (cur, prev), timestamps, user avatars, usernames, and edit summaries. The first two revisions are highlighted with orange borders and marked as 'pending review'. The third revision is marked as '2017 source edit'. Below the list is a button 'Compare selected revisions' and the text 'Draft revisions'.

| Action | Timestamp | User | Size | Summary | Status |
|----------------|------------------------|-----------|----------------------|--|----------------|
| (cur prev) ● | 14:04, 4 November 2019 | WikiSysop | (1,332 bytes) (+486) | (Tag: Visual edit) | pending review |
| (cur prev) ● | 14:03, 4 November 2019 | WikiSysop | (846 bytes) (+213) | (Tag: Visual edit) | pending review |
| (cur prev) ○ | 13:36, 4 November 2019 | WikiSysop | (633 bytes) (+38) | (Tag: 2017 source edit) | |
| (cur prev) ○ | 12:45, 4 November 2019 | WikiSysop | (595 bytes) (+595) | (Created page with "FlaggedRevs is an extension to the MediaWiki software that allows a wiki to monitor the changes that are made to pag...") (Tag: Visual edit) | |


Compare selected revisions

Draft revisions

The revisions in draft status have a dotted border and are highlighted in orange. In addition, they are marked as *pending review*. These revisions can be compared before the pending changes of the page are accepted.

Accepting a page

Users with *review* rights can accept a draft page any time they save a page (*Accept this unreviewed page*):



The screenshot shows the 'Working with Drafts' page in a MediaWiki interface. The page title is 'Working with Drafts'. The main content area contains text about the 'FlaggedRevs' extension. On the right side, there is a sidebar with a 'Summary' section, a 'Watch this page' checkbox, and an 'Accept this unreviewed page' checkbox. The 'Accept this unreviewed page' checkbox is highlighted with a yellow circle. Below the sidebar, there is a 'Review your changes' button. The page footer includes links for 'Privacy policy' and 'About nextminor.bluespice.test.hw.local', and a 'MediaWiki' logo.

Working with Drafts

FlaggedRevs® is an extension to the MediaWiki software that allows a wiki to monitor the changes that are made to the content that is displayed to the wiki's readers. Page changes that have been reviewed and found to meet whichever criteria the wiki has set are then visible to those users to review new changes. A wiki can use a scale of such flags to indicate the level of review.

Privacy policy | About nextminor.bluespice.test.hw.local

MediaWiki

Summary:

Describe what you changed

☐ Watch this page

☒ Accept this unreviewed page


Please note that all contributions to nextminor.bluespice.test.hw.local may be edited, altered, or removed by other contributors. If you do not want your writing to be edited mercilessly, then do not submit it here. You are also promising us that you wrote this yourself, or copied it from a public domain or similar free resource (see Nextminor.bluespice.test.hw.local:Copyrights for details). Do not submit copyrighted work without permission!

Review your changes

Accepting pending changes


If the page is not accepted at this point, it can be accepted independently from the editing process.

A user with *review* rights can accept the page quickly with the review feature in the title section of the page. The draft message will display an arrow which includes the *accept* function:



When accepting the page, the reviewer can leave a comment. This comment will then be shown in the version history of the page.

The page status now shows the page version as accepted.



Setting read permissions for drafts

By default, all users can see the drafts of a page, even readers.

To hide drafts from readers, the group *user* has to be removed from the configuration. An administrator deletes the group user from "Show unstable pages for the following groups" in *Global actions > Management > Config manager*.

Config Manager

Feature ▼ | |

☐ Export

☐ Skinning

☐ System

☐ Searching and Navigation

☐ Data analysis

☐ Personalization

☐ Book

☐ Content structuring

☒ Quality assurance

☐ Administration

☐ Editor

BlueSpiceChecklist

☒ Mark checklist changes as minor edit

BlueSpiceExpiry

☒ Show watermark for expired pages

BlueSpiceFlaggedRevsConnector

☒ Automatically set the page to stable, when the workflow was finished successfully

☒ Automatically delete the workflow, when a page was marked as stable

Show unstable pages for following groups


Warning! If the group *user* is removed from the *BlueSpiceFlaggedRevs* configuration, users in this group will not be able to see draft versions when they are added as reviewers in a review process.


When the group *user* is removed, only *sysop* and *reviewer* users can access drafts. If you want other groups, for example *editor*, to see draft versions, you need to add them to the configuration and save it:

The two checkboxes *Automatically set the page to stable...* (checkbox is available until version 3.1.) and *Automatically delete the workflow...* determine what happens at the end of a workflow, if there is an active [Review](#) for a page. A page can be set to accepted status by a workflow and the workflow can be deleted after the page is marked as stable.

Note: If no user groups are specified in the configuration field, not even reviewers and sysops users will see a visual status indication of a page. They will have access to drafts through the revision history of a page instead.

Anyone with edit permissions will receive a notification that there are pending changes for the page when they access the page in edit mode:





Changes to embedded templates and files

If a page uses templates or contains other files such as images and embedded PDFs and these files have been modified since the page was approved, those changes must also be approved. The wiki can be set up in two different ways to achieve this approval:

- 1. The embedded resource is located in a namespace without approval feature** If the embedded resource is in a namespace without its own approval function, the resource version at the time of the page approval is displayed. The draft version of the page shows the most recent version of the embedded resource. To approve the resource change, the page itself must be approved again. The approval has to be done on all pages that have this resource embedded.
[Information about automatic mass approval via server script.](#)
- 2. The embedded resource is located in a namespace with approval feature:** The pages that include the changed resource do not give any indication that the resource has been changed. Which version of the included resource is displayed depends on the configuration of the wiki:

| Setting | Description |
|---|--|
| Stable versions FR_INCLUDES_STABLE (default) | Always shows the approved (stable) version of a resource, even if it was approved after the page that includes the resource was approved (this works only if the resource is located in a namespace with active approval feature). |
| Current versions FR_INCLUDES_CURRENT | Always shows the latest version of the included resource (as if approvals was not activated in the resource namespace). |

Ignoring changes to embedded resources

If the *Current versions* option is selected under "Include handling" in the config manager and the resource namespaces **do not** have approvals activated, changes to these resources are ignored on the approved pages. This should be communicated to wiki users and quality managers accordingly.

BlueSpiceFlaggedRevsConnector
Show unstable pages for following groups

user X

Include handling

Current versions

Current versions

Stable versions

Ignore changes to embedded resources

Effects on Semantic MediaWiki properties

If a namespace has SemanticMediaWiki [Semantic MediaWiki](#) activated, the following SMW queries are available depending on the approval status of the page:

| Document state | Available properties |
|-------------------------------|---|
| First draft | Current values |
| Approved | Values of the approved (stable) version |
| Draft | Values of the approved (stable) version (default setting) |
| Implicit draft ^[1] | Values of the approved (stable) version |

The availability of the semantic properties is determined by the following configuration setting:

```
$bsgFlaggedRevsConnectorStabilizeSMWPropertyValues = true;
```

The value for this setting can be set to *false* in the *LocalSettings.php* of the server file system. If set to *false*, the property values of the draft version are used for semantic queries instead of the values for the stable version.

Quality management overview

The Special page *Special:Quality_management_overview* allows all users to view and filter a list of wiki pages and their review status. Pages for which a user does not have read permissions are not shown.

Quality management overview

Export table ▾

| Page title | State ↑ | Page categories |
|--|----------|----------------------------|
| Manual:What is a wiki | Approved | |
| Manual:Create pages | Approved | organiz... |
| Manual:Subpage | Approved | organiz... |
| Setup:System requirements | Approved | |
| Setup:Release Notes | Approved | Setup |
| Setup:Download | Approved | Setup |
| Setup:Release History | Approved | Setup |
| Setup:Portal | Approved | |
| Manual:Getting started - Login and configuration | Approved | Manual |
| Manual:Using the Version History | Approved | |

↑ Sort Ascending

↓ Sort Descending

Columns >

Filters >

☒ First draft
☒ Draft
☒ Approved
☐ Not enabled
☒ Implicit draft

Special page [Quality management overview](#)

Related info

- [Quality management tools](#)
- [Reference:FlaggedRevs](#)
- [Reference:BlueSpiceFlaggedRevsConnector](#)
- [Manual:Semantic MediaWiki](#)

1. ↑ An approved page has an implicit draft, if there have been changes to embedded resources (e.g., a template or an image) since the last page approval.

➔ [Technical Reference: FlaggedRevs](#)

Customizing the user interface

Contents

1 Access 59

2 Logo and Favicon 59

2.1 Logo 59

2.2 Favicon 60

3 Layout colors 60

4 Content 62

4.1 Colors 62

4.2 Font 62

4.3 Layout 62

4.4 Headers 62

5 Free CSS 63

5.1 Neutral page tools (right sidebar) 63


5.2 Neutral top bar backgrounds and hovers 64

Access

You can access the special page (*Special:FlexiSkin*) for customizing the skin from the *Global actions* menu:

⚙️ (*Global actions*) > *Management* > *Skin*

The page allows you to customize the logo, favicon, colors and font settings of the wiki. To edit the page, you need *admin*-rights in the wiki.




Important! If you don't see the changes in the wiki after saving your settings, you need to clear your browser cache (**Ctrl** + **F5**).


Logo and Favicon

Logo

To upload your logo:

1. **Click** *Select a file* to choose a file from your file explorer **or drag the file** into the dotted area of the Logo upload area.





2. **Click** the *Preview* button on the page and check the placement of the logo.
3. **Click** *Save & activate*. The logo is now visible for all users.


To use **a different logo**, click the "x" symbol in the upload area of the logo and repeat the steps above.

Favicon


The favicon is the image that is shown in the browser tabs. Follow the [steps for uploading a logo](#), just use the favicon upload area instead.

Layout colors

Here you can adjust the colors of the individual layout areas.




- **Header color (3):** Color settings for the header bar. These colors also apply to the mega menus.



- **Sidebar colors (4):** Color settings for the main navigation and the page tools.
- **Footer colors (5):** Color settings for the footer.

The following options to enter a color value are available:

- **Standard color palette:** A standard color can be selected by clicking on a color preview.



- **Pencil symbol:** Click on the pencil symbol to select a color from the color mixer.
- **Manually entering a value:** To provide a custom value (e.g., your for your CI colors), enter the hex-value for the color.

If you delete a color and FlexiSkin is saved with one or more empty color values, the standard colors of the Discovery skin are saved as values instead.

Standardfarben des "Discovery"-Skin

| | Background | Foreground | Highlight |
|--------|------------|------------|-----------|
| Header | #ffffff | #252525 | #3e5389 |

| | Background | Foreground | Highlight |
|---------|------------|------------|-----------|
| Sidebar | #f1f3f9 | #252525 | #3e5389 |
| Footer | #d3d3d3 | #454545 | - |

Content

These settings apply to all styles of the content area of a wiki page:

Colors

Here you can adjust the background, font and link colors. Broken links in the wiki are shown in red by default so that they can be easily identified. You should carefully consider whether you want to deviate from this convention. If you want to color visited links differently than standard links, you can insert the following setting in the Free CSS area:

```
#mw-content-text a:visited,[class^="mw-content-"] a:visited {color: #951b81;}
```

Font


The font settings only apply to the text in the content area. The text in other areas such as B. in the navigation and toolbars or in the menus is not affected.


Layout

If you want to change the layout width just test it on many devices to make sure your setting works as intended. Other wiki users work with different display settings and can be negatively affected by this change. Unless you have a specific reason to change the content width, you shouldn't adjust this setting. The standard content width is 61.25 rem.

Headers

You can adjust the color, font size and underlining for all heading levels. You can also change the unit for the font settings (e.g. *px* instead of *rem*). If you are not familiar with the differences between these units, just leave the default setting, *rem*. This is based on the superordinate size setting in the wiki. In contrast, *em* sizes are in relation to the enclosing container.





Free CSS


Note: If the same styles are defined in both FlexiSkin or FlexiSkin Free CSS and in MediaWiki:Common.css, the styles from Common.css are applied.

For additional customizations that are not possible with the FlexiSkin settings, you can use the *Free CSS* field if you are familiar with CSS. Here are some examples.

Neutral page tools (right sidebar)


If you select a color for your left navigation bar, you sometimes don't want the color to be applied to the right sidebar (the page tools). To keep the light-grey background, add the following Free CSS:

```
/*right sidebar*/
#sb-sec-cnt {background-color:#efefef; color:#252525;}
#sb-sec-cnt .card-header.menu-title {color:#747474;}
```




Neutral top bar backgrounds and hovers

When you set the header highlight color, it can happen that the automatically calculated values for the searchbar as well as the button hovers and backgrounds don't fit your needs.



In this case, you can neutralize them to grey.



Add the following Free CSS:

```
/*top bar neutral search box, button backgrounds and hovers */
#nb-pri form input, #nb-pri form button{border-color:#f1f3f3}
#nb-pri form input, #nb-pri form button,#sb-pri-tgl-btn, #sb-pri-tgl-btn:hover,.mws-
dropdown-primary.dropdown-menu a:hover,a.ico-btn:hover, a#sb-sec-tgl-btn, #nb-pri form
.bs-extendedsearch-searchbar-clear {background:#f1f3f3}
.mws-button-primary:hover {background-color:#747474; color:#fff}
/*top bar neutral bottom border*/
#nb-pri {box-shadow: 0 0 4px 0 #747474}
.card.mega-menu {box-shadow: inset 0 2px 3px -2px #747474}
/*mega menu neutral bottom overlay*/
@media (min-width: 768px){.dropdown-menu.megamenu .mm-bg {background-color:#747474}}
```

➔ [Technical Reference: FlexiSkin](#)


Images

Contents


- 1 How to insert an image on a page 67
 - 1.1 Details 68
 - 1.2 General settings 70
 - 1.3 Advanced settings 71
- 2 Inserting images with drag-and-drop 74
 - 2.1 Drag-and drop settings v4.3+ 75
- 3 Images and namespaces 75
- 4 Changing an embedded image 75

How to insert an image on a page

In addition to text, images are probably the most important components of typical content pages. With VisualEditor, the images can be uploaded, inserted and formatted all in one step. Images are inserted via the menu item *Insert > Media*.




The dialog box *Media Settings* opens.



After uploading, you can edit the image settings: Details, General Settings, and Advanced Settings.

Details



Media settings

Back Save

Content cell

Details

Target namespace

(Main)

Name

content cell *

A unique descriptive title for the file, which will serve as a filename. You may use plain language with spaces. Do not include the file extension.

Description

Briefly describe everything notable about the work. For a photo, mention the main things that are depicted, the occasion, or the place.

Categories

Ac

Media settings

Here you can assign a namespace and categories to a picture.


- **Target namespace:** The picture can be assigned directly to a namespace. The access rights of the namespace are also applied to the image. This means that only users with access to the namespace can view the image on the wiki.
- **Name:** Choose a name that makes it easy to find the image later during an image search. Or simply leave the current file name.
- **Description:** The description is mainly useful for photos or infographics when the image name does not adequately describe the image content.
- **Categories:** Here, the picture can be assigned to categories.

Note: When uploading a new file, you should check the file/page name for unusual special characters (e.g., " , % , / , < , > , [,] , { , }). Change the name to include only standard characters, since the server file system could have problems with them or since some characters have special meanings in MediaWiki.

The special characters (,) , & , + can be used and are translated into their equivalent %-hex notation.


: will be converted to spaces, unless it is part of an existing namespace prefix.

Error message when saving: If the image already exists, an error message is displayed. If you want to overwrite the existing file, you can click on the file name and overwrite the file via the image page in the wiki. This is done by clicking the "Upload a new version of this file" link in the "File Versions" section. In VisualEditor itself overwriting an image does not work.



Upload error

General settings



In the general settings, the image descriptions are added.

Caption: The caption is shown with framed images and thumbnails. Note: If you change an image to frameless and then back to "framed", you need to re-enter the caption.

Alternate text: The alternate text should be entered for each image since it replaces the image in certain contexts. For example, this so-called "alt" text is used by users who work with screen readers. Screen readers are used by users with visual limitations, but search engines can also read this text. In some business areas, the indication of the "alt" text is also required by law. If you are not sure, ask your company accordingly.

Advanced settings


Advanced settings: position (image alignment), image type, image width and image height



In the advanced settings, you can set the position (image alignment), image type, image width and image height.


The following settings are possible:

- **Position:**
 - Wrap text around this item: If unchecked, the image is left-aligned between two paragraphs. If checked, one of the following positions can be selected:
 - *Left*: The image is displayed on the left side of the text. The content surrounds the image.
 - *Center*: The image is displayed centered between two paragraphs.
 - *Right*: The image is displayed to the right of the text. The content surrounds the image.
- **Image type:** If you insert an image with VisualEditor, the image is usually linked to the Media Viewer. To suppress the link on an image, you must add an empty link attribute to the image tag in the source code:
 - frameless picture with link (standard): `[[File:adult-chair-company-380769.jpg|frameless]]`
 - frameless picture without link: `[[File:adult-chair-company-380769.jpg|frameless|link=]]`

| Image type | Output | Description |
|------------|--------|--|
| | | The preview picture shows the image with a |

| Image type | Output | Description |
|------------|---|--|
| Thumbnail | <div><p>This is the caption</p></div> | <p>standard width of 300px. The width can be adjusted as required.</p> <p>In addition, the caption is displayed below the picture. A preview icon indicates that the image can be viewed in a larger size.</p> |
| | | <p>The frameless version shows the picture without a frame. The width can be adjusted as required (here we set the example to 300px).</p> <p>The caption does not appear below the picture.</p> <p>By default, the image is inserted</p> |

| Image type | Output | Description |
|------------|---|---|
| Frameless |  | <p>without text wrapping. It will break up a sentence exactly where it is inserted. By default, the image is centered.</p> <p>However, the image size and position can be adjusted as needed.</p> |
| Frame |  <p>Dies ist die Beschriftung</p> | <p>The framed version is similar to the preview picture. Compared to the preview, the magnifying glass symbol is not displayed and the image is inserted on the page full-size.</p> <p>The size cannot be adjusted.</p> |


| Image type | Output | Description |
|------------|---|---|
| Basic |  | <p>The basic version is like the frameless version.</p> <p>By default, text does not wrap, but the text is separated at the point where the image was inserted.</p> <p>The image is inserted in full width, while the frameless image is inserted in miniature image width (300px). The size can be adjusted.</p> |

- **Image size:**

- *Standard:* sets the image width to 300px (unless the standard width has been changed in the [user preferences](#)).
- *Custom:* allows setting a custom size.
- *Make full size:* resets the size to the actual image size. **Note:** An image cannot be set to a larger dimension than the actual image dimension.

Inserting images with drag-and-drop

In visual edit mode, an image can be dragged directly from the file folder into the wiki with the mouse. It is important that the position for inserting the image shows a horizontal line before you drop the image. Otherwise the image will not be uploaded or inserted.



Drag-and drop settings v4.3+

The standard image settings that should be applied when placing an image via drag-and-drop can be adjusted in the [Config Manager](#).

Images and namespaces

You can save pictures and files in the general namespace (*pages*). If pictures should be accessible by all users, you can save these pictures in the main namespace if other namespaces have access restrictions. If you have created additional namespaces, you can also save images in these namespaces if you have the necessary access rights. Images are then only shown to users who have the necessary read permissions in these namespaces.

In the upload dialog, the namespace field always suggests the namespace of the current page for the image upload.

Changing an embedded image

Different image: In the editing mode of the page, it is possible to edit the image with a double-click. Use the "Change image" button to exchange the image with a different image.

Same image with different version: If you want to use a new version of the same image, open the "Special:Upload file" page in a new browser tab (so that you don't lose any changes on your wiki page). There, you can save already existing pictures with the same name again. The original image is kept as a version.

Personalization

Contents

| | |
|---------------------------------------|----|
| 1 Accessing preference settings | 77 |
|---------------------------------------|----|

| | | |
|------|---|----|
| 2 | User profile | 77 |
| 2.1 | Basic Information | 77 |
| 2.2 | Internationalisation | 77 |
| 2.3 | Signature | 77 |
| 2.4 | Email options | 77 |
| 2.5 | WebDAV | 78 |
| 3 | Appearance | 78 |
| 3.1 | Skin | 78 |
| 3.2 | Reading preferences | 78 |
| 3.3 | Date format | 78 |
| 3.4 | Time offset | 78 |
| 3.5 | Files | 78 |
| 3.6 | Diffs | 80 |
| 3.7 | Advanced options | 80 |
| 3.8 | Bookshelf special page | 81 |
| 3.9 | Context menu | 81 |
| 3.10 | Dashboards | 82 |
| 3.11 | Video player | 82 |
| 3.12 | Timeline | 82 |
| 4 | Editing | 82 |
| 4.1 | General options | 82 |
| 4.2 | Editor | 83 |
| 4.3 | Preview | 84 |
| 4.4 | Reminder | 85 |
| 4.5 | Timeline | 85 |
| 5 | Recent changes | 85 |
| 5.1 | Display options | 85 |
| 5.2 | Advanced options | 86 |
| 5.3 | Changes shown | 86 |
| 5.4 | Edit review | 86 |
| 6 | Watchlist | 87 |
| 6.1 | Edit watchlist | 87 |
| 6.2 | Display options | 87 |
| 6.3 | Advanced options | 87 |
| 6.4 | Changes shown | 88 |
| 6.5 | Watched pages | 88 |
| 6.6 | Token | 89 |
| 7 | Notifications | 89 |
| 7.1 | Email options | 89 |
| 7.2 | Notify me about these events | 90 |
| 7.3 | New message indicator | 90 |
| 7.4 | Notifications on namespace events | 90 |
| 7.5 | Notifications on categories | 90 |
| 7.6 | Review | 90 |
| 8 | Extended Search | 90 |
| 9 | Semantic MediaWiki | 90 |
| 10 | Resetting all preferences | 91 |


Accessing preference settings

1. **Click** on the user menu.
2. **Click** *Preferences*. This opens the preferences page with multiple tabs.

Alternatively, you can access the page *Special:Preferences* directly.

User profile

Basic Information



- **Real name:** This name is shown throughout the wiki. When users hover over your real name, your profile picture and contact information is shown.
- **Change password:** If your wiki is not connected with the central authentication system of your company, you can manage your password here.
- **User image:**
 - *User image* text field: Enter the webaddress of a picture on another website and click *Save* at the bottom of the page. The profile picture points directly to the external image:
 - *Change profile picture* link: Upload an image to the wiki. Click *Browse* and then *Upload* to create a new profile image. If you click *Generate new avatar*, the system generates a graphic instead.
- **Privacy policy** acceptance checkbox: Select and save this checkbox setting to confirm that you accept the privacy policy. Administrators can review this setting for all users on the page *Special:Privacy_Admin*.

Internationalisation

- **Language:** Users can change their personal language that is used in the layout and menus. BlueSpice currently supports de-formal-German (formal), de-German and en-English.
- **How do you prefer to be described?** Option for setting your gender preferences.

Signature

- **Your existing signature:** shows a preview of your current signature including your profile info when you hover over the link.
- **New signature:** Enter a new name for your signature and save the *Preferences* page.
- **Treat signature as wikitext:** Your signature will be shown as text-only.

Email options

If you provide an email address, you can specify to receive email notifications in addition or in place of wiki notifications. As long as the email address is not confirmed, the system will not send emails. This also affects the settings in the [Notifications](#) tab.

WebDAV

This link is used as mounting path to your wiki. It only works if your server administrator has configured a WebDAV connection. By default, no WebDAV connection is configured.

Appearance

Skin

If your system has more than one skin installed, you can select one here. It only affects your view. All other users see the skin that is selected in their preferences.

Reading preferences

Page previews: You can set if you want to see the first lines of an article as a tool tip before you click on a link. This functionality is provided by the extension [Popups](#).

Date format

You can set how you would like to see the timestamp on wiki pages, for example the timestamp of a user signature on a discussion page.


[Rodrigue \(talk\)](#) 09:10, 3 December 2019 (CET)

Time offset

- **Server time:** Shows the server time so that you can compare it to your local time.
- **Local time:** Shows the time set in the time zone setting.
- **Time zone:** When you select a time zone, your local time will be shown throughout the wiki wherever there is a timestamp.


Files

- **Image size limit:** Sets the maximum size of the preview image on the file description page.





- **Thumbnail size:** Sets the size of the thumbnail image on a page if no custom size is specified in the image settings.
- **Enable Media Viewer:** If this checkbox is not selected, image links on a page will load the file description page rather than the media viewer overlay.




Diffs

Diffs are a comparison view between different versions of a page. They are accessible from the version history of a page. You can select two versions for a comparison and then click *Compare selected revisions* to view the differences.

- **Do not show the page content below diffs:** Turns off the display of the current page preview below the differences view.
- **Don't show diff after performing a rollback:** After an administrator does a rollback of a page, the difference between the previous latest and the current latest version is shown by default. If turned off, the rollback loads the current page directly instead.
- **Don't show the revision slider:** By default there is a collapsed interactive graph of the revision history. This graph can be deactivated.

Advanced options

- **Link underlining:**
 - *Always:* Underlines all links in the content area of a page, even if the selected skin specifies no underlining. The table of contents is not affected by this setting.



- *Never:* Never underlines links in the content area of a page, even if the selected skin specifies underlining.
- *Skin or browser default:* Keeps the link settings as specified in the skin.
- **Threshold for stub link formatting:** Determines when the target page is considered short enough to change the link color to a page that fits the threshold criteria. If you choose 50 bytes, a link to a page with less than 50 characters (including wikitext), will be marked as a stub link and be shown in a different color. This only works if your wiki skin has a separate color value for stub links defined.
- **Show hidden categories:** The categories that a page is in are normally listed on the page. A category can be hidden from this list by adding the magic word `__HIDDECAT__` to the category page. With this setting, a user can opt to show the hidden category anyway.
- **Auto-number headings -v4.3 :** Adds heading numbers to the page headings. **Note:** The heading numbers for books are set independently by administrators in the [Config manager](#).

5 Handling and storage

If caustic soda is left unsealed in the air, it will react with carbon dioxide and form sodium carbonate. It should be stored in hermetically sealed containers.

5.1 Safe handling advice

- Use and open container with care.
- Avoid dust formation.
- Supply eye wash bottle.

5.2 Advice on protection against fire and explosion


- No special actions required.

- **Show a confirmation prompt when clicking on a rollback link:** If an admin user wants to perform a rollback of multiple options from the version history of a page, the rollback is executed immediately after clicking the link by default. With this setting, the admin user needs to click on the "Rollback" link again to confirm the rollback before it is executed.

Bookshelf special page


Grid: Shows the details view (=list view) of available books by default (2)


Images: Shows the thumbnails view of available books by default (1)



Context menu

Page links in the content area of the wiki show a context menu that allows to perform actions on the target page without having to go to the target page first. You can set whether you want to show the context menu with *right-click* or with *right-click + Strg*.





Dashboards

By default, the logo of your wiki links to the main page. You can change this and link to your user dashboard instead.

Video player

When a page contains a video that was inserted with the [BlueSpicePlayer](#) extension, you can set it to autoplay when you load a page.

Timeline

You can set the timestamp on the timeline entries in date format or as age.

Note: It can take up to 24 hours for all timeline entries to show the new timestamp format. When you create a new entry, you should see the changed format immediately.




Editing

General options

- **Enable section editing by right clicking on section titles:** Right-clicking a section title with the mouse sets the page in edit mode. The specified section can be edited immediately.

- **Editing pages by double clicking (JavaScript):** Double-clicking on the page sets the page in edit mode. The double-click needs to be inside the text area of the page. Clicking in the title section of a page will not set the page into edit mode.
- **Enable the [Paragraph-based Edit Conflict Interface](#)** to resolve edit conflicts: Allows section-based merging of differences which improves the process for solving edit conflicts between users. If this setting is disabled: Users will see the source code of the latest version, a diff view between the latest and the own version, and a source diting window to manually work on the user's unsaved version.
- **Show the pending changes diff when editing pages:** In the BlueSpice 4 Discovery skin, no visual diff is shown during editing, so this setting can be ignored. It simply adds a duplicate notice about pending changes, when opening a page in edit mode:




Editor

- **Edit area font style:** Displays source code in monospace, serif, or sans-serif font.

Note: This setting is ignored if the [CodeMirror](#) extension is enabled (from BlueSpice 4.2).


- **Mark all edits minor by default:** This automatically sets the minor flag in the save dialog. It can be selected or deselected in the save dialog on the page itself:



marking a minor edit

Note: Note: The 'Watch this page' checkbox in the save dialog can be activated or deactivated by default under the preferences tab *Watchlist* under *Advanced options: Add pages and files I edit to my watchlist*.

- **Prompt me when entering a blank edit summary:** Displays a text message when you click *Save changes* reminding you to enter a summary description. If you do not enter a description after that, the page will save without the summary the next time you click *Save changes*.



The screenshot shows the MediaWiki save dialog. At the top are three buttons: 'Resume editing', 'Save your changes', and 'Save changes'. Below these is a 'Summary:' section with a text input field containing the placeholder 'Describe what you changed'. Under the summary field is a checkbox labeled 'Watch this page' which is checked, with the number '255' to its right. Below this is a warning message: 'Please note that all contributions to nextminor.bluespice.test.hw.local may be edited, altered, or removed by other contributors. If you do not want your writing to be edited mercilessly, then do not submit it here.' A yellow arrow points down to a 'Reminder' message: 'Reminder: You have not provided an edit summary. If you click "Save page" again, your edit will be saved without one.' At the bottom of the dialog is the text 'edit summary prompt'.

- **Warn me when I leave an edit page with unsaved changes:** When you reload or leave a page with unsaved edits, a warning message is displayed. You can confirm to leave the page or stay on the page and save your changes.
- **Show edit toolbar:** Disables VisualEditor in visual editing mode. Disabling is not recommended, as this reverts the editor back to a previous version of MediaWiki editor.
- **Temporarily disable the visual editor while it is in beta:** You can disable visual editor while it is in [Extension:VisualEditor|beta mode](#). We recommend you do not disable VisualEditor unless you prefer to work with a previous visual editor version.


Preview

These preview settings are only applied if you have temporarily disabled VisualEditor and the edit text area is on the same page as the page preview. In BlueSpice 3.1+ you can generally ignore these settings.

- **Show preview on first edit:** The preview of the article is displayed when you click on "Edit"
- **Show preview before edit box:** If this option is deactivated, the preview will be shown under the edit form
- **Show previews without loading the page:**

Reminder

- **Default reminder period:** Prefills the date field for reminders with *current date + x days* specified here.



- **Set reminder on page creation:** When you create a new page, a reminder for that page is automatically created based on the default reminder period you entered.
- **Do not create reminder for the following namespaces:** Excludes namespaces from the automatic reminder on page creation.


Timeline

- **Warn me when I leave an edit of an entry with unsaved changes:** If unchecked, any unsaved changes to a social entity (such as blog entry, comment, microblog or discussion topic) will be automatically lost if you navigate to a different page or reload the page before saving your changes.
- **Skip dialog on discussion creation:** Automatically creates a discussion page when a user adds a discussion directly on a page and the discussion page for the entry does not yet exist. If this checkbox is unchecked, the user has to create the discussion page first before the discussion topic can be posted.

Recent changes

Display options

- **Days to show in recent changes:** You can set how many results are displayed on the page *Recent changes*.
- **Number of edits to show in recent changes, (,...) by default:** Setting for the filter (1) on the *Recent changes* page and similar log pages. The filter can be manually changed during page visits.



Recent changes default filter setting (1)

Advanced options

- **Group changes by page in recent changes and watchlist:** This view creates a collapsible view of all the changes on a page that occurred before another page was edited. All changes still count towards the number of changes that are set in the view filter for the page.

22 March 2023

▼ 13:56 MLR:Test [pending edits] (2 changes | history) .. (+25) .. [WikiSysop (2×)]

13:56 (cur | prev) .. (+14) .. WikiSysop (talk | contribs | block) [rollback 2 edits]
13:55 (cur | prev) .. (+11) .. WikiSysop (talk | contribs | block)

13:42 MediaWiki:Common.js (diff | hist) .. (+276) .. WikiSysop [rollback more than 10 edits]

▶ 13:23 MLR:Test1 [pending edits] (6 changes | history) .. (+104) .. [Maximilian Achterbahn (6×)]

Grouped changes

- **Use non-JavaScript interface:** Removes the advanced filter option to save filters and to color-highlight changes.

Changes shown

- **Hide minor edits from recent changes:** Hide [edits marked as minor](#) from appearing on your *Recent changes* page by default.

Edit review

These settings are provided by the extension [FlaggedRevs](#) (approval feature).



FlaggedRevs is available up to BlueSpice 4.2.

- **Basic interface:** This setting has no effect in the *BlueSpice Discovery* skin
- **When to show the stable version of content pages by default:**
 - Use the default settings for each page: This setting has no effect in BlueSpice (default settings cannot be [set by administrators on a page level](#))
 - **Always show the stable version (if there is one):** This default setting is only applied if the [FlaggedRevs](#) feature is active in a namespace. It shows the approved (stable) version by default when navigating to that page.
 - **Always show the latest version:** It is a useful settings for users with review permissions who can accept draft versions. It loads the latest revision of a page by default instead of the stable version.
- **Show the pending changes diff when viewing the latest pending version:** This setting has no effect in the *BlueSpice Discovery* skin.

Watchlist

Edit watchlist


- **Edit entries on your watchlist:**

- *View and remove titles on your watchlist:* Links to the page Special:EditWatchlist where you can manage your watchlist entries. The watchlist is organized by namespaces.
- *Edit raw watchlist:* Links to the page Special:EditWatchlist/raw where you can remove pages by page name from a textbox. This list is also organized by namespaces.
- *Clear watchlist:* Links to the page Special:EditWatchlist/clear where you can empty your watchlist with the click of a button.

Display options

- **Days to show in watchlist** (default:7): Presets the value in the selection menu Period of time to display on the page *Special:Watchlist*.
- **Maximum number of changes to show in watchlist** (default:250): Limits the number of changes that are displayed in your watchlist.

This example shows a default setting of 8 days and 20 changes.



Advanced options

- **Expand watchlist to show all changes, not just the most recent** (default): Determines if a changed page is displayed several times in the filtered time period or if only the latest change is listed.
- **Add direct unwatch/watch markers (x/+) to watched pages with changes (JavaScript required for toggle functionality):** An icon for the direct removal of the page from the watchlist is available.




- **Use non-JavaScript interface:** A basic view of the watchlist loads (without special filter menu and without highlighting options).
- **Add pages I review to my watchlist** (until BlueSpice 4.2): Automatically adds pages the user approves to the watchlist.

Changes shown

These settings configure a standard filter for the watchlist. By default, no filter is applied. Possible standard filters are:

- **Hide minor edits from the watchlist**
- **Hide bot edits from the watchlist**
- **Hide my edits from the watchlist**
- **Hide edits by anonymous users from the watchlist**
- **Hide edits by logged in users from the watchlist**




The screenshot shows the 'Active filters' section of the watchlist. It contains two filter buttons: 'Changes by others' and 'Non-minor edits', both with an 'X' icon to remove them. A red circle with the number '1' highlights the 'Non-minor edits' button. Below the filters is a search bar labeled 'Filter changes (use menu or search for filter name)'. To the right of the search bar are links for 'Namespaces' and 'Tags'. Below the search bar is a 'Live updates' button. At the bottom left, there is a 'Hide' section with a checked checkbox for 'social entities' and a 'Show' button. At the bottom right, there is a gear icon followed by '250 changes, 7 days' and a dropdown arrow. A 'Hide' link is in the top right corner. Below the filter interface, the text 'Standard filter with preset values from the preferences settings' is displayed.

Watched pages

These settings determine which pages are automatically added to the watchlist by preselecting the checkbox *Watch this page* of the related dialog window. If no dialog window is available, the addition to the watchlist automatically happens in the background:

- **Add pages and files I edit to my watchlist (default)**



The screenshot shows a 'Save your changes' dialog window. It has a title bar with a close button (X) and a 'Save changes' button. The main content area has a 'Summary:' label followed by a text input field with the placeholder text 'Describe what you changed'. Below the text field are two checkboxes: 'This is a minor edit' (unchecked) and 'Watch this page' (checked). The 'Watch this page' checkbox is highlighted with a red circle. At the bottom of the dialog is a 'Review your changes' button. Below the dialog, the text 'Pre-checked watchlist checkbox' is displayed.

- **Add pages and files I move to my watchlist**
- **Add pages and files I delete to my watchlist**
- **Add pages I create and files I upload to my watchlist** (default)
- **Add pages where I have performed a rollback to my watchlist**

- **Add new files I upload to my watchlist** (default)

Token


- **Watchlist token:** The token can be used to create a public RSS feed to your watchlist. Anyone who knows this token can access the feed. The syntax for the feed URL is: `https://[YourWikiDomain]/w/api.php?action=feedwatchlist&wlower=[USERNAME]&wltoken=[TOKEN]` .

Notifications

Important! Notification don't consider the edit type "Minor edit". Therefore, notifications are sent even in the case where a user makes a minor edit.

Here you can set how and when you would like to receive notifications in email and/or in the notifications area of your user profile (Web notifications). If you haven't received email notifications yet, make sure that your email adress has been verified. This information is available in the *User profile* tab, under the section *Email options*.

To view your Web notifications, go to your User profile menu and select Notifications.




The user profile image in the main toolbar and the *Notifications* menu item show the number of new notifications. Notifications can set for a variety of events, such as new assignments or reminders. You can also select to be notified about changes only in certain namespaces or categories.

To configure which notifications you want to get, click on *Preferences* in the *Settings* menu (3).

Email options

You can specify how often you receive emails: *never*, *immediately*, *daily*, or *weekly*.



If you unexpectedly don't receive emails for notifications, check under the *User profile* tab to make sure that you have already confirmed your email account.

| | |
|---------------------------|---|
| Email confirmation: | Your email address is not yet confirmed. No email will be sent for any of the following features. Confirm your email address |
| unconfirmed email address | |

Notify me about these events

Notifications can be displayed in the Notifications page of the wiki. This functionality is provided by the MediaWiki extension *Echo*.

New message indicator

This setting currently has no effect in BlueSpice. It is a configuration setting for the MediaWiki extension [Extension:Echo|Echo](#) (echo-show-alert).

Notifications on namespace events

Select for which namespaces you want to receive notifications.

Notifications on categories

Select for pages in which categories you want to receive notifications.

Review

- **Notify me about changes if I am the owner of a review:** Select if you want to be notified in email of any workflow changes of a review workflow if you are the owner of the review.
- **Notify me about changes if I am the reviewer of a review:** Select if you want to be notified in email of any workflow changes of a review workflow if you are the owner of the review.

Under the settings for *Notify me about these events*, you can set if and how you want to be notified if someone assigns a review task to you.

Extended Search


Here you can set which namespaces you want to include in your search results. This can be useful if you work in only some areas of the wiki or if you are looking for information in a few areas of your wiki only.

Semantic MediaWiki

These user preferences are provided by Semantic MediaWiki. If you would like to change these settings, you can visit the corresponding [help page](#).

Resetting all preferences

If you click *Restore all default settings (in all sections)*, all your customizations on all tabs are reset to their default settings. Since this could affect lots of customized settings, a warning page appears before the reset.



Use the browser's back button if you do not want to restore the default settings.

Reference:BlueSpiceConfigManager

Extension: BlueSpiceConfigManager

→ [all extensions](#)

| Overview | | | |
|---------------------|--|--------------------|------------------------------|
| Description: | Offers the possibility to admins, to configurate the whole wiki from a single special page | | |
| State: | beta | Dependency: | BlueSpice |
| Developer: | HalloWelt | License: | GPL-3.0-only |
| Type: | BlueSpice | Category: | Administration |
| Edition: | BlueSpice pro, BlueSpice free, BlueSpice Farm, BlueSpice Cloud | Version: | 4.1+ |

Overview

[? View user help page](#)

Features

BlueSpiceConfigManager provides a special page that enables managing all global wiki settings in one place.

Once on the special page, all settings will be grouped by logical groups. There are three ways of grouping the settings:

- Feature - grouping by type of functionality setting belongs to (searching, administration...)
- Extension - grouping by the extension the setting is coming from
- Package - grouping by the package extension providing the setting comes from.

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.36.0

BlueSpiceFoundation: 4.1

Integrates into

Special pages

- BlueSpiceConfigManager

Permissions

| Name | Description | Role |
|--|---|---|
| bluespiceconfigmanager-viewspecialpage | Access to the special page Special:BlueSpiceConfigManager | admin, maintenanceadmin, structuremanager |

Configuration

| Name | Value |
|-----------------------------|--|
| ConfigManagerLogExcludeList | array (0 => 'DistributionConnectorEventBusEventServices',) |

API Modules

- bs-configmanager-store
- bs-configmanager-tasks

Hooks

- [MWStakeCommonUIRegisterSkinSlotComponents](#)

Accessibility

| | |
|-------------------------|---|
| Test status: | 2-testing complete |
| Checked for: | Authoring tool |
| Last test date: | 2022-08-08 |
| WCAG level: | AA |
| WCAG support: | partially supports (workaround: no) |
| Comments: | <p>Keyboard/screenreader:</p> <ul style="list-style-type: none">• search field needs aria-role "search"• infoboxes don't open• save button does not get focus. Workaround: Focus via browser search function (not useful for screenreader users) <p>erm:27702</p> |
| Extension type: | core |
| Extension focus: | admin |