

Contents

1. Manual:Extension/BlueSpiceDiscovery/Main navigation	2
2. Manual:Extension/BlueSpiceConfigManager	6
3. Manual:Extension/BlueSpiceDiscovery/Main navigation/Icons	27
4. Manual:Extension/BlueSpiceDiscovery/Main navigation/Language support	29
5. Reference:UserFunctions	31
6. User:Margit.link-rodrique	32

Manual:Extension/BlueSpiceDiscovery/Main navigation

[Browse history interactively](#)
[VisualWikitext](#)

Revision as of 14:52, 21 March 2022 ([view source](#))
[Margit Link-Rodrigue](#) ([talk](#) | [contribs](#))
No edit summary
Tag: [Visual edit](#)
[← Older edit](#)

Revision as of 11:05, 22 March 2022 ([view source](#))
[Margit Link-Rodrigue](#) ([talk](#) | [contribs](#))
No edit summary
Tag: [Visual edit](#)
[Newer edit →](#)

Line 1:

`<bookshelf src="Book:Admin manual" />`

`==How does the main navigation work?==`

Line 1:

`{{DISPLAYTITLE:Main navigation}}`

`<bookshelf src="Book:Admin manual" />`

`==How does the main navigation work?==`


Revision as of 11:05, 22 March 2022

Contents

1	How does the main navigation work?	4
2	Adding links	4
3	Deactivating standard links	5
4	Group-specific navigation	5
5	Additional customizations	5

How does the main navigation work?

By default, some links are provided as entry points to the wiki. Wiki administrators can deactivate these links in the [configuration manager](#) if needed. In addition, custom links can be added here. Please note that no hierarchical links can be created. Therefore, it makes sense to mainly set up links to the most important topics and to portal pages that contain additional links or page lists.



Adding links

To add new links:

1. **Open** the page *MediaWiki:Sidebar* from the browser's address bar.
2. **Change** to edit mode.
3. **Create** one or more navigation links (with or without section heading). The following example shows a link to the page "Company" with the label "Our company" and an external link to the BlueSpice website with the label "Website". The links are grouped together under the section heading "Quicklinks":

```
*Quicklinks
**Company|Our company
**https://www.bluespice.com/de|Website
```

4. **Save** the page. The links are now shown in the main navigation.

Note: As soon as you have created at least one additional link, a direct edit link to the *MediaWiki:Sidebar* page is displayed when you move the mouse over such a link (see screenshot above).

Link labels may collide with system messages. If this is the case, simply append the HTML-code for an empty space to the description:

```
**Portal|Portal&#160;
```

Deactivating standard links

The standard links can be deactivated in the [configuration manager](#). The following settings are available under *Feature > Skinning*:

BlueSpiceBookshelf:

- Show entrypoint "Bookshelf"

BlueSpiceDiscovery:

- Show entrypoint "Mainpage"
- Show entrypoint "All pages"
- Show entrypoint "Recent changes"

BlueSpiceSocial:

- Show entrypoint "Timeline"

BlueSpiceSocialBlog:

- Show entrypoint "Blog"

Group-specific navigation

It is possible to show navigation elements for specific user groups only. Please note that the pipe symbol (|) between the page name and its label has to be escaped as `{{!}}` within this function.

This syntax is defined in the extension [UserFunctions](#).

```
{{#ifingroup:sysop,widgeteditor |  
*Test2  
**somepage{{!}}Some page  
|}}
```

Additional customizations

- [Display icons with navigation links](#)
- [Multi-language navigation](#)

Config manager

Latest revision as of 11:06, 28 February 2024 ([view source](#))

[Margit Link-Rodrigue](#) ([talk](#) | [contribs](#))

No edit summary

Tag: [Visual edit](#)

(No difference)

Latest revision as of 11:06, 28 February 2024

Contents

1 Layout	8
1.1 Filter options	8
1.2 Searching for settings	8
2 Settings by extension	9
2.1 EventBus	9
2.2 EnhancedUpload v4.3+	9
2.3 BlueSpiceFoundation	9
2.3.1 Updating logo and favicon	9
2.3.2 System	11
2.4 BlueSpiceArticleInfo	11
2.5 BlueSpiceAuthors	12
2.6 BlueSpiceAvatars	12
2.7 BlueSpiceBookshelf	13
2.8 BlueSpiceChecklist	14
2.9 BlueSpiceExtendedSearch	15
2.10 BlueSpiceExtendedStatistics	17
2.11 BlueSpiceInsertCategory	17
2.12 BlueSpiceInsertLink	17
2.13 BlueSpicePageTemplates	18
2.14 BlueSpicePermissionManager	19
2.15 BlueSpiceRSSFeeder	19
2.16 BlueSpiceReaders	19
2.17 BlueSpiceSaferEdit	20
2.18 BlueSpiceUEModuleBookPDF	20
2.19 BlueSpiceUEModuleHTML	20
2.20 BlueSpiceUEModulePDF	21
2.21 BlueSpiceUniversalExport	21
2.22 BlueSpiceVisualEditorConnector	21
2.23 BlueSpiceWholsOnline	22
2.24 BlueSpiceExpiry	22
2.25 BlueSpiceFlaggedRevsConnector	22
2.26 BlueSpiceSocial	24
2.27 BlueSpiceSocialBlog	24
2.28 BlueSpiceSocialTopics	25
3 BlueSpiceDiscovery	25
3.1 Deactivating the Entrypoint links	25
3.2 Positioning of skin elements	26
3.3 Content Stabilization v4.3+	26


With the Config manager, a wiki user with *sysop* rights can manage wiki-wide settings in one place. In the [navigation](#), it is located at *Global navigation > Management > Configuration*. This link loads the page *Special:BluespiceConfigManager*.

Layout

Filter options

All settings can be accessed through the following filter options:

- **Feature:** group by type of functionality the setting belongs to (search, administration...)
- **Extension:** group by extension name
- **Package:** group by BlueSpice edition and services (BlueSpice free, BlueSpice pro, Matomo)




All settings are available in any type of grouping. Changing the grouping type does not add or remove setting options. It just groups them differently. After settings are adjusted, they can be saved by clicking *Save*, or cancelled by clicking *Reset*.

Note: If a server administrator has configured a setting to no longer be writable, it will be shown as greyed-out in the config manager. You will have to talk to your server administrator about changing such a setting.

Searching for settings

A search bar is located above the list of settings. Type in a keyword such as "logo" to find the corresponding setting. The search returns settings regardless of the currently selected group.

Note: The search field has to be empty if you want to see the filter menu instead of the search.



Config manager search box


Settings by extension

EventBus

Eventbus sends notifications to external urls in case something happens in the wiki. For example, if a page is created, an external service could then be started and create a pdf of that page. See the extension's page on mediawiki.org.

EnhancedUpload v4.3+

Sets the defaults for the [advanced image settings](#) when uploading and embedding an image into the wiki via drag-and-drop functionality. The default settings determine the orientation, type, and size of the image. These can be adjusted after embedding via the "Advanced settings" of the image on the page.



Configuration settings for the Enhanced upload

BlueSpiceFoundation


Updating logo and favicon

Note: Since BlueSpice 4.2, the logo and favicon can also be managed via the page [Special:Flexiskin](#) together with further skin customizations.


- **Logo path:** The logo image should be stored in the /images folder of your installation. If you store it in the /skins folder of your BlueSpice installation, it could be overwritten with an upgrade.

To upload the logo directly in the wiki:


1. **Upload** the logo on the page from the menu *Global actions > File list (Special:ExtendedFilelist)*.
2. **Click** on the thumbnail image of the logo. This opens the logo on a separate page.



3. **Copy** the relative logo path from the address bar. In a typical Wiki configuration, this path starts with */w/....*.



4. **Paste** the logo path into the text field for the logo.



5. **Click Save.**

6. **Refresh** the page (Strg+F5).

If the uploaded logo is too large, you can add the following code snippet to the page *MediaWiki:Common.css*. This automatically adjusts the image to the height of the main toolbar:

```
.bs-logo a {background-size: contain;}
```

- **Favicon path:** The favicon image should be stored in the */images* folder of your installation. If you store it in the */skins* folder of your BlueSpice installation, it could be overwritten with an upgrade. [Favicon images](#) have the file extension *.ico*.

System

- **Allowed file extensions:** For security reasons, the types of files that users can upload are restricted. Here, you can allow additional file formats. If a file format is blacklisted in the server configuration, adding this file extension here will not allow this file type to be uploaded. See [mediawiki.org/wiki/Manual:\\$wgFileExtensions](https://mediawiki.org/wiki/Manual:$wgFileExtensions) for more info.

XML file type: v4.x++

The *xml* file type is blacklisted since MW 1.39 and has to be allowed in *LocalSettings.php*:


```
$GLOBALS['wgProhibitedFileExtensions'] = array_diff( $GLOBALS['wgProhibitedFileExtensions'] ?? [], [ 'xml' ] );  
$GLOBALS['wgMimeTypeExclusions'] = array_diff( $GLOBALS['wgMimeTypeExclusions'] ?? [], [ 'application/xml', 'text/xml' ] );
```


- **Allowed image extensions:** The standard web image types are listed here. In general, you want to restrict image uploads to web images. See developer.mozilla.org/en-US/docs/Web/Media/Formats/Image_types for more on browser-supported image types.

BlueSpiceArticleInfo

BlueSpiceArticleInfo, together with *BlueSpiceAuthors*, *BlueSpiceReaders*, and *BlueSpiceExtendedSearch* is part of the *Page information* in the quality management tools.

- **Update interval in seconds:** Sets the refresh rate for the "Last edit" value. By default, this date is updated every 10 seconds via JavaScript.






BlueSpiceAuthors

BlueSpiceAuthors, together with *BlueSpiceArticleInfo* and *BlueSpiceReaders*, is part of the *Page information* in the quality management tools.


- **Display authors:** Show or hide authors on the page information page.




BlueSpiceAvatars

An avatar image is automatically generated if the user does not upload a profile picture or if the user decides to create an avatar image in the preferences.


- **Generator**
 - **InstantAvatar:** Generates an avatar image based on using the initials of the Real name or the Username
 - **Identicon:** Generates an avatar image based on parts of the user's IP address.






BlueSpiceBookshelf

- **Show book chapter pager after content:** Displays previous/next book page navigation at the end of each book page. (1)
- **Show book chapter pager before content:** Displays previous/next book page navigation at the beginning of each book page. (2)




- **Use the display title from book source on article:** Shows the title from the book navigation as page title instead of the page name.



Note: If the page additionally contains a `{{DISPLAYTITLE}}` tag, the display title of the page is shown instead of the book title.

- **Prepend article table of contents and headlines with book numeration:** The page TOC does not start with the main heading 1, but with the actual number from the book chapter (see screenshot). If users have activated in their [user preferences](#) to "auto-number headings", the numbering system is matched accordingly.



- **Suppress namespace prefix of book articles in output:** The namespace prefix of an article is not shown in PDFs.

BlueSpiceChecklist

- **Mark checklist changes as minor edit:** If this setting is active, changes to a checklist (for example, checking a checkbox) in view mode are logged as minor edits. If this setting is inactive, a change to the checklist is recorded as a regular version in the page history.

• (cur | prev) @ 12:01, 2019 December 5 ML Mlink-rodrigue (talk | contribs | block) m
(2,820 bytes) (+9) .. (Unchecked checkbox #1) (rollback 6 edits | undo) (Tag: Checklist change)

minor edit

BlueSpiceExtendedSearch

- **External file paths:** External locations to scan for and index files from. These locations are entered in key/value pairs of Physical path and URL prefix.
 - *Physical path:* Storage path. For mounted drives, for example: *X:\Documents*
 - *URL prefix:* All files indexed from the indexed physical location are prefixed in the search results. It should be used if files are available from a web server. By default, the URL prefix is set to the same value as *Physical path*.

Examples for external file paths

Example file	Phys. Path	URL Prefix	Link in results list
S:\Sales\Info\glossaryy.pdf	S:\	file:///S:/	file:///S:/Sales/Info/glossary.pdf
		https://sharepoint /Sales/ documents/	https://sharepoint/Sales/ documents/Sales/Info /glossary.pdf
		https://intranet /showdocs inline.aspx?path=	https://intranet/showdocsinline. aspx? path=/Sales/Info/glossary.pdf
/var/www/bluespice/w /mounted_ share/Sales/Info /glossary.pdf	/var/www /bluespice/w/ mounted_share/		https://wiki.company.local/w /mounted_ share/Sales/Info/glossary.pdf

Feature ▼ | Reset 2 Save

☐ System
☐ Skinning
☐ Data analysis
☐ Personalization
☐ Book
☐ Export
☐ Content structuring
☐ Quality assurance
☒ Searching and Navigation
☐ Editor
☐ Administration

BlueSpiceExtendedSearch

External file paths ⓘ

No values set!

Add new entry

Physical path * URL prefix ✓ 1

☐ Use simple autocomplete ⓘ
☐ Automatically set language filter ⓘ

Exclude patterns

No values set!

Add new entry

Physical path * Exclude regular expression pattern * ✓

Add an external file path: (1) confirm the checkmark and (2) save the settings.

- **Use simple autocomplete:** forces a more compact autocomplete (1-column Sales thumbnail preview).

Configu

Configure search
Configuration
Getting started - Login and configuration
Robot Configuration
Create and configure articles
ExtendedSearch configuration
Setup:Installation Manual/System Configuration/Apache Tomcat
+ Create page "Configu"
Search full text

compact autocomplete

Configu

Configure search
Configuration
Getting started - Login and configuration
Robot Configuration
Create and configure articles
ExtendedSearch configuration
Setup:Installation Manual/System Configuration/Apache Tomcat
VisualEditor configuration
+ Create page "Configu"
Search full text

Salesautocompletey

- **Automatically set language filter:** The search only returns pages whose language (PageLanguage) is identical to the user language (Language). Users can set their language in their [preferences](#). By default, the language of content pages is the same as the installation language (ContentLanguage) of the wiki. Some extensions can set the language of individual pages independently of the content language of the wiki.. (See: https://www.mediawiki.org/wiki/Manual:Language#Page_content_language). In many wikis, activating this filter has little effect.
- **Exclude patterns:** Files at external file locations can be excluded from search based on regular expression patterns.

BlueSpiceExtendedStatistics

- **Exclude these users:** Some user groups, like WikiSysop can skew the statistics, for example the statistics for search queries or because they complete automated maintenance tasks. These types of user groups can be excluded from the statistical results.
- **Maximum number of interval steps:** Sets the size of the x-axis for the results. For a few days, select the interval *Day* or *Calendar Week*, for periods over one year, select *Year* or *Month*. If you do not get any results for your query, try to adjust the interval accordingly.

BlueSpiceInsertCategory

- Insert category with its parent categories
- Preset categories of a page in the upload dialog


BlueSpiceInsertLink

- **Allow unmapped links:** if there is no prefix in the map, the link will still be inserted. Example: S:\HR. If this setting is unchecked, the link will not be inserted.
- **Allowed locations for external files:**

Example file	Filesystem prefix	Web accessible Prefix	Link output
S:\Sales\Info\glossaryy.pdf	S:\	file:///S:/	file:///S:/Sales/Info/glossary.pdf
		https://sharepoint/Sales/documents/	https://sharepoint/Sales/documents/Sales/Info/glossary.pdf
		https://intranet/showdocs inline.aspx?path=	https://intranet/showdocsinline.aspx? path=/Sales/Info/glossary.pdf
/var/www/bluespice/w /mounted_			


Example file	Filesystem prefix	Web accessible Prefix	Link output
share/Sales/Info/glossary.pdf	/var/www /bluespice/w/ mounted_share/		https://wiki.company.local/w/mounted_ share/Sales/Info/glossary.pdf

When a new entry is added, it has to be confirmed by clicking the checkmark next to it before saving the page.



BlueSpicePageTemplates

- **Force target namespace:** The page is always created in the target namespace that is associated with the template, even if the user provided a different namespace prefix. In the screenshot below, the user wants to create the page "NewPage" and then selects a template for the QM namespace. The page is, therefore, created as "QM:NewPage" if this setting is activated.



- **Hide default templates:** Hides the default *Empty page* template.


- **Hide template if the page is not to be created in the target namespace:** Depending on the namespace prefix of the page to be created, templates that are associated with other namespaces will not be shown to the user for selection.

BlueSpicePermissionManager

- **Backup limit:** Sets the number of backups for the permissions manager. Each time the page *Special:PermissionManager* is saved, a backup is created. If the backup limit is set to 5, the last five versions of the permissions configuration are saved as backups.

BlueSpiceRSSFeeder


- **URL whitelist:** RSS feeds need to be whitelisted here by an administrator before they can be displayed in a wiki page.
- **Maximum number of allowed redirects:** If there are URL redirects for any of the whitelisted URLs, the number of redirects needs to be adjusted (usually to 1 or 2).



The screenshot shows the 'Administration' section for 'RSS Feed settings'. It contains two main fields: 'URL whitelist' and 'Maximum number of allowed redirects'. The 'URL whitelist' field is a text input containing two URLs: 'https://blog.bluespice.com/feed/' and 'https://blog.hallowelt.com/feed/'. The 'Maximum number of allowed redirects' field is a numeric input set to '0', with minus and plus buttons for adjustment. The interface is titled 'Administration' and 'RSS Feed settings'.

BlueSpiceReaders

- **Number of readers to display:** Sets the number of readers that are displayed on the Page information in the Quality management tools.



The screenshot shows the 'Page information for "Manual:Extension/BlueSpiceReaders"' window. It features a sidebar with tabs: 'General', 'Last edit', 'Properties', 'Expiry of page', 'Authors of this page', 'Readers of this page' (which is selected and highlighted in blue), and 'Reminder'. The main content area is currently empty. At the bottom, there is a pagination bar showing 'Page 0 of 0' and navigation icons. Below the screenshot, the text 'displays readers of the page' is present.

BlueSpiceSaferEdit

- **Interval for lookup for concurrent editings:** Sets the time in seconds for checking if another person is editing the page.
- **Show name of current editor:** Shows or hides the name of the user who is currently editing the page.

BlueSpiceUEModuleBookPDF

- Table of Contents
 - *Only article titles (indent by grade):* Only shows the article titles in the main contents table of the PDF.

Table of contents	
1 Introduction	3
2 Wiki pages model	4
3 User rights	7
3.1 Group manager	15
3.2 Permission manager	18
3.3 User manager	24
4 Namespace manager	28

PDF table of contents without article TOCs

- *Embed article TOCs (No indent of article titles):* Shows the table of contents for each article in the main contents table of the PDF.

Table of contents	
1 Introduction	5
2 Wiki pages model	6
1 The pages modell	6
2 Page types	6
2.1 Special page	6
2.2 Content page	7
2.3 Wiki page	7
2.4 Category page	8
2.5 File / image (description) page	8
3 User rights	9
3.1 Group manager	17
1 Accessing the group manager	17
2 Functionality	18
3 Assigning roles and users to groups	18

Embed article TOCs


BlueSpiceUEModuleHTML

- **Hide namespace prefix in HTML:** If activated, the namespace is shown in the HTML main heading.

Note: If the page contains a "displaytitle" tag in the page source, the page display title is shown and this setting has no effect.

BlueSpiceUEModulePDF

- **Hide namespace prefix in PDF:** If activated, the namespace is shown in the PDF main heading for a page.



Note: If the page contains a "displaytitle" tag in the page source, the page display title is shown and this setting has no effect.

BlueSpiceUniversalExport

- **Metadata (standard, JSON):** Additional data to be passed to the rendering template in JSON format. This data can be used in the export template. The template itself is maintained server-side.
- **Metadata (override, JSON):** Allows overriding standard data sent to the rendering template in JSON format. Values that are set by default can be overridden with this option.

BlueSpiceVisualEditorConnector


- **Enable VisualEditor for BlueSpice extensions**
- **Configuration variable to use a simplified save process**
- **Upload type**
 - Original (Here a confirmation of the rights of use/upload is obtained, file name and namespace of the file can be changed, a category can be assigned and a description of the file **MUST** be given).
 - Simple (No confirmation of required rights is obtained here, the name and namespace of the file can be changed, a description and a category can be assigned, but does not have to be specified)
 - One click (No confirmation about required rights is obtained here, the image cannot be renamed and no category can be assigned. Only the namespace can, but does not have to be adjusted before uploading)

BlueSpiceWholsOnline

- **Time in seconds until a user is marked as offline:** The system checks every x seconds if a user logged out and no longer displayed as online. This can be less frequent than the update interval for newly logged-in users.
- **Update interval in seconds:** The system checks every x seconds for users.

BlueSpiceExpiry

- **Show watermark for expired pages in PDF:** Shows the watermark for expired pages in PDFs.
- **Show watermark for expired pages in print version:** Shows the watermark for expired pages when a page is printed.
- **Show watermark for expired pages:** Shows a watermark on the page itself.



BlueSpiceFlaggedRevsConnector




BlueSpiceFlaggedRevsConnector is available up to BlueSpice 4.2.

Export

The export settings affect how the pages of a book are generated in the PDF export.

- **Bookshelf: List approved revisions log:** Shows a log of stable page versions of pages in the PDF and when these pages were put into accepted status. If editors did not provide a comment when accepting the page, the *Stable comment* field for a revision is empty.



Stable date	Page	Stable comment
18.11.2019	Permission matrix	
18.11.2019	Permission matrix	
15.11.2019	Wiki pages model	
14.11.2019	Permission manager	
14.11.2019	Group manager	

accepted revisions log

- **Bookshelf: List pages without stable revision:** Displays a list of PDF pages at the beginning of the PDF that only exist as a first draft and have no released version.

<p>Not stable pages</p> <hr/> <p>QM:Checklists</p> <hr/> <p>Pages without acceptance feature</p>
--

- **Bookshelf: List pages without FlaggedRevs:** Displays a list of PDF pages that do not have a release mechanism at the beginning of the PDF.

<p>Not FlaggedRevs namespace</p> <hr/> <p>Introduction</p> <p>Wiki pages model</p> <p>User rights</p> <p>Group manager</p> <hr/> <p>Pages with no FlaggedRevs feature.</p>

- **UEModulePDF: Show FlaggedRevs info below main heading:** Prints the latest revision dates (last acceptance and last edit date) below the heading.

<p>Introduction</p> <hr/> <p><i>Stable: 06.12.2019 - 12:00 / Revision: 06.12.2019 - 11:43</i></p> <hr/> <p>FlaggedRevs info below heading</p>
--

Quality assurance

- **Include handling:** If resources are embedded in a page and those resources are located in namespaces with approval mechanism, then the following settings can be selected. For example: If an approved page contains a template or a file that has been changed after the page itself has been approved, the page will not get another draft version, but instead one of two configurations applies:
 - Current versions: Always show the latest version of the embedded resource.
 - Stable versions: Always show the stable (=approved) version of a resource.
- **Show unstable pages for following groups:** If the group *user* is removed from the *BlueSpiceFlaggedRevs* configuration, users in this group will not be able to see draft versions when they are added as reviewers in a review process. When the group *user* is removed, only *sysop* and *reviewer* users can access drafts. If you want other groups, for example *editor*, to see draft versions, you need to add them to the configuration. If no user groups are specified in the configuration field, not even reviewers and sysops users will see a visual status indication of a page. They will have access to drafts through the revision history for the page instead.

Searching and Navigation


- **Indexing only stable versions:** Draft versions are excluded from the search results. If a page does not have a stable version, it is not shown as a search result.

BlueSpiceSocial

- **Show endpoint "Timeline":** Shows a link to the page *Special:Timeline* in the main navigation.

BlueSpiceSocialBlog

- **Use teaser text for blog entries in the timeline:** When you create a blog entry, you can create a teaser text for it by clicking the cogwheel symbol in the blog entry form. If this setting is active, the teaser text will be shown on the page *Special:Timeline* instead of the first part of the content.




The screenshot shows a form for creating a blog entry. The 'Title' field contains 'ISO 7010 Symbole'. The 'Content' field contains a message about ISO 2010 graphics standards. Below the content field is a 'Teaser' field, which is highlighted with a red circle. The 'Teaser' field contains the text 'Pages in violation of ISO 2010 graphics standards will be expired'. At the bottom right of the form, there is a 'Cancel' button and a 'Post' button, both highlighted with red circles. A gear icon is also visible next to the 'Cancel' button.

blog teaser text


- **Show endpoint "Blog":** Shows a link to the page *Special:Blog* in the main navigation.

BlueSpiceSocialTopics

- **Automatically create all discussion pages.** If a user creates the first discussion topic for a page using the link in the page footer of a wiki page, the needed discussion page is automatically created first.




A message "This discussion page was created automatically" is inserted on the discussion page.



If this setting is deactivated, the user is directed to the "Create page" default page first.

BlueSpiceDiscovery

Deactivating the Entrypoint links



Entrypoint links for Discovery skin

Positioning of skin elements



Elements below the page title

page-sentence X

Elements below the page content

categories X rating X recommendations X

positioning skin elements

- page-sentence: display of page status ([Approval status](#), [Expiry](#))
- categories: display of [page categories](#)
- rating: display of [page ratings](#)
- recommendations: display of [page recommendations](#)

Content Stabilization v4.3+

The following configuration options are available for page approvals:

- **Include handling (1):** Wenn Ressourcen in eine Seite eingebettet sind **und sich diese Ressourcen in Namensräumen mit Freigabe befinden**, können die folgenden Einstellungen ausgewählt werden. Es gibt zwei mögliche Einstellungen:

	Verhalten
Stable versions of included pages	Shows the approved (stable) version of a resource, even if it was approved after the page that includes the resource was approved. (This works only if the resource is located in a namespace with active approval feature).
Versions that were current at the time of approval	Shows the version of the resource which was embedded at the time of the last approval of the wiki page where it is embedded. (This works only if the resource is located in a namespace with active approval feature).

For example, if an approved page contains a template that was modified after the page itself was approved, the page will not show a draft version. Approvals work directly via the embedded resource.

- **Allow viewing of first draft version (2):** If this setting is activated, then all users with read rights can view the first draft. When disabled, only groups from the "Show unstable pages for following groups" setting can see first drafts.
- **Update semantic properties from stable pages only (3):** The property value of the page is read from the stable version of the page and not from the draft version.
- **Entwurfsseiten für folgende Gruppen anzeigen (4):** If the group `user` has been removed from the configuration, users in this group will not be able to see draft versions when they are added as reviewers in a review process. In this case, only users with the roles `sysop` and `reviewer` can access drafts unless other groups are specified. These system groups can only access drafts through the site's version history.

➔ [Technical Reference: BlueSpiceConfigManager](#)

➔ [Technical Reference: BlueSpiceConfigManager](#)

Manual:Extension/BlueSpiceDiscovery/Main navigation/Icons: Difference between revisions

Latest revision as of 11:38, 23 December 2021 ([view source](#))

[Margit Link-Rodrigue](#) ([talk](#) | [contribs](#))

[m](#) ((username removed) (log details removed))

(No difference)

Latest revision as of 11:38, 23 December 2021

Icons anpassen


You can assign individual symbols to the navigation links in the main navigation by adapting the styling using CSS. Let's say you have a link named *Softwarekatalog*.

To add a book icon:

1. **Open** the page *MediaWiki:Common.css* in edit mode.
2. **Add** the following lines at the end of the page.
3. **Save** the page.

```
a#n-Softwarekatalog::before {
  content: '\e970';
  font-family: 'entypo';
  margin-left: -20px;
  padding-right: 4px;
  vertical-align:middle;
}
```

The link is now displayed with an icon.



Reload the page or empty the browser cache (**F5** on the keyboard) if the changes are not immediately visible. If your link label includes special characters, you need to follow the instructions for [navigation links with special characters](#).

Available icons

You can see all available icons on the page `w/extensions/BlueSpiceFoundation/resources/bs.icons.php` of your wiki.

A [list with all icons](#) and their character keys on this helpdesk is available here and is the same for any default installation of a BlueSpice wiki.

In the upper line you can click through different fonts, below you find the icons with the corresponding character keys. In *MediaWiki:Common.css* you have to adjust the entries *font-family* (entypo, fontawesome, icomoon, ...) and *content* (character key) accordingly.

Navigation links with special characters

If the text for the menu items contains special characters, they are converted in the HTML code of the page. In this case, right-click on the corresponding entry and, depending on the browser used, select "Inspect" or similar.



For example, if you want to display the link description Introduction to Semantic MediaWiki with the book symbol, copy the value from the link ID and paste the following formatting instruction in *MediaWiki:Common.css*:

```
a#n-Softwarekatalog::before,a[id="n-Einf.C3.BChrung-Semantic-MediaWiki"]::before {content: '\e970';font-family: 'entypo';margin-left: -20px;padding-right: 4px;vertical-align:middle;}
}
```

After saving *Common.css* and reloading the page you now see the selected icon.

Manual:Extension/BlueSpiceDiscovery/Main navigation /Language support: Difference between revisions

Latest revision as of 16:14, 30 March 2022 ([view source](#))

[Margit Link-Rodrigue](#) ([talk](#) | [contribs](#))

No edit summary

Tag: [Visual edit](#)

(No difference)

Latest revision as of 16:14, 30 March 2022

Contents

1	Navigation based on the user language setting	30
1.1	Link labels	30
1.2	Link targets	30
2	Related info	31

Navigation based on the user language setting

Note: These instructions do not apply in a farm environment or in separate language wikis. These instructions are used for maintaining languages in as single wiki.

Link labels

If you want the link labels in the main navigation or the [custom menu](#) to match the language a user has set under their *Preferences*, you need to provide a separate system message page for each menu item. These message pages need to be created in the namespace *MediaWiki*.

In the following example, we create a menu item called *Quality assurance*. A user who specified German (de) or formal German (de-formal) in their preferences, should see the label *Qualitätssicherung* instead.

To create the labels in EN, DE and DE-formal:

1. **Create** the page *MediaWiki:QA* and add the text for the English label (*Quality assurance*). Save the page.
2. **Create** the page *MediaWiki:QA|de* and add the text for the German label (*Qualitätssicherung*). Save the page.
3. **Create** a link on the page *MediaWiki:Sidebar*: `**About_quality_assurance|QA` This creates a link in the main navigation to the page *About quality assurance* and displays the label that is defined in the different language message pages for the message "QA". To test the languages, go to *Preferences > User Profile* in your user profile menu. In the section *Internationalisation*, set the language from English to German or vice versa and save the setting. The language of the menu item now displays in the correct language.

Link targets

If you have content in multiple languages, you want that users with English language preference settings not only see the corresponding menu labels. They should also be directed to an English page when they click on a menu item. Users with German language settings should see the German content after clicking on the German menu link. In this case, you also have to create separate link targets in addition to the language labels.

In the previous section, we already created the labels when a user switches languages. Now we also have to create different link targets for these pages. If the main language is English and the page is called *About quality assurance*, the translations can be located in subpages. For example, the German version is located under *About quality assurance/de*.

To create the link targets to the language pages:

1. **Create** the page *MediaWiki:QA-url* and add the link to the English page *About quality assurance*. The link is entered without brackets, in plain text. Save the page.
2. **Create** the page *MediaWiki:QA-url|de* and add the text for the German page (*About quality assurance /de*). The link is entered without brackets, in plain text. Save the page.

In the navigaion link to the *Quality assurance* page, change the link from

```
**About_quality_assurance|QA
```

to

```
**QA-url|QA
```

This achieves the language switch for the target pages (QA-url) and for the label (QA) of the menu item.

Depending on the language settings of the user, the user is now directly directed to the correct language version.

Related info

- [Interwikilinks](#)

Reference:UserFunctions: Difference between revisions

Latest revision as of 16:42, 5 August 2022 ([view source](#))

[Margit Link-Rodrigue](#) ([talk](#) | [contribs](#))

No edit summary

(No difference)

Latest revision as of 16:42, 5 August 2022

Extension: UserFunctions

→ [all extensions](#)

Overview			
Description:	Enhance parser with user functions		
State:	stable	Dependency:	MediaWiki

Overview			
Developer:	Ross McClure, Toni Hermoso, Pulido, and others	License:	GPL v2+
Type:	MediaWiki	Category:	Administration
Edition:	BlueSpice pro, BlueSpice free, BlueSpice Farm, BlueSpice Cloud	Version:	4.1+
For more info, visit Mediawiki .			

Features

The extension **UserFunctions** provides a set of dynamic parser functions that trigger on the current user.

Accessibility

Test status:	2-testing complete
Checked for:	Web, Authoring tool
Last test date:	2022-08-05
WCAG level:	AA
WCAG support:	supports
Comments:	source code editing; text-based
Extension type:	core
Extension focus:	editor

User:Margit.link-rodrigue: Difference between revisions

Latest revision as of 13:43, 18 January 2023 ([view source](#))

[Margit Link-Rodrigue](#) ([talk](#) | [contribs](#))

No edit summary

[Tag:](#) 2017 source edit

(No difference)

Latest revision as of 13:43, 18 January 2023
