

Manual:Extension/BlueSpiceHideTitle

Contents

1 Description 2

2 Properties 2

2.1 Input properties 2

2.2 Output properties 3

3 Usage 3

Description

The *EditWikiPage* activity appends content to an existing wiki page.

Short profile	
Name	EditWikiPage
Async	Yes
BPMN type	bpmn:Task
BPMN Extension Element "wf:type"	edit_page

Properties

Input properties

Each input property can provide a default value if no other value is set by the workflow.

Name of property	Source	Description	Possible values	Type
title	-	Name of the wiki page that will be edited by this activity.		string
user	-	Name of user that will be shown as making the edit.	Default value: <i>MediaWiki default</i>	string
content	-	Content that will be added to the wiki page.		string
mode	-	How the content is added to the wiki page.	<i>append</i>: Content is added at the end of the page. <i>replace</i>: Content replaces all existing page content. <i>prepend</i>: Content is added at the beginning of the page.	string
minor	-	The edit will be marked as <i>major</i> or <i>minor</i> revision.	<i>1</i> (=minor revision) <i>0</i> (=major revision)	int

Output properties

Name of property	Source	Description	Type
<code>revisionId</code>	-	The revision ID of the edited page.	string
<code>timestamp</code>	-	The revision time of the edited page.	int

Usage

```
<bpmn:task id="Activity_18egh9o" name="Edit page">
  <bpmn:extensionElements>
    <wf:type>edit_page</wf:type>
  </bpmn:extensionElements>
  <bpmn:property name="title" default="Some page" validation="required"/>
  <bpmn:property name="user" default="Mediawiki default" validation="existing-
user"/>
  <bpmn:property name="content" default="This is my test at editing"/>
  <bpmn:property name="mode" default="append"/> <!-- Allowed: append, replace,
prepend -->
  <bpmn:property name="minor" default="1"/>
  <!-- Output properties -->
  <bpmn:property name="revisionId"/>
  <bpmn:property name="timestamp"/>
</bpmn:task>
```

[Technical Reference: BlueSpiceHideTitle](#)