

Contents

1. Manual:Preferences	2
2. Manual:Extension/BlueSpiceConfigManager	18
3. Manual:Extension/BlueSpicePlayer	39
4. Reference:CodeMirror	41
5. Reference:FlaggedRevs	42
6. Reference:Popups	43
7. Reference:RevisionSlider	44

Personalization

Contents

1	Accessing preference settings	4
2	User profile	4
2.1	Basic Information	4
2.2	Internationalisation	4
2.3	Signature	4
2.4	Email options	4
2.5	WebDAV	5
3	Appearance	5
3.1	Skin	5
3.2	Reading preferences	5
3.3	Date format	5
3.4	Time offset	5
3.5	Files	5
3.6	Diffs	7
3.7	Advanced options	7
3.8	Bookshelf special page	8
3.9	Context menu	8
3.10	Dashboards	9
3.11	Video player	9
3.12	Timeline	9
4	Editing	10
4.1	General options	10
4.2	Editor	10
4.3	Preview	12
4.4	Reminder	12
4.5	Timeline	12
5	Recent changes	12
5.1	Display options	12
5.2	Advanced options	13
5.3	Changes shown	13
5.4	Edit review	13
6	Watchlist	14
6.1	Edit watchlist	14
6.2	Display options	14
6.3	Advanced options	14
6.4	Changes shown	15
6.5	Watched pages	15
6.6	Token	16
7	Notifications	16
7.1	Email options	17

7.2	Notify me about these events	17
7.3	New message indicator	17
7.4	Notifications on namespace events	17
7.5	Notifications on categories	17
7.6	Review	17
8	Extended Search	18
9	Semantic MediaWiki	18
10	Resetting all preferences	18


Accessing preference settings

1. **Click** on the user menu.
2. **Click** *Preferences*. This opens the preferences page with multiple tabs.

Alternatively, you can access the page *Special:Preferences* directly.

User profile

Basic Information



- **Real name:** This name is shown throughout the wiki. When users hover over your real name, your profile picture and contact information is shown.
- **Change password:** If your wiki is not connected with the central authentication system of your company, you can manage your password here.
- **User image:**
 - *User image* text field: Enter the webaddress of a picture on another website and click *Save* at the bottom of the page. The profile picture points directly to the external image:
 - *Change profile picture* link: Upload an image to the wiki. Click *Browse* and then *Upload* to create a new profile image. If you click *Generate new avatar*, the system generates a graphic instead.
- **Privacy policy** acceptance checkbox: Select and save this checkbox setting to confirm that you accept the privacy policy. Administrators can review this setting for all users on the page *Special:Privacy_Admin*.

Internationalisation

- **Language:** Users can change their personal language that is used in the layout and menus. BlueSpice currently supports de-formal-German (formal), de-German and en-English.
- **How do you prefer to be described?** Option for setting your gender preferences.

Signature

- **Your existing signature:** shows a preview of your current signature including your profile info when you hover over the link.
- **New signature:** Enter a new name for your signature and save the *Preferences* page.
- **Treat signature as wikitext:** Your signature will be shown as text-only.

Email options

If you provide an email address, you can specify to receive email notifications in addition or in place of wiki notifications. As long as the email address is not confirmed, the system will not send emails. This also affects the settings in the [Notifications](#) tab.

WebDAV

This link is used as mounting path to your wiki. It only works if your server administrator has configured a WebDAV connection. By default, no WebDAV connection is configured.

Appearance

Skin


If your system has more than one skin installed, you can select one here. It only affects your view. All other users see the skin that is selected in their preferences.

Reading preferences

Page previews: You can set if you want to see the first lines of an article as a tool tip before you click on a link. This functionality is provided by the extension [Popups](#).

Date format

You can set how you would like to see the timestamp on wiki pages, for example the timestamp of a user signature on a discussion page.



Rodrigue (talk) 09:10, 3 December 2019 (CET)

Time offset


- **Server time:** Shows the server time so that you can compare it to your local time.
- **Local time:** Shows the time set in the time zone setting.
- **Time zone:** When you select a time zone, your local time will be shown throughout the wiki wherever there is a timestamp.

Files

- **Image size limit:** Sets the maximum size of the preview image on the file description page.



- **Thumbnail size:** Sets the size of the thumbnail image on a page if no custom size is specified in the image settings.
- **Enable Media Viewer:** If this checkbox is not selected, image links on a page will load the file description page rather than the media viewer overlay.




Diffs

Diffs are a comparison view between different versions of a page. They are accessible from the version history of a page. You can select two versions for a comparison and then click *Compare selected revisions* to view the differences.

- **Do not show the page content below diffs:** Turns off the display of the current page preview below the differences view.
- **Don't show diff after performing a rollback:** After an administrator does a rollback of a page, the difference between the previous latest and the current latest version is shown by default. If turned off, the rollback loads the current page directly instead.
- **Don't show the revision slider:** By default there is a collapsed interactive graph of the revision history. This graph can be deactivated.

Advanced options

- **Link underlining:**
 - *Always:* Underlines all links in the content area of a page, even if the selected skin specifies no underlining. The table of contents is not affected by this setting.



- *Never:* Never underlines links in the content area of a page, even if the selected skin specifies underlining.
 - *Skin or browser default:* Keeps the link settings as specified in the skin.
- **Threshold for stub link formatting:** Determines when the target page is considered short enough to change the link color to a page that fits the threshold criteria. If you choose 50 bytes, a link to a page with less than 50 characters (including wikitext), will be marked as a stub link and be shown in a different color. This only works if your wiki skin has a separate color value for stub links defined.
- **Show hidden categories:** The categories that a page is in are normally listed on the page. A category can be hidden from this list by adding the magic word `__HIDDENCAT__` to the category page. With this setting, a user can opt to show the hidden category anyway.
- **Auto-number headings -v4.3 :** Adds heading numbers to the page headings. **Note:** The heading numbers for books are set independently by administrators in the [Config manager](#).

5 Handling and storage

If caustic soda is left unsealed in the air, it will react with carbon dioxide and form sodium carbonate. Therefore, it must be stored in hermetically sealed containers.

5.1 Safe handling advice

- Use and open container with care.
- Avoid dust formation.
- Supply eye wash bottle.

5.2 Advice on protection against fire and explosion

- No special actions required.

- **Show a confirmation prompt when clicking on a rollback link:** If an admin user wants to perform a rollback of multiple options from the version history of a page, the rollback is executed immediately after clicking the link by default. With this setting, the admin user needs to click on the "Rollback" link again to confirm the rollback before it is executed.


Bookshelf special page

Grid: Shows the details view (=list view) of available books by default (2)

Images: Shows the thumbnails view of available books by default (1)

Here you can see all available books. To add a new book, go to [book manager](#).


1 Thumbnails
 Details
2

Title
 : A
Animals

Tabs on the page *Special:Bookshelf*

Context menu

Page links in the content area of the wiki show a context menu that allows to perform actions on the target page without having to go to the target page first. You can set whether you want to show the context menu with *right-click* or with *right-click + Strg*.



Dashboards

By default, the logo of your wiki links to the main page. You can change this and link to your user dashboard instead.

Video player

When a page contains a video that was inserted with the [BlueSpicePlayer](#) extension, you can set it to autoplay when you load a page.

Timeline

You can set the timestamp on the timeline entries in date format or as age.


Note: It can take up to 24 hours for all timeline entries to show the new timestamp format. When you create a new entry, you should see the changed format immediately.



Editing

General options

- **Enable section editing by right clicking on section titles:** Right-clicking a section title with the mouse sets the page in edit mode. The specified section can be edited immediately.
- **Editing pages by double clicking (JavaScript):** Double-clicking on the page sets the page in edit mode. The double-click needs to be inside the text area of the page. Clicking in the title section of a page will not set the page into edit mode.
- **Enable the Paragraph-based Edit Conflict Interface** to resolve edit conflicts: Allows section-based merging of differences which improves the process for solving edit conflicts between users. If this setting is disabled: Users will see the source code of the latest version, a diff view between the latest and the own version, and a source editing window to manually work on the user's unsaved version.
- **Show the pending changes diff when editing pages:** In the BlueSpice 4 Discovery skin, no visual diff is shown during editing, so this setting can be ignored. It simply adds a duplicate notice about pending changes, when opening a page in edit mode:



Editor

- **Edit area font style:** Displays source code in monospace, serif, or sans-serif font.

Note: This setting is ignored if the [CodeMirror](#) extension is enabled (from BlueSpice 4.2).

- **Mark all edits minor by default:** This automatically sets the minor flag in the save dialog. It can be selected or deselected in the save dialog on the page itself:

marking a minor edit

Note: Note: The 'Watch this page' checkbox in the save dialog can be activated or deactivated by default under the preferences tab *Watchlist* under *Advanced options: Add pages and files I edit to my watchlist*.

- **Prompt me when entering a blank edit summary:** Displays a text message when you click *Save changes* reminding you to enter a summary description. If you do not enter a description after that, the page will save without the summary the next time you click *Save changes*.

edit summary prompt

- **Warn me when I leave an edit page with unsaved changes:** When you reload or leave a page with unsaved edits, a warning message is displayed. You can confirm to leave the page or stay on the page and save your changes.
- **Show edit toolbar:** Disables VisualEditor in visual editing mode. Disabling is not recommended, as this reverts the editor back to a previous version of MediaWiki editor.
- **Temporarily disable the visual editor while it is in beta:** You can disable visual editor while it is in [Extension:VisualEditor|beta mode](#). We recommend you do not disable VisualEditor unless you prefer to work with a previous visual editor version.


Preview

These preview settings are only applied if you have temporarily disabled VisualEditor and the edit text area is on the same page as the page preview. In BlueSpice 3.1+ you can generally ignore these settings.

- **Show preview on first edit:** The preview of the article is displayed when you click on "Edit"
- **Show preview before edit box:** If this option is deactivated, the preview will be shown under the edit form
- **Show previews without loading the page:**

Reminder

- **Default reminder period:** Prefills the date field for reminders with *current date + x days* specified here.



reminder default date

- **Set reminder on page creation:** When you create a new page, a reminder for that page is automatically created based on the default reminder period you entered.
- **Do not create reminder for the following namespaces:** Excludes namespaces from the automatic reminder on page creation.


Timeline

- **Warn me when I leave an edit of an entry with unsaved changes:** If unchecked, any unsaved changes to a social entity (such as blog entry, comment, microblog or discussion topic) will be automatically lost if you navigate to a different page or reload the page before saving your changes.
- **Skip dialog on discussion creation:** Automatically creates a discussion page when a user adds a discussion directly on a page and the discussion page for the entry does not yet exist. If this checkbox is unchecked, the user has to create the discussion page first before the discussion topic can be posted.

Recent changes


Display options

- **Days to show in recent changes:** You can set how many results are displayed on the page *Recent changes*.
- **Number of edits to show in recent changes, (...) by default:** Setting for the filter (1) on the *Recent changes* page and similar log pages. The filter can be manually changed during page visits.



Advanced options

- **Group changes by page in recent changes and watchlist:** This view creates a collapsible view of all the changes on a page that occurred before another page was edited. All changes still count towards the number of changes that are set in the view filter for the page.



- **Use non-JavaScript interface:** Removes the advanced filter option to save filters and to color-highlight changes.

Changes shown

- **Hide minor edits from recent changes:** Hide [edits marked as minor](#) from appearing on your *Recent changes* page by default.

Edit review

These settings are provided by the extension [FlaggedRevs](#) (approval feature).



FlaggedRevs is available up to BlueSpice 4.2.

- **Basic interface:** This setting has no effect in the *BlueSpice Discovery* skin
- **When to show the stable version of content pages by default:**
 - Use the default settings for each page: This setting has no effect in BlueSpice (default settings cannot be [set by administrators on a page level](#))

- **Always show the stable version (if there is one):** This default setting is only applied if the [FlaggedRevs](#) feature is active in a namespace. It shows the approved (stable) version by default when navigating to that page.
- **Always show the latest version:** It is a useful settings for users with review permissions who can accept draft versions. It loads the latest revision of a page by default instead of the stable version.
- **Show the pending changes diff when viewing the latest pending version:** This setting has no effect in the *BlueSpice Discovery* skin.

Watchlist

Edit watchlist

- **Edit entries on your watchlist:**
 - *View and remove titles on your watchlist:* Links to the page [Special:EditWatchlist](#) where you can manage your watchlist entries. The watchlist is organized by namespaces.
 - *Edit raw watchlist:* Links to the page [Special:EditWatchlist/raw](#) where you can remove pages by page name from a textbox. This list is also organized by namespaces.
 - *Clear watchlist:* Links to the page [Special:EditWatchlist/clear](#) where you can empty your watchlist with the click of a button.

Display options

- **Days to show in watchlist** (default:7): Presets the value in the selection menu Period of time to display on the page *Special:Watchlist*.
- **Maximum number of changes to show in watchlist** (default:250): Limits the number of changes that are displayed in your watchlist.

This example shows a default setting of 8 days and 20 changes.

– Watchlist options

Below are the last 20 changes in the last 192 hours, as of 3 December 2019, 13:40.
Period of time to display: 8 days

watchlist display options

Advanced options

- **Expand watchlist to show all changes, not just the most recent** (default): Determines if a changed page is displayed several times in the filtered time period or if only the latest change is listed.
- **Add direct unwatch/watch markers (x/+) to watched pages with changes (JavaScript required for toggle functionality):** An icon for the direct removal of the page from the watchlist is available.

22 March 2023

o

x

13:23 MLR:Test1 [pending edits] (diff | hist) ..(+22).. Maximilian Achterbahn (→Heading 1) [rollback 6 edits]

o

x

12:54 Test (diff | hist) ..(+5).. Maximilian Achterbahn [rollback 1 edit]

1

2

17 March 2023

•

x

17:03 FB:Yet another page [pending edits] (diff | hist) ..(-43).. WikiSysop [rollback 4 edits]

3

Direct markers: (1) Changes have been read, (2) remove from watchlist, (3) changes have not been read

- **Use non-JavaScript interface:** A basic view of the watchlist loads (without special filter menu and without highlighting options).
- **Add pages I review to my watchlist** (until BlueSpice 4.2): Automatically adds pages the user approves to the watchlist.

Changes shown

These settings configure a standard filter for the watchlist. By default, no filter is applied. Possible standard filters are:

- **Hide minor edits from the watchlist**
- **Hide bot edits from the watchlist**
- **Hide my edits from the watchlist**
- **Hide edits by anonymous users from the watchlist**
- **Hide edits by logged in users from the watchlist**

Active filters

Changes by others X

Non-minor edits X

1

Hide

Filter changes (use menu or search for filter name)

Namespaces Tags

Live updates

Hide: ☒ social entities Show


250 changes, 7 days


Standard filter with preset values from the preferences settings

Watched pages

These settings determin which pages are automatically added to the watchlist by preselecting the checkbox *Watch this page* of the related dialog window. If no dialog window is available, the addition to the watchlist automatically happens in the background:

- **Add pages and files I edit to my watchlist (default)**





- **Add pages and files I move to my watchlist**
- **Add pages and files I delete to my watchlist**
- **Add pages I create and files I upload to my watchlist** (default)
- **Add pages where I have performed a rollback to my watchlist**
- **Add new files I upload to my watchlist** (default)

Token


- **Watchlist token:** The token can be used to create a public RSS feed to your watchlist. Anyone who knows this token can access the feed. The syntax for the feed URL is: `https://[YourWikiDomain]/w/api.php?action=feedwatchlist&wlower=[USERNAME]&wltoken=[TOKEN]`.

Notifications

Important! Notification don't consider the edit type "Minor edit". Therefore, notifications are sent even in the case where a user makes a minor edit.

Here you can set how and when you would like to receive notifications in email and/or in the notifications area of your user profile (Web notifications). If you haven't received email notifications yet, make sure that your email adress has been verified. This information is available in the *User profile* tab, under the section *Email options*.

To view your Web notifications, go to your User profile menu and select Notifications.




The user profile image in the main toolbar and the *Notifications* menu item show the number of new notifications. Notifications can set for a variety of events, such as new assignments or reminders. You can also select to be notified about changes only in certain namespaces or categories.


To configure which notifications you want to get, click on *Preferences* in the *Settings* menu (3).

Email options

You can specify how often you receive emails: *never*, *immediately*, *daily*, or *weekly*.



If you unexpectedly don't receive emails for notifications, check under the *User profile* tab to make sure that you have already confirmed your email account.



Notify me about these events

Notifications can be displayed in the Notifications page of the wiki. This functionality is provided by the MediaWiki extension *Echo*.

New message indicator

This setting currently has no effect in BlueSpice. It is a configuration setting for the MediaWiki extension [Extension:Echo|Echo](#) (echo-show-alert).

Notifications on namespace events

Select for which namespaces you want to receive notifications.

Notifications on categories

Select for pages in which categories you want to receive notifications.

Review

- **Notify me about changes if I am the owner of a review:** Select if you want to be notified in email of any workflow changes of a review workflow if you are the owner of the review.

- **Notify me about changes if I am the reviewer of a review:** Select if you want to be notified in email of any workflow changes of a review workflow if you are the owner of the review.

Under the settings for *Notify me about these events*, you can set if and how you want to be notified if someone assigns a review task to you.

Extended Search

Here you can set which namespaces you want to include in your search results. This can be useful if you work in only some areas of the wiki or if you are looking for information in a few areas of your wiki only.

Semantic MediaWiki

These user preferences are provided by Semantic MediaWiki. If you would like to change these settings, you can visit the corresponding [help page](#).

Resetting all preferences

If you click *Restore all default settings (in all sections)*, all your customizations on all tabs are reset to their default settings. Since this could affect lots of customized settings, a warning page appears before the reset.

You can use this page to reset your preferences to the site defaults. This cannot be undone.

Restore all default settings (in all sections)

restoring default settings

Use the browser's back button if you do not want to restore the default settings.

Config manager

Contents	
1	Layout 20
1.1	Filter options 20
1.2	Searching for settings 20
2	Settings by extension 21
2.1	EventBus 21
2.2	EnhancedUpload v4.3+ 21

2.3 BlueSpiceFoundation	21
2.3.1 Updating logo and favicon	21
2.3.2 System	23
2.4 BlueSpiceArticleInfo	23
2.5 BlueSpiceAuthors	24
2.6 BlueSpiceAvatars	24
2.7 BlueSpiceBookshelf	25
2.8 BlueSpiceChecklist	26
2.9 BlueSpiceExtendedSearch	27
2.10 BlueSpiceExtendedStatistics	29
2.11 BlueSpiceInsertCategory	29
2.12 BlueSpiceInsertLink	29
2.13 BlueSpicePageTemplates	30
2.14 BlueSpicePermissionManager	31
2.15 BlueSpiceRSSFeeder	31
2.16 BlueSpiceReaders	31
2.17 BlueSpiceSaferEdit	32
2.18 BlueSpiceUEModuleBookPDF	32
2.19 BlueSpiceUEModuleHTML	32
2.20 BlueSpiceUEModulePDF	33
2.21 BlueSpiceUniversalExport	33
2.22 BlueSpiceVisualEditorConnector	33
2.23 BlueSpiceWholsOnline	34
2.24 BlueSpiceExpiry	34
2.25 BlueSpiceFlaggedRevsConnector	34
2.26 BlueSpiceSocial	36
2.27 BlueSpiceSocialBlog	36
2.28 BlueSpiceSocialTopics	37
3 BlueSpiceDiscovery	37
3.1 Deactivating the Entrypoint links	37
3.2 Positioning of skin elements	38
3.3 Content Stabilization v4.3+	38


With the Config manager, a wiki user with *sysop* rights can manage wiki-wide settings in one place. In the [navigation](#), it is located at *Global navigation > Management > Configuration*. This link loads the page *Special:BluespiceConfigManager*.

Layout

Filter options

All settings can be accessed through the following filter options:

- **Feature:** group by type of functionality the setting belongs to (search, administration...)
- **Extension:** group by extension name
- **Package:** group by BlueSpice edition and services (BlueSpice free, BlueSpice pro, Matomo)




All settings are available in any type of grouping. Changing the grouping type does not add or remove setting options. It just groups them differently. After settings are adjusted, they can be saved by clicking *Save*, or cancelled by clicking *Reset*.

Note: If a server administrator has configured a setting to no longer be writable, it will be shown as greyed-out in the config manager. You will have to talk to your server administrator about changing such a setting.

Searching for settings

A search bar is located above the list of settings. Type in a keyword such as "logo" to find the corresponding setting. The search returns settings regardless of the currently selected group.

Note: The search field has to be empty if you want to see the filter menu instead of the search.



Config manager search box


Settings by extension

EventBus

Eventbus sends notifications to external urls in case something happens in the wiki. For example, if a page is created, an external service could then be started and create a pdf of that page. See the extension's page on mediawiki.org.

EnhancedUpload v4.3+

Sets the defaults for the [advanced image settings](#) when uploading and embedding an image into the wiki via drag-and-drop functionality. The default settings determine the orientation, type, and size of the image. These can be adjusted after embedding via the "Advanced settings" of the image on the page.



Configuration settings for the Enhanced upload

BlueSpiceFoundation


Updating logo and favicon

Note: Since BlueSpice 4.2, the logo and favicon can also be managed via the page [Special:Flexiskin](#) together with further skin customizations.


- **Logo path:** The logo image should be stored in the /images folder of your installation. If you store it in the /skins folder of your BlueSpice installation, it could be overwritten with an upgrade.

To upload the logo directly in the wiki:

1. **Upload** the logo on the page from the menu *Global actions > File list (Special:ExtendedFilelist)*.
2. **Click** on the thumbnail image of the logo. This opens the logo on a separate page.



3. **Copy** the relative logo path from the address bar. In a typical Wiki configuration, this path starts with */w/....*



4. **Paste** the logo path into the text field for the logo.

5. **Click Save.**

6. **Refresh** the page (Strg+F5).

If the uploaded logo is too large, you can add the following code snippet to the page *MediaWiki:Common.css*. This automatically adjusts the image to the height of the main toolbar:

```
.bs-logo a {background-size: contain;}
```

- **Favicon path:** The favicon image should be stored in the */images* folder of your installation. If you store it in the */skins* folder of your BlueSpice installation, it could be overwritten with an upgrade. [Favicon images](#) have the file extension *.ico*.

System

- **Allowed file extensions:** For security reasons, the types of files that users can upload are restricted. Here, you can allow additional file formats. If a file format is blacklisted in the server configuration, adding this file extension here will not allow this file type to be uploaded. See [mediawiki.org/wiki/Manual:\\$wgFileExtensions](https://mediawiki.org/wiki/Manual:$wgFileExtensions) for more info.

XML file type: v4.x++

The *xml* file type is blacklisted since MW 1.39 and has to be allowed in *LocalSettings.php*:


```
$GLOBALS['wgProhibitedFileExtensions'] = array_diff( $GLOBALS['wgProhibitedFileExtensions'] ?? [], [ 'xml' ] );  
$GLOBALS['wgMimeTypeExclusions'] = array_diff( $GLOBALS['wgMimeTypeExclusions'] ?? [], [ 'application/xml', 'text/xml' ] );
```


- **Allowed image extensions:** The standard web image types are listed here. In general, you want to restrict image uploads to web images. See developer.mozilla.org/en-US/docs/Web/Media/Formats/Image_types for more on browser-supported image types.

BlueSpiceArticleInfo

BlueSpiceArticleInfo, together with *BlueSpiceAuthors*, *BlueSpiceReaders*, and *BlueSpiceExtendedSearch* is part of the *Page information* in the quality management tools.

- **Update interval in seconds:** Sets the refresh rate for the "Last edit" value. By default, this date is updated every 10 seconds via JavaScript.






BlueSpiceAuthors

BlueSpiceAuthors, together with *BlueSpiceArticleInfo* and *BlueSpiceReaders*, is part of the *Page information* in the quality management tools.

- **Display authors:** Show or hide authors on the page information page.




BlueSpiceAvatars

An avatar image is automatically generated if the user does not upload a profile picture or if the user decides to create an avatar image in the preferences.

- **Generator**
 - **InstantAvatar:** Generates an avatar image based on using the initials of the Real name or the Username
 - **Identicon:** Generates an avatar image based on parts of the user's IP address.





User image:

Change profile picture

Change profile picture

Identicon

Change profile picture


Picture upload

Picture from wiki or picture URL

Auto generate avatar

BlueSpiceBookshelf

- **Show book chapter pager after content:** Displays previous/next book page navigation at the end of each book page. (1)
- **Show book chapter pager before content:** Displays previous/next book page navigation at the beginning of each book page. (2)



User manual

< Previous 1 Next >

Login and preferences

① Last edited 3 months ago by MLR ★ Unwatch 🔔 No status information

Login

To work with your BlueSpice wiki, you need to log in. Click on the login button in the top right corner of the screen.

In the following window, enter your user name and password. Click *Log in* and you're ready to go.

SPECIAL PAGE

Log in

Username

Password

☐ Keep me logged in


Help with logging in


Forgot your password?

< Previous 2 Next >

Book navigation


- **Use the display title from book source on article:** Shows the title from the book navigation as page title instead of the page name.





Note: If the page additionally contains a `{{DISPLAYTITLE}}` tag, the display title of the page is shown instead of the book title.

- **Prepend article table of contents and headlines with book numeration:** The page TOC does not start with the main heading 1, but with the actual number from the book chapter (see screenshot). If users have activated in their [user preferences](#) to "auto-number headings", the numbering system is matched accordingly.



- **Suppress namespace prefix of book articles in output:** The namespace prefix of an article is not shown in PDFs.

BlueSpiceChecklist

- **Mark checklist changes as minor edit:** If this setting is active, changes to a checklist (for example, checking a checkbox) in view mode are logged as minor edits. If this setting is inactive, a change to the checklist is recorded as a regular version in the page history.

minor edit

- **External file paths:** External locations to scan for and index files from. These locations are entered in key/value pairs of Physical path and URL prefix.
 - *Physical path:* Storage path. For mounted drives, for example: *X:\Documents*
 - *URL prefix:* All files indexed from the indexed physical location are prefixed in the search results. It should be used if files are available from a web server. By default, the URL prefix is set to the same value as *Physical path*.

Example file	Phys. Path	URL Prefix	Link in results list
S:\Sales\Info\glossaryy.pdf	S:\	file:///S:/	file:///S:/Sales/Info/glossary.pdf
		https://sharepoint/Sales/ documents/	https://sharepoint/Sales/ documents/Sales/Info/ glossary.pdf
		https://intranet/showdocs inline.aspx?path=	https://intranet/showdocsinline.aspx? path=/Sales/Info/glossary.pdf
/var/www/bluespice/w /mounted_ share/Sales/Info /glossary.pdf	/var/www /bluespice/w/ mounted_share/		https://wiki.company.local/w /mounted_ share/Sales/Info/glossary.pdf

Feature: System Skinning Data analysis Personalization Book Export Content structuring Quality assurance **Searching and Navigation** Editor Administration

BlueSpiceExtendedSearch

External file paths ⓘ

No values set!

Add new entry

Physical path: S:\ * URL prefix: file:///S:/ ✓ 1

☐ Use simple autocomplete ⓘ

☐ Automatically set language filter ⓘ

Exclude patterns

No values set!

Add new entry

Physical path: * Exclude regular expression pattern: * ✓

Add an external file path: (1) confirm the checkmark and (2) save the settings.

- **Use simple autocomplete:** forces a more compact autocomplete (1-column Sales thumbnail preview).

Configu

Configure search

Configuration

Getting started - Login and configuration

Robot Configuration

Create and configure articles

ExtendedSearch configuration

Setup:Installation Manual/System Configuration/Apache Tomcat

+ Create page "Configu"

Search full text

compact autocomplete

Configu

Configure search

Configuration

Getting started - Login and configuration

Robot Configuration

Create and configure articles

ExtendedSearch configuration

Setup:Installation Manual/System Configuration/Apache Tomcat

VisualEditor configuration

+ Create page "Configu"

Search full text

Salesautocompletey

- **Automatically set language filter:** The search only returns pages whose language (PageLanguage) is identical to the user language (Language). Users can set their language in their [preferences](#). By default, the language of content pages is the same as the installation language (ContentLanguage) of the wiki. Some extensions can set the language of individual pages independently of the content language of the wiki.. (See: https://www.mediawiki.org/wiki/Manual:Language#Page_content_language). In many wikis, activating this filter has little effect.
- **Exclude patterns:** Files at external file locations can be excluded from search based on regular expression patterns.

BlueSpiceExtendedStatistics

- **Exclude these users:** Some user groups, like WikiSysop can skew the statistics, for example the statistics for search queries or because they complete automated maintenance tasks. These types of user groups can be excluded from the statistical results.
- **Maximum number of interval steps:** Sets the size of the x-axis for the results. For a few days, select the interval *Day* or *Calendar Week*, for periods over one year, select *Year* or *Month*. If you do not get any results for your query, try to adjust the interval accordingly.

BlueSpiceInsertCategory

- Insert category with its parent categories
- Preset categories of a page in the upload dialog

BlueSpiceInsertLink

- **Allow unmapped links:** if there is no prefix in the map, the link will still be inserted. Example: S:\HR. If this setting is unchecked, the link will not be inserted.
- **Allowed locations for external files:**

Example file	Filesystem prefix	Web accessible Prefix	Link output
S:\Sales\Info\glossaryy.pdf	S:\	file:///S:/	file:///S:/Sales/Info/glossary.pdf
		https://sharepoint/Sales/documents/	https://sharepoint/Sales/documents/Sales/Info/glossary.pdf
		https://intranet/showdocs inline.aspx?path=	https://intranet/showdocsinline.aspx? path=/Sales/Info/glossary.pdf
/var/www/bluespice/w /mounted_			

Example file	Filesystem prefix	Web accessible Prefix	Link output
share/Sales/Info/glossary.pdf	/var/www /bluespice/w/ mounted_share/		https://wiki.company.local/w/mounted_ share/Sales/Info/glossary.pdf

When a new entry is added, it has to be confirmed by clicking the checkmark next to it before saving the page.

BlueSpicePageTemplates

- Force target namespace:** The page is always created in the target namespace that is associated with the template, even if the user provided a different namespace prefix. In the screenshot below, the user wants to create the page "NewPage" and then selects a template for the QM namespace. The page is, therefore, created as "QM:NewPage" if this setting is activated.

- Hide default templates:** Hides the default *Empty page* template.


- **Hide template if the page is not to be created in the target namespace:** Depending on the namespace prefix of the page to be created, templates that are associated with other namespaces will not be shown to the user for selection.

BlueSpicePermissionManager

- **Backup limit:** Sets the number of backups for the permissions manager. Each time the page *Special:PermissionManager* is saved, a backup is created. If the backup limit is set to 5, the last five versions of the permissions configuration are saved as backups.

BlueSpiceRSSFeeder

- **URL whitelist:** RSS feeds need to be whitelisted here by an administrator before they can be displayed in a wiki page.
- **Maximum number of allowed redirects:** If there are URL redirects for any of the whitelisted URLs, the number of redirects needs to be adjusted (usually to 1 or 2).



Administration

URL whitelist


Maximum number of allowed redirects

+

RSS Feed settings

BlueSpiceReaders

- **Number of readers to display:** Sets the number of readers that are displayed on the Page information in the Quality management tools.



Page information for "Manual:Extension/BlueSpiceReaders"

General

Last edit

Properties

Expiry of page

Authors of this page

Readers of this page

Reminder

Page 0 of 0

displays readers of the page

BlueSpiceSaferEdit

- **Interval for lookup for concurrent editings:** Sets the time in seconds for checking if another person is editing the page.
- **Show name of current editor:** Shows or hides the name of the user who is currently editing the page.

BlueSpiceUEModuleBookPDF

- Table of Contents
 - *Only article titles (indent by grade):* Only shows the article titles in the main contents table of the PDF.

Table of contents	
1 Introduction	3
2 Wiki pages model	4
3 User rights	7
3.1 Group manager	15
3.2 Permission manager	18
3.3 User manager	24
4 Namespace manager	28

PDF table of contents without article TOCs

- *Embed article TOCs (No indent of article titles):* Shows the table of contents for each article in the main contents table of the PDF.

Table of contents	
1 Introduction	5
2 Wiki pages model	6
1 The pages modell	6
2 Page types	6
2.1 Special page	6
2.2 Content page	7
2.3 Wiki page	7
2.4 Category page	8
2.5 File / image (description) page	8
3 User rights	9
3.1 Group manager	17
1 Accessing the group manager	17
2 Functionality	18
3 Assigning roles and users to groups	18

Embed article TOCs


BlueSpiceUEModuleHTML

- **Hide namespace prefix in HTML:** If activated, the namespace is shown in the HTML main heading.

Note: If the page contains a "displaytitle" tag in the page source, the page display title is shown and this setting has no effect.

BlueSpiceUEModulePDF

- **Hide namespace prefix in PDF:** If activated, the namespace is shown in the PDF main heading for a page.



Note: If the page contains a "displaytitle" tag in the page source, the page display title is shown and this setting has no effect.

BlueSpiceUniversalExport

- **Metadata (standard, JSON):** Additional data to be passed to the rendering template in JSON format. This data can be used in the export template. The template itself is maintained server-side.
- **Metadata (override, JSON):** Allows overriding standard data sent to the rendering template in JSON format. Values that are set by default can be overridden with this option.

BlueSpiceVisualEditorConnector


- **Enable VisualEditor for BlueSpice extensions**
- **Configuration variable to use a simplified save process**
- **Upload type**
 - Original (Here a confirmation of the rights of use/upload is obtained, file name and namespace of the file can be changed, a category can be assigned and a description of the file **MUST** be given).
 - Simple (No confirmation of required rights is obtained here, the name and namespace of the file can be changed, a description and a category can be assigned, but does not have to be specified)
 - One click (No confirmation about required rights is obtained here, the image cannot be renamed and no category can be assigned. Only the namespace can, but does not have to be adjusted before uploading)

BlueSpiceWholsOnline

- **Time in seconds until a user is marked as offline:** The system checks every x seconds if a user logged out and no longer displayed as online. This can be less frequent than the update interval for newly logged-in users.
- **Update interval in seconds:** The system checks every x seconds for users.

BlueSpiceExpiry

- **Show watermark for expired pages in PDF:** Shows the watermark for expired pages in PDFs.
- **Show watermark for expired pages in print version:** Shows the watermark for expired pages when a page is printed.
- **Show watermark for expired pages:** Shows a watermark on the page itself.



BlueSpiceFlaggedRevsConnector




BlueSpiceFlaggedRevsConnector is available up to BlueSpice 4.2.

Export

The export settings affect how the pages of a book are generated in the PDF export.

- **Bookshelf: List approved revisions log:** Shows a log of stable page versions of pages in the PDF and when these pages were put into accepted status. If editors did not provide a comment when accepting the page, the *Stable comment* field for a revision is empty.



Stable date	Page	Stable comment
18.11.2019	Permission matrix	
18.11.2019	Permission matrix	
15.11.2019	Wiki pages model	
14.11.2019	Permission manager	
14.11.2019	Group manager	

accepted revisions log

- **Bookshelf: List pages without stable revision:** Displays a list of PDF pages at the beginning of the PDF that only exist as a first draft and have no released version.

<p>Not stable pages</p> <hr/> <p>QM:Checklists</p> <hr/> <p>Pages without acceptance feature</p>
--

- **Bookshelf: List pages without FlaggedRevs:** Displays a list of PDF pages that do not have a release mechanism at the beginning of the PDF.

<p>Not FlaggedRevs namespace</p> <hr/> <p>Introduction</p> <p>Wiki pages model</p> <p>User rights</p> <p>Group manager</p> <hr/> <p>Pages with no FlaggedRevs feature.</p>

- **UEModulePDF: Show FlaggedRevs info below main heading:** Prints the latest revision dates (last acceptance and last edit date) below the heading.

<p>Introduction</p> <hr/> <p><i>Stable: 06.12.2019 - 12:00 / Revision: 06.12.2019 - 11:43</i></p> <hr/> <p>FlaggedRevs info below heading</p>
--

Quality assurance

- **Include handling:** If resources are embedded in a page and those resources are located in namespaces with approval mechanism, then the following settings can be selected. For example: If an approved page contains a template or a file that has been changed after the page itself has been approved, the page will not get another draft version, but instead one of two configurations applies:
 - Current versions: Always show the latest version of the embedded resource.
 - Stable versions: Always show the stable (=approved) version of a resource.
- **Show unstable pages for following groups:** If the group *user* is removed from the *BlueSpiceFlaggedRevs* configuration, users in this group will not be able to see draft versions when they are added as reviewers in a review process. When the group *user* is removed, only *sysop* and *reviewer* users can access drafts. If you want other groups, for example *editor*, to see draft versions, you need to add them to the configuration. If no user groups are specified in the configuration field, not even reviewers and sysops users will see a visual status indication of a page. They will have access to drafts through the revision history for the page instead.

Searching and Navigation

- **Indexing only stable versions:** Draft versions are excluded from the search results. If a page does not have a stable version, it is not shown as a search result.

BlueSpiceSocial

- **Show endpoint "Timeline":** Shows a link to the page *Special:Timeline* in the main navigation.

BlueSpiceSocialBlog

- **Use teaser text for blog entries in the timeline:** When you create a blog entry, you can create a teaser text for it by clicking the cogwheel symbol in the blog entry form. If this setting is active, the teaser text will be shown on the page *Special:Timeline* instead of the first part of the content.

Title

ISO 7010 Symbole

Content

Please makes sure to adhere to the ISO 2010 graphics standards¹ when using symbols in your manuals.

We still see a lot of outdated images throughout the company and will flag documents as expired if they contain the wrong images.

ISO 7010 M002

For questions, please contact your documentation team. Thank you!

Teaser

Pages in violation of ISO 2010 graphics standards will be expired


× Main Page

blog teaser text


- **Show endpoint "Blog":** Shows a link to the page *Special:Blog* in the main navigation.

BlueSpiceSocialTopics

- **Automatically create all discussion pages.** If a user creates the first discussion topic for a page using the link in the page footer of a wiki page, the needed discussion page is automatically created first.




A message "This discussion page was created automatically" is inserted on the discussion page.



If this setting is deactivated, the user is directed to the "Create page" default page first.

BlueSpiceDiscovery

Deactivating the Entrypoint links



Positioning of skin elements



positioning skin elements

- page-sentence: display of page status ([Approval status](#), [Expiry](#))
- categories: display of [page categories](#)
- rating: display of [page ratings](#)
- recommendations: display of [page recommendations](#)

Content Stabilization v4.3+

The following configuration options are available for page approvals:

- **Include handling (1):** Wenn Ressourcen in eine Seite eingebettet sind **und sich diese Ressourcen in Namensräumen mit Freigabe befinden**, können die folgenden Einstellungen ausgewählt werden. Es gibt zwei mögliche Einstellungen:

	Verhalten
Stable versions of included pages	Shows the approved (stable) version of a resource, even if it was approved after the page that includes the resource was approved. (This works only if the resource is located in a namespace with active approval feature).
Versions that were current at the time of approval	Shows the version of the resource which was embedded at the time of the last approval of the wiki page where it is embedded. (This works only if the resource is located in a namespace with active approval feature).

For example, if an approved page contains a template that was modified after the page itself was approved, the page will not show a draft version. Approvals work directly via the embedded resource.

- **Allow viewing of first draft version (2):** If this setting is activated, then all users with read rights can view the first draft. When disabled, only groups from the "Show unstable pages for following groups" setting can see first drafts.
- **Update semantic properties from stable pages only (3):** The property value of the page is read from the stable version of the page and not from the draft version.
- **Entwurfseiten für folgende Gruppen anzeigen (4):** If the group `user` has been removed from the configuration, users in this group will not be able to see draft versions when they are added as reviewers in a review process. In this case, only users with the roles `sysop` and `reviewer` can access drafts unless other groups are specified. These system groups can only access drafts through the site's version history.

➔ [Technical Reference: BlueSpiceConfigManager](#)

Video Player

The extension BlueSpice **Player** allows you to embed local video files in a page. These files have to be uploaded to your wiki first.

If you want to embed videos from a video sharing service such as Youtube, you can use the installed extension *EmbedVideo*. EmbedVideo is documented at www.mediawiki.org/wiki/Extension:EmbedVideo.

Contents

1	How to use the video player	40
1.1	Optional arguments	40
1.2	Compatibility matrix	40
2	Technical details	40
3	Related info	41

How to use the video player

Use the tag `<bs:showtime>Video.mp4</bs:showtime>` anywhere in an article to activate the player. Upload the video into your wiki first. You can upload the video just like an image (*Global actions > Upload file*).

The following video formats are supported: **mp4, ogv, flv, webm**

0: bs-player-file-does-not-exist

Optional arguments

You can configure the player with the following arguments:

Argument	Description	Type	Default
<i>width</i>	Width of the video	int	320
<i>height</i>	Height of the video	int	240
<i>autostart</i>	Automatically starts the video when the page is loaded	bool	false
<i>repeat</i>	Automatically repeats the video in a loop	bool	false

Example syntax: `<bs:showtime width="960" height="760" autostart="true">Testvideo.mp4</bs:showtime>`

Compatibility matrix

For technical reasons, not all video formats can be played in all browsers.

Format	Firefox	Chrome	Internet Explorer
mp4	yes	yes	yes
flv	yes	yes	yes
ogv	yes	yes	no
webm	yes	yes	no

Please note: due to VideoJS standards, the player is set back from HTML5 to Flash when playing an flv-file or using Internet Explorer.

Technical details

The video player is enabled by the extension BlueSpicePlayer. An administrator has to add the necessary video extensions to the allowed file extensions in the [Config Manager](#).

Related info

- [Reference:BlueSpicePlayer](#) (for embedding videos that are uploaded to the wiki)
- [Reference:EmbedVideo](#) (for embedding videos form external services such as YouTube)

➔ [Technical Reference: BlueSpicePlayer](#)

Reference:CodeMirror

Extension: CodeMirror

➔ [all extensions](#)

Overview			
Description:	Syntax highlighting in the wikitext editor.		
State:	stable	Dependency:	MediaWiki
Developer:	Pavel Astakhov	License:	GPL v2+
Type:	MediaWiki	Category:	Editor
Edition:	BlueSpice pro, BlueSpice free, BlueSpice Farm, BlueSpice Cloud	Version:	4.2+
For more info, visit Mediawiki .			

Features

The extension **CodeMirror** provides syntax highlighting in MediaWiki's wikitext editor. It adds an icon to the options menu of VisualEditor where it can be deactivated on a per-page basis.

↶ ↷ Paragraph ▾ A ▾ ↻ Cite ▾ ≡ ▾ Insert ▾ Ω 📎 ? ≡ ✎ ▾ 🚫 Save changes...

kattachments title="More attachments" hideversion="1" hideeditor="1" showcategories="1">

* [[Media:Testseite Verena 1690535785927.pdf]]

</attachments><bs:bookshelf src="Book:Book1052568" />

Richtlinien [\[Main Page\]](#) Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

== Überschrift ==

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

<attachments>

* [[Media:Baulicher_Brandschutz.pdf]]

Options

Categories

Page settings

Advanced settings

Languages

Templates used

Syntax highlighting

View as right-to-left Ctrl+Shift+X

deactivate CodeMirror

Accessibility

Test status:	2-testing complete
Checked for:	Authoring tool
Last test date:	2022-08-08
WCAG level:	AA
WCAG support:	supports
Comments:	<div>Tested by original developpers for AA support:</div> <div>https://meta.wikimedia.org/wiki/WMDE_Technical_Wishes/Improved_Color_Scheme_of_Syntax_Highlighting</div> <div>Could be completely deactivated in on-premise installation.</div>
Extension type:	core
Extension focus:	editor

Reference:FlaggedRevs

Extension: FlaggedRevs

→ [all extensions](#)

Overview			
Description:	Allows for article content management by editors and reviewers.		
State:	stable	Dependency:	MediaWiki
Developer:	Aaron Schulz, Joerg Baach	License:	-
Type:	MediaWiki	Category:	Quality Assurance
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	Version:	4.1- 4.2.x
? View help page			

Features

FlaggedRevs is a MediaWiki extension that activates an approval mechanism.

New versions of an article are initially marked as drafts and remain so until a user with revision rights checks and approves the page.

The MediaWiki extension is customized in BlueSpice. It uses the [FlaggedRevsConnector](#) to work alongside [workflows](#), realising the complete functionality of an editorial process with a final approval step.

Warning! The setting FR_INCLUDES_FREEZE for handling the state of included files of an approved wikipage has [no long term support by](#) and should not be introduced in a new wiki for that reason.

Reference:Popups

Extension: Popups

→ [all extensions](#)

Overview			
Description:	Displays previews when the user hovers over a page link		
State:	stable	Dependency:	MediaWiki
Developer:	Prateek Saxena, Yair Rand	License:	GPL v2+
Type:	MediaWiki	Category:	Search and Navigation
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	Version:	4.1+
For more info, visit Mediawiki .			

The **Popups** extension displays page previews – summaries of the introductory content of a page when the user hovers over a link to that page.

In MediaWiki, any intro text before the first content heading (h2) is displayed in the popup together with the page image (if available). If there is no intro text available, BlueSpice displays the first sentences of the page, including the heading (unformatted).


Reference:RevisionSlider

Extension: RevisionSlider

🔗 [all extensions](#)

Overview			
Description:	Shows a slider for selecting and comparing revisions on a diff page.		
State:	stable	Dependency:	MediaWiki
Developer:		License:	-
Type:	MediaWiki	Category:	Quality Assurance
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	Version:	4.1+
For more info, visit Mediawiki .			

The revision slider is collapsed by default on the version comparison page. It can be expanded by clicking *Browse history interactively*.



If a user doesn't want to see the collapsed RevisionSlider bar at the top of the diff page, they can opt-out by checking *Don't show the RevisionSlider* in their preferences under *Appearance -> Diffs*.