

BlueSpiceCustomMenu

CustomMenu is a menu with configurable items.

BlueSpiceCustomMenu

Provides customizable menus

Status:	stable
Developer:	
Extension type:	BlueSpice
Edition:	BlueSpice free
Dependencies:	BlueSpice
License:	GPL v3 only
Activated:	No
Category:	Search and Navigation

Usage / features

CustomMenu is implemented as header menu with flyout child menus. It appears as collapsible menu above the top navigation bar. The HTML output is an unordered list. CustomMenu is **enabled by default**.

Menu items can be modified by editing the `MediaWiki:CustomMenu/Header`.

Syntax:

```
* html ID (has to be unique) | target page | label (optional)
```

The `html ID` can be used to apply CSS rules in `MediaWiki:Common.css`.

Examples:

1. A link to the Wiki page 'Intranet':

```
* menuLink1 | Intranet
```

The html ID 'menuLink1' is used to display the menu item, because no label has been specified.

2. A link to the Wiki page 'Intranet'. The visible label is 'Our Intranet':

```
* menuLink1 | Intranet | Our Intranet
```

3. A Dropdown with link to the Wiki pages 'Intranet' and 'Demo'. The visible label of the menu is 'Hello World'. The dropdown contains 'Our Intranet' and 'Demo':

```
* Hello World  
** menuLink1 | Intranet | Our Intranet  
** demoLink | https://en.demo.bluespice.com | Demo
```

Technical information

BlueSpiceCustomMenu will be hidden on mobile devices. The width is restricted to the content width. It is limited to one line.

By default, there are only 2 menu levels (link text and one dropdown). More levels can be set, but it is tested only up to level 3. We recommend not to use more levels. Menu may be outside the window!

Config

Name	Default value	Override by
\$bsgCustomMenuHeaderNumberOfLevels	2	\$bsgOverrideCustomMenuHeaderNumberOfLevels
\$bsgCustomMenuHeaderNumberOfMainEntries	10	\$bsgOverrideCustomMenuHeaderNumberOfMainEn
\$bsgCustomMenuHeaderNumberOfSubEntries	10	\$bsgOverrideCustomMenuHeaderNumberOfSubEnt