Contents

1. Reference:BlueSpiceExpiry 2
2. Category:Extension 4
3. GPL-3.0-only 9
4. Manual:Extension/BlueSpiceExpiry 9

Reference:BlueSpiceExpiry

Extension: BlueSpiceExpiry

all extensions

Overview			
Description:	Pages can be marked as expired.		
State:	stable	**Dependency:**	BlueSpice
Developer:	HalloWelt	**License:**	GPL-3.0-only
Type:	BlueSpice	**Category:**	Quality Assurance
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	**Version:**	4.1+
View user help page			

Features

Expiry marks — after a certain period of time — a chosen article as "obsolete". The article can be updated by editing or by confirming that the article is still up-to-date. Expiry is the ideal basis for an archiving system. Outdated articles can be moved to an archive after being queried.

- An author can add an expiration date to an article.
- The expiry date can automatically be postponed to the future for a specific period of time.
- Several authors: There can only be one expiration date. The user who originally entered the expiration date will be informed of the change.
- There is no limit to the number of expiration dates with respect to users.

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.36.0
BlueSpiceFoundation: 4.1

- BlueSpiceReminder: 4.1

Integrates into

- BlueSpiceEchoConnector
- BlueSpiceReminder
- BlueSpiceSMWConnector

Special pages

- Expiry

Permissions

Name	Description	Role
expirearticle	Expire pages	admin, editor, maintenanceadmin
expiry-delete	Remove expiration from pages	admin, editor, maintenanceadmin

Configuration

Name	Value
ExpiryEnablePDFWatermark	true
ExpiryEnablePageWatermark	true
ExpiryEnablePrintWatermark	true

API Modules

- bs-expiry-store
- bs-expiry-tasks

Hooks

- BSUEModulePDFBeforeAddingStyleBlocks
- BSUEModulePDFgetPage
- BeforePageDisplay
- BlueSpiceDiscoveryTemplateDataProviderAfterInit
- ChameleonSkinTemplateOutputPageBeforeExec
- LoadExtensionSchemaUpdates
- MWStakeCommonUIRegisterSkinSlotComponents
- SkinTemplateNavigation::Universal
- StandardDialogsRegisterPageInfoPanelModules

- wgQueryPages

Accessibility

Test status:	2-testing complete
Checked for:	Web, Authoring tool
Last test date:	2022-08-05
WCAG level:	AA
WCAG support:	supports
Comments:	erm:27714 (fix: 4.2.4)
Extension type:	core
Extension focus:	reader

Category:Extension

Extensions that are bundled with one or more BlueSpice pro editions.

Pages in category "Extension"

The following 200 pages are in this category, out of 214 total.

(previous page) (next page)

A

- Reference:Arrays
- Reference:AtMentions
- Reference:Auth remoteuser

B

- Reference:BlueSpiceAbout
- Reference:BlueSpiceArticleInfo
- Reference:BlueSpiceArticlePreviewCapture
- Reference:BlueSpiceAvatars
- Reference:BlueSpiceBookshelf
- Reference:BlueSpiceCategoryCheck

- Reference:BlueSpiceCategoryManager
- Reference:BlueSpiceChecklist
- Reference:BlueSpiceCloudClient
- Reference:BlueSpiceConfigManager
- Reference:BlueSpiceContextMenu
- Reference:BlueSpiceCountThings
- Reference:BlueSpiceCustomMenu
- Reference:BlueSpiceDashboards
- Reference:BlueSpiceDiscovery
- Reference:BlueSpiceDistributionConnector
- Reference:BlueSpiceDrawioConnector
- Reference:BlueSpiceEchoConnector
- Reference:BlueSpiceEmoticons
- Reference:BlueSpiceExpiry
- Reference:BlueSpiceExportTables
- Reference:BlueSpiceExtendedFilelist
- Reference:BlueSpiceExtendedSearch
- Reference:BlueSpiceExtendedStatistics
- Reference:BlueSpiceFilterableTables
- Reference:BlueSpiceFlaggedRevsConnector
- Reference:BlueSpiceFoundation
- Reference:BlueSpiceGroupManager
- Reference:BlueSpiceHideTitle
- Reference:BlueSpiceInsertCategory
- Reference:BlueSpiceInsertFile
- Reference:BlueSpiceInsertLink
- Reference:BlueSpiceInsertMagic
- Reference:BlueSpiceInsertTemplate
- Reference:BlueSpiceInstanceStatus
- Reference:BlueSpiceInterWikiLinks
- Reference:BlueSpiceInterwikiSearch
- Reference:BlueSpiceMultiUpload
- Reference:BlueSpiceNamespaceManager
- Reference:BlueSpiceNSFileRepoConnector
- Reference:BlueSpicePageAccess
- Reference:BlueSpicePageAssignments
- Reference:BlueSpicePageFormsConnector
- Reference:BlueSpicePagesVisited
- Reference:BlueSpicePageTemplates
- Reference:BlueSpicePermissionManager
- Reference:BlueSpicePlayer
- Reference:BlueSpicePrivacy
- Reference:BlueSpiceProDistributionConnector
- Reference:BlueSpiceQrCode
- Reference:BlueSpiceRating
- Reference:BlueSpiceReadConfirmation
- Reference:BlueSpiceReaders
- Reference:BlueSpiceReminder
- Reference:BlueSpiceRSSFeeder

- Reference:BlueSpiceSaferEdit
- Reference:BlueSpiceSignHere
- Reference:BlueSpiceSmartList
- Reference:BlueSpiceSMWConnector
- Reference:BlueSpiceSocial
- Reference:BlueSpiceSocialBlog
- Reference:BlueSpiceSocialComments
- Reference:BlueSpiceSocialMicroBlog
- Reference:BlueSpiceSocialProfile
- Reference:BlueSpiceSocialRating
- Reference:BlueSpiceSocialResolve
- Reference:BlueSpiceSocialTags
- Reference:BlueSpiceSocialTimelineUpdate
- Reference:BlueSpiceSocialTopics
- Reference:BlueSpiceSocialWatch
- Reference:BlueSpiceTagCloud
- Reference:BlueSpiceUEModuleBookPDF
- Reference:BlueSpiceUEModuleDOCX
- Reference:BlueSpiceUEModuleHTML
- Reference:BlueSpiceUEModulePDF
- Reference:BlueSpiceUEModulePDFRecursive
- Reference:BlueSpiceUEModulePDFSubpages
- Reference:BlueSpiceUEModuleTable2Excel
- Reference:BlueSpiceUniversalExport
- Reference:BlueSpiceUsageTracker
- Reference:BlueSpiceUserInfo
- Reference:BlueSpiceUserManager
- Reference:BlueSpiceUserSidebar
- Reference:BlueSpiceVisualEditorConnector
- Reference:BlueSpiceWatchList
- Reference:BlueSpiceWebDAVClientIntegration
- Reference:BlueSpiceWebDAVMinorSave
- Reference:BlueSpiceWhoIsOnline
- Reference:BlueSpiceWikiExplorer
- Reference:BlueSpiceWikiFarm

C

- Reference:CategoryTree
- Reference:Checklists
- Reference:Cite
- Reference:CiteThisPage
- Reference:CodeEditor
- Reference:CodeMirror
- Reference:CognitiveProcessDesigner
- Reference:ConfirmAccount
- Reference:ConfirmEdit
- Reference:ContainerFilter
- Reference:ContentDroplets

- Reference:ContentProvisioning
- Reference:ContentStabilization
- Reference:ContentTransfer
- Reference:CreateUserPage

D

- Reference:Data Transfer
- Reference:DateTimeTools
- Reference:DrawioEditor
- Reference:DynamicPageList3

E

- Reference:Echo
- Reference:EmbedVideo
- Reference:EmbedVideo (fork)
- Reference:EnhancedUpload
- Reference:EventBus
- Reference:External Data
- Reference:ExtJSBase

F

- Reference:FilterSpecialPages
- Reference:FlaggedRevs
- Reference:FlexiSkin
- Reference:FontAwesome
- Reference:Forms

G

- Reference:Gadgets

H

- Template:Hdsk PT Extension HW
- Template:Hdsk PT Extension MW
- Reference:Header Tabs
- Reference:HeaderFooter
- Reference:HitCounters

I

- Reference:ImageMap
- Reference:ImageMapEdit
- Reference:ImportOfficeFiles
- Reference:InputBox
- Reference:Interwiki
- Reference:InviteSignup

L

- Reference:LDAP Authorization
- Reference:LDAPAuthentication2
- Reference:LDAPGroups
- Reference:LDAPProvider
- Reference:LDAPSyncAll
- Reference:LDAPUserInfo
- Reference:Lingo
- Reference:LocalisationUpdate
- Reference:LoginNotify
- Reference:Loops

M

- Reference:Maps
- Reference:Math
- Reference:MediaWiki
- Reference:MenuEditor
- Reference:MergeArticles
- Reference:MultimediaViewer

N

- Reference:NSFileRepo
- Reference:Nuke

O

- Reference:OATHAuth
- Reference:OOJSPlus
- Reference:OpenID Connect
- Reference:OpenLayers

P

- Reference:Page Forms
- Reference:PageCheckout
- Reference:PageHeader
- Reference:PageImages
- Reference:ParserFunctions
- Reference:ParserHooks
- Reference:PDFEmbed
- Reference:PdfHandler
- Reference:PluggableAuth
- Reference:Poem
- Reference:Popups
- Reference:PreToClip

R

- Archive:Reference:BlueSpiceCalumma
- Archive:Reference:BlueSpiceLatexRenderer
- Archive:Reference:BlueSpiceMatomoConnector
- Archive:Reference:BlueSpiceNamespaceCSS
- Archive:Reference:BlueSpiceSocialWikiPage
- Archive:Reference:Bootstrap
- Archive:Reference:Chameleon
- Reference:Renameuser
- Reference:Replace Text
- Reference:RevisionSlider
- Reference:RSS

S

- Reference:Scribunto
- Reference:SectionAnchors
- Reference:SecureLinkFixer
- Reference:Semantic Compound Queries
- Reference:Semantic Extra Special Properties
- Reference:Semantic MediaWiki
- Reference:Semantic Result Formats
- Reference:Semantic Scribunto
- Reference:SimpleSAMLphp
- Reference:SimpleTasks
- Reference:SpamBlacklist
- Reference:StandardDialogs
- Reference:SubPageList
- Reference:SyntaxHighlight

T

- Reference:TabberNeue
- Reference:TemplateData
- Reference:TemplateStyles
- Reference:TextExtracts
- Reference:TitleBlacklist

(previous page) (next page)

GPL-3.0-only

Redirect to:

- GPL v3

Expiry

An article can be marked as "expired" after a certain date and is the ideal basis for an archiving system.

Contents

1 Setting an expiration date 11
2 Unexpiring a page 11
3 List of expired pages 11
4 Archiving obsolete pages 11
5 Expiration log 11
6 Configuration 11

Setting an expiration date

To set the expiration date for an article:

1. **Click** S*et expiry* in the page tools.
2. **Enter** an expiration date. It could be today or any day in the future.
3. **Enter** an expiration comment (optional).
4. **Click** *Save*

When the expiration date is reached, the page shows the expiration marker "expired" in the title area. Additionally a watermark is shown on the article by default.

Unexpiring a page

To remove the expiration marker from an article, click the drop-down arrow next to the "expired"-marker in the title area and unexpire the page.

List of expired pages

To view all pages that have an expiration date, you can go to *Global settings > Tools > Expired pages*. From there, users can remove the expiration marker of any page.

Archiving obsolete pages

Administrators can create an *Archive* namespace if obsolete pages should be archived rather than deleted. Users can then move articles to this namespace.

Expiration log

Administrators can view a log with all expiration activities from the page *Special:Log*.

1. **Select** the log type *Expiry* from the drop-down menu.
2. **Click** Show.

Configuration

You can set the following options in the Config manager.

Additionally, the display of the expiry status can be moved after the page content in the Config manager.

Technical Reference: BlueSpiceExpiry