

Contents

1. Reference:BlueSpiceSocial	2
2. Category:Extension	4
3. GPL-3.0-only	10
4. Manual:Extension/BlueSpiceSocial	10
5. Reference:BlueSpiceSocialBlog	14
6. Reference:BlueSpiceSocialComments	16
7. Reference:BlueSpiceSocialMicroBlog	18
8. Reference:BlueSpiceSocialProfile	20
9. Reference:BlueSpiceSocialRating	24
10. Reference:BlueSpiceSocialResolve	25
11. Reference:BlueSpiceSocialTags	27
12. Reference:BlueSpiceSocialTimelineUpdate	30
13. Reference:BlueSpiceSocialTopics	31
14. Reference:BlueSpiceSocialWatch	35
15. Reference:BlueSpiceSocialWikiPage	36

Reference:BlueSpiceSocial

Extension: BlueSpiceSocial

→ [all extensions](#)

Overview			
Description:	Base extension for social extensions		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL-3.0-only
Type:	BlueSpice	Category:	Administration
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	Version:	4.1+
? View user help page			

Features

BlueSpiceSocial is a group of extensions that add social media features to the wiki. This allows users to quickly communicate on the wiki and to express their opinions on pages more easily.

Warning! Pages in the namespaces *SocialEntity* and *User* are indexed by search engines by default until prior to version 3.1.13. If you run a public wiki with an earlier version, you should [exclude these namespaces from being searchable](#) unless you want these pages to be indexed by public search engines.

BlueSpiceSocial provides the architecture for all *Social* extensions. It contains base classes, SourceTitle namespace, SocialEntity ContentModel, notifications, etc.

This extension is required by all *Social* extensions. Without another *Social* extension (e.g., BlueSpiceSocialBlog), this extension has no effect.

The following *Social* extensions are available:

- [SocialBlog](#)
- [SocialComments](#)
- [SocialMicroBlog](#)
- [SocialProfile](#)

- [SocialRating](#)
- [SocialResolve](#)
- [SocialTags](#)
- [SocialTimelineUpdate](#)
- [SocialTopics](#)
- [SocialWatch](#)
- [SocialWikiPage](#)

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.37.0
BlueSpiceExtendedSearch: 4.4

- BlueSpiceFoundation: 4.1

Integrates into

- BlueSpiceExtendedSearch
- BlueSpicePrivacy

Special pages

- Activities
- Timeline

Permissions

Name	Description	Role
social-deleteothers	Delete others' entries	admin, maintenanceadmin
social-editothers	Edit others' entries	admin, maintenanceadmin
social-source	View the source page	maintenanceadmin

Configuration

Name	Value
SocialCanHaveChildrenBlacklist	array ()
SocialMainLinksTimeline	false
SocialRenderCacheEntityBlacklist	array ()
SocialUseRenderCache	true

User options

Name	Value
bs-social-datedisplaymode	'age'
bs-social-warnonleave	true
echo-subscriptions-web-bs-social-entity-cat	1

API Modules

- [bs-social-tasks](#)
- [bs-socialentity-store](#)
- [bs-socialtitlequery-store](#)

Hooks

- [BSEntityDeleteComplete](#)
- [BSEntitySaveComplete](#)
- [BSRSSFeederBeforeGetRecentChanges](#)
- [BSUEModulePDFBeforeAddingStyleBlocks](#)
- [BeforeEchoEventInsert](#)
- [BeforePageDisplay](#)
- [ChangesListSpecialPageStructuredFilters](#)
- [GetPreferences](#)
- [HtmlPageLinkRendererEnd](#)
- [LoadExtensionSchemaUpdates](#)
- [MWStakeCommonUIRegisterSkinSlotComponents](#)
- [MergeAccountFromTo](#)
- [SendWatchlistEmailNotification](#)
- [SkinBuildSidebar](#)

Category:Extension

Extensions that are bundled with one or more BlueSpice pro editions.

Pages in category "Extension"

The following 200 pages are in this category, out of 214 total.

(previous page) ([next page](#))

A

- [Reference:Arrays](#)
- [Reference:AtMentions](#)
- [Reference:Auth remoteuser](#)

B

- [Reference:BlueSpiceAbout](#)
- [Reference:BlueSpiceArticleInfo](#)
- [Reference:BlueSpiceArticlePreviewCapture](#)
- [Reference:BlueSpiceAvatars](#)
- [Reference:BlueSpiceBookshelf](#)
- [Reference:BlueSpiceCategoryCheck](#)
- [Reference:BlueSpiceCategoryManager](#)
- [Reference:BlueSpiceChecklist](#)
- [Reference:BlueSpiceCloudClient](#)
- [Reference:BlueSpiceConfigManager](#)
- [Reference:BlueSpiceContextMenu](#)
- [Reference:BlueSpiceCountThings](#)
- [Reference:BlueSpiceCustomMenu](#)
- [Reference:BlueSpiceDashboards](#)
- [Reference:BlueSpiceDiscovery](#)
- [Reference:BlueSpiceDistributionConnector](#)
- [Reference:BlueSpiceDrawioConnector](#)
- [Reference:BlueSpiceEchoConnector](#)
- [Reference:BlueSpiceEmoticons](#)
- [Reference:BlueSpiceExpiry](#)
- [Reference:BlueSpiceExportTables](#)
- [Reference:BlueSpiceExtendedFilelist](#)
- [Reference:BlueSpiceExtendedSearch](#)
- [Reference:BlueSpiceExtendedStatistics](#)
- [Reference:BlueSpiceFilterableTables](#)
- [Reference:BlueSpiceFlaggedRevsConnector](#)
- [Reference:BlueSpiceFoundation](#)
- [Reference:BlueSpiceGroupManager](#)
- [Reference:BlueSpiceHideTitle](#)
- [Reference:BlueSpiceInsertCategory](#)
- [Reference:BlueSpiceInsertFile](#)

- [Reference:BlueSpiceInsertLink](#)
- [Reference:BlueSpiceInsertMagic](#)
- [Reference:BlueSpiceInsertTemplate](#)
- [Reference:BlueSpiceInstanceStatus](#)
- [Reference:BlueSpiceInterWikiLinks](#)
- [Reference:BlueSpiceInterwikiSearch](#)
- [Reference:BlueSpiceMultiUpload](#)
- [Reference:BlueSpiceNamespaceManager](#)
- [Reference:BlueSpiceNSFileRepoConnector](#)
- [Reference:BlueSpicePageAccess](#)
- [Reference:BlueSpicePageAssignments](#)
- [Reference:BlueSpicePageFormsConnector](#)
- [Reference:BlueSpicePagesVisited](#)
- [Reference:BlueSpicePageTemplates](#)
- [Reference:BlueSpicePermissionManager](#)
- [Reference:BlueSpicePlayer](#)
- [Reference:BlueSpicePrivacy](#)
- [Reference:BlueSpiceProDistributionConnector](#)
- [Reference:BlueSpiceQrCode](#)
- [Reference:BlueSpiceRating](#)
- [Reference:BlueSpiceReadConfirmation](#)
- [Reference:BlueSpiceReaders](#)
- [Reference:BlueSpiceReminder](#)
- [Reference:BlueSpiceRSSFeeder](#)
- [Reference:BlueSpiceSaferEdit](#)
- [Reference:BlueSpiceSignHere](#)
- [Reference:BlueSpiceSmartList](#)
- [Reference:BlueSpiceSMWConnector](#)
- [Reference:BlueSpiceSocial](#)
- [Reference:BlueSpiceSocialBlog](#)
- [Reference:BlueSpiceSocialComments](#)
- [Reference:BlueSpiceSocialMicroBlog](#)
- [Reference:BlueSpiceSocialProfile](#)
- [Reference:BlueSpiceSocialRating](#)
- [Reference:BlueSpiceSocialResolve](#)
- [Reference:BlueSpiceSocialTags](#)
- [Reference:BlueSpiceSocialTimelineUpdate](#)
- [Reference:BlueSpiceSocialTopics](#)
- [Reference:BlueSpiceSocialWatch](#)
- [Reference:BlueSpiceTagCloud](#)
- [Reference:BlueSpiceUEModuleBookPDF](#)
- [Reference:BlueSpiceUEModuleDOCX](#)
- [Reference:BlueSpiceUEModuleHTML](#)
- [Reference:BlueSpiceUEModulePDF](#)
- [Reference:BlueSpiceUEModulePDFRecursive](#)
- [Reference:BlueSpiceUEModulePDFSubpages](#)
- [Reference:BlueSpiceUEModuleTable2Excel](#)
- [Reference:BlueSpiceUniversalExport](#)
- [Reference:BlueSpiceUsageTracker](#)

- [Reference:BlueSpiceUserInfo](#)
- [Reference:BlueSpiceUserManager](#)
- [Reference:BlueSpiceUserSidebar](#)
- [Reference:BlueSpiceVisualEditorConnector](#)
- [Reference:BlueSpiceWatchList](#)
- [Reference:BlueSpiceWebDAVClientIntegration](#)
- [Reference:BlueSpiceWebDAVMinorSave](#)
- [Reference:BlueSpiceWholsOnline](#)
- [Reference:BlueSpiceWikiExplorer](#)
- [Reference:BlueSpiceWikiFarm](#)

C

- [Reference:CategoryTree](#)
- [Reference:Checklists](#)
- [Reference:Cite](#)
- [Reference:CiteThisPage](#)
- [Reference:CodeEditor](#)
- [Reference:CodeMirror](#)
- [Reference:CognitiveProcessDesigner](#)
- [Reference:ConfirmAccount](#)
- [Reference:ConfirmEdit](#)
- [Reference:ContainerFilter](#)
- [Reference:ContentDroplets](#)
- [Reference:ContentProvisioning](#)
- [Reference:ContentStabilization](#)
- [Reference:ContentTransfer](#)
- [Reference>CreateUserPage](#)

D

- [Reference:Data Transfer](#)
- [Reference:DateTimeTools](#)
- [Reference:DrawioEditor](#)
- [Reference:DynamicPageList3](#)

E

- [Reference:Echo](#)
- [Reference:EmbedVideo](#)
- [Reference:EmbedVideo \(fork\)](#)
- [Reference:EnhancedUpload](#)
- [Reference:EventBus](#)
- [Reference:External Data](#)
- [Reference:ExtJSBase](#)

F

- [Reference:FilterSpecialPages](#)
- [Reference:FlaggedRevs](#)

- [Reference:FlexiSkin](#)
- [Reference:FontAwesome](#)
- [Reference:Forms](#)

G

- [Reference:Gadgets](#)

H

- [Template:Hdsk PT Extension HW](#)
- [Template:Hdsk PT Extension MW](#)
- [Reference:Header Tabs](#)
- [Reference:HeaderFooter](#)
- [Reference:HitCounters](#)

I

- [Reference:ImageMap](#)
- [Reference:ImageMapEdit](#)
- [Reference:ImportOfficeFiles](#)
- [Reference:InputBox](#)
- [Reference:Interwiki](#)
- [Reference:InviteSignup](#)

L

- [Reference:LDAP Authorization](#)
- [Reference:LDAPAuthentication2](#)
- [Reference:LDAPGroups](#)
- [Reference:LDAPProvider](#)
- [Reference:LDAPSynAll](#)
- [Reference:LDAPUserInfo](#)
- [Reference:Lingo](#)
- [Reference:LocalisationUpdate](#)
- [Reference>LoginNotify](#)
- [Reference:Loops](#)

M

- [Reference:Maps](#)
- [Reference:Math](#)
- [Reference:MediaWiki](#)
- [Reference:MenuEditor](#)
- [Reference:MergeArticles](#)
- [Reference:MultimediaViewer](#)

N

- [Reference:NSFileRepo](#)

- [Reference:Nuke](#)

O

- [Reference:OATHAuth](#)
- [Reference:OJSPlus](#)
- [Reference:OpenID Connect](#)
- [Reference:OpenLayers](#)

P

- [Reference:Page Forms](#)
- [Reference:PageCheckout](#)
- [Reference:PageHeader](#)
- [Reference:PageImages](#)
- [Reference:ParserFunctions](#)
- [Reference:ParserHooks](#)
- [Reference:PDFEmbed](#)
- [Reference:PdfHandler](#)
- [Reference:PluggableAuth](#)
- [Reference:Poem](#)
- [Reference:Popups](#)
- [Reference:PreToClip](#)

R

- [Archive:Reference:BlueSpiceCalumma](#)
- [Archive:Reference:BlueSpiceLatexRenderer](#)
- [Archive:Reference:BlueSpiceMatomoConnector](#)
- [Archive:Reference:BlueSpiceNamespaceCSS](#)
- [Archive:Reference:BlueSpiceSocialWikiPage](#)
- [Archive:Reference:Bootstrap](#)
- [Archive:Reference:Chameleon](#)
- [Reference:Renameuser](#)
- [Reference:Replace Text](#)
- [Reference:RevisionSlider](#)
- [Reference:RSS](#)

S

- [Reference:Scribunto](#)
- [Reference:SectionAnchors](#)
- [Reference:SecureLinkFixer](#)
- [Reference:Semantic Compound Queries](#)
- [Reference:Semantic Extra Special Properties](#)
- [Reference:Semantic MediaWiki](#)
- [Reference:Semantic Result Formats](#)
- [Reference:Semantic Scribunto](#)
- [Reference:SimpleSAMLphp](#)
- [Reference:SimpleTasks](#)

- [Reference:SpamBlacklist](#)
- [Reference:StandardDialogs](#)
- [Reference:SubPageList](#)
- [Reference:SyntaxHighlight](#)

T

- [Reference:TabberNeue](#)
- [Reference:TemplateData](#)
- [Reference:TemplateStyles](#)
- [Reference:TextExtracts](#)
- [Reference:TitleBlacklist](#)

(previous page) ([next page](#))

GPL-3.0-only

Redirect to:

- [GPL v3](#)

Social Wiki

BlueSpiceSocial is a set of extensions that add social features around a wiki page. It allows users to quickly communicate on the wiki and to express their opinion on pages.

Contents

1 Scope	11
2 User profile	11
3 Discussions	12
4 Timeline	12
4.1 Creating new entries	12
4.2 Interacting with social entities	12
5 Blog	13
6 Permissions	13
7 Deactivating the comments feature	13
8 Related info	14

Scope

BlueSpice Social contains the following functionality:

- **User profile:** Provides the page *User:<username>*.
- **Attachments:** Connects uploaded files to wiki pages.
- **Discussions:** Enables discussions with comments created on wiki pages. Discussion entries can be marked as "closed".
- **Activities:** Automatically creates pages in the *SocialEntity* namespace to track page edits and creations.
- **Blog:** Provides the special page *Special:Blog*. A blog view can also be embedded into individual wiki pages.
- **Microblog:** Similar to blog entries, but without a headline.
- **Timeline:** A chronological list of all social entities. The timeline filter can be used for displaying social entities on wiki pages.

User profile

Every user has a profile that is displayed on the page *User:<username>*. Users can access their user profile by clicking on *Profile* in the user menu (located in the [header bar](#)).

The user profile shows the user's basic information (depending on the wiki setup) and the user's profile image.

Below the user info, the user's wiki activities are listed: Comments the user made, actions on pages, and in general the user's activity on the wiki. It also allows other users to leave comments on the user's profile page.

The screenshot displays a user profile for Sarah Naumann. At the top, there is a profile picture of a smiling woman. To the right of the picture, a table lists her details: Name (Sarah Naumann), Department (IT), Function (Senior Operations Engineer), Location (Ulm), and Telephone (+49 73 4860-94). An 'Edit' button is visible in the top right corner of this section. Below the profile information, there are four circular icons: a list, a funnel, a plus sign, and a refresh symbol. The main content area shows a comment by Greg Rundlett about BlueSpice, followed by a comment by Sarah Naumann. Sarah's comment includes a smaller version of her profile information table. At the bottom, another comment by Sarah Naumann is partially visible.

Name	Sarah Naumann
Department	IT
Function	Senior Operations Engineer
Location	Ulm
Telephone	+49 73 4860-94

Greg Rundlett über BlueSpice

Bei der EMWCon in Houston kam Greg Rundlett zu folgendem Ergebnis:BlueSpice is really the best option out there - I think globally - for MediaWiki Enterprise, MediaWiki hosting and support.

Comment (1) vor einem Monat • Sarah Naumann

Sarah Naumann

Name	Sarah Naumann
Department	IT
Function	Senior Operations Engineer
Location	Ulm
Telephone	+49 73 4860-94

vor einem Monat

Sarah Naumann commented "Starker Kaffee"

Die Pulvermenge steigt doch nicht linear mit der Wassermenge. Siehe zum Beispiel den

Discussions

BlueSpiceSocial integrates a discussion section at the bottom of every wiki page. This section allows users to create comments directly on a wiki page. If it is the first entry in a discussion, the discussion page is automatically created at this time if this is configured in the [Configuration manager](#).

The discussion section can be disabled on the page-level by adding the [MagicWord](#) `__NODISCUSSION__` to the page in source editing mode.

Timeline

The screenshot shows a 'Timeline' page with three entries. Each entry includes a user profile picture, a title, a comment text, and a 'Recommend' button with a count. The first entry is by Horst Schreiber, the second by Greg Rundlett, and the third by Maik Kalb. The timeline is titled 'Timeline' at the bottom.

Horst Schreiber commented "Greg Rundlett über BlueSpice"

Danke für den Hinweis! Eine Übersetzung wäre noch schön gewesen. Ich glaube auch nicht, dass jeder Leser schon versteht, was WebDAV bringt. Vielleicht kann man das noch etwas ausführlicher erklären?

vor einem Monat • Horst Schreiber

Recommend (0)

Greg Rundlett über BlueSpice

Bei der EMWCon in Houston kam Greg Rundlett zu folgendem Ergebnis: BlueSpice is really the best option out there - I think globally - for MediaWiki Enterprise, MediaWiki hosting and support.

Comment (1) vor einem Monat • Sarah Naumann

More ▾

Recommend (0)

Maik Kalb commented "Starker Kaffee"

Naja, 6g Kaffee pro Tasse sagt die Anleitung. Und linear mit den Tassen steigt dann schon die Pulvermenge. Übrigens: Wer den letzten Kaffee rauspresst, sollte gleich neuen kochen.

vor einem Monat • Maik Kalb

Recommend (0)

Timeline

Timeline is a special page that provides an overview of all social conversations on the wiki.

By default, it is listed on the *Main navigation*. You can also access the page directly at [Special: Timeline](#). On this page, users can sort and filter existing social entries or create new entries.

Creating new entries

To create a new entry, click on the "Plus" icon to add a new timeline entry:

- **Blog entry:** [Blog](#) is used for topics to be shared with other users on the wiki
- **Microblog:** Like a blog entry, but without titles. It should be used for a short entry, e.g., a quick announcement.
- **Discussion topic:** Adds a discussion entry to a particular wiki page.

Interacting with social entities

Every entry in the timeline is called a social entity. Depending on the type of social entity, the following interaction options exist:

- **Comments:** Number of comments related to the entity. Clicking on *Comments* opens all current comments and allows users to add a comment (if user has the necessary permissions).

- **Recommend:** Number of users that recommended the entity. Users can add a recommendation by clicking on *Recommend*.
- **Linked articles:** Number of articles linked to this entity. Clicking on *Linked articles* shows the list of linked articles.
- **Watch/Unwatched:** Shows if the user is currently watching the entity (the receives notifications when the entity is changed). Clicking on Watch or Unwatch changes the state of watching.
- **Resolved/Unresolved:** The status of the entity. Some entities, like discussions on a question can have a status attached to them, so that other users know if the question is answered.

Blog

Blog is a special page showing an overview of all blog entities available on the wiki. By default, it is listed on the *Main navigation*. You can also access the page directly at `Special:Blog`. Users can sort and filter the list entries by clicking on the icons above the list.

Learn how to [include the blog on any wiki page](#).

Permissions

From BlueSpice version 3.2.7 the following roles have associated "social" permissions. Earlier versions have no option to limit the creation and editing of blog entries by using the role *commenter*.

Rechte/Rolle	commenter	editor	admin	maintenance-admin	Berechtigung
Create and edit blog entry		x	x	x	social-blog
Comment on blog entry	x	x	x	x	social-blog-comment
Create and edit microblog entry	x	x	x	x	social-microblog
Comment on microblog entry	x	x	x	x	social-microblog-comment
Create discussion entry	x	x	x	x	social-topics
Comment on discussion entry	x	x	x	x	social-topics-comment
Create and edit attachments	x	x	x	x	social-stash

The comments function for blog, microblog and discussion entries can be deactivated in the LocalSettings-file on the server.

Deactivating the comments feature

The comment function for comments on blog, microblog and discussion entries can be deactivated in the LocalSettings file on the server.

```
$bsgSocialCanHaveChildrenBlacklist = [  
    'blog', // disable comments on blog  
    'topic', // disable comments on discussion topics  
    'microblog' // disable comments on microblogs  
];
```

Related info

- [Blog](#)
- [Discussions and Attachments](#)
- [Reference:BlueSpiceSocial](#)

[Technical Reference: BlueSpiceSocial](#)

Reference:BlueSpiceSocialBlog

Extension: BlueSpiceSocialBlog

[all extensions](#)

Overview			
Description:	Blog entity for BlueSpiceSocial		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL-3.0-only
Type:	BlueSpice	Category:	Communication
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	Version:	4.1+
? View user help page			

Features

BlueSpiceSocialBlog provides the SocialEntity type *blog*.

Warning! Pages in the namespaces *SocialEntity* and *User* are indexed by search engines by default until version 3.1.13. If you run a public wiki with an earlier version, you should [exclude these namespaces from being searchable](#) unless you want these pages to be indexed by public search engines.

The extension BlueSpiceSocialBlog is the basis for the *Special:Blog* page. In every new wiki installation, this page is linked directly from the main navigation. Customized blog views can be added to a wiki page using the `<bs: timeline />` tag.

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.36.0
BlueSpiceFoundation: 4.1

- BlueSpiceSocial: 4.1

Integrates into

Special pages

- Blog

Permissions

Name	Description	Role
social-blog	Create and edit blogs	editor, admin, maintenanceadmin
social-blog-comment	Comment on blogs	commenter, editor, admin, maintenanceadmin

Configuration

Name	Value
BSSocialUseBlogTeaser	true
SocialBlogMainLinksBlog	false
SocialBlogPreloadTitle	'Template: Blog'

Hooks

- [BeforePageDisplay](#)
- [LoadExtensionSchemaUpdates](#)
- [MWStakeCommonUIRegisterSkinSlotComponents](#)
- [SkinBuildSidebar](#)

Configuration

Name	Description	Type	Default	Scope
bsgSocialBlogPreloadTitle	article that is used as preload for SocialEntities of type <i>blog</i>	str	Template: Blog	LocalSettings. php
bsgBSSocialUseBlogTeaser	usa a teaser-text system for SocialEntities of type <i>blog</i>	bool	true	ConfigManager

Reference:BlueSpiceSocialComments

Extension: BlueSpiceSocialComments

→ [all extensions](#)

Overview			
Description:	Comment functionality for BlueSpiceSocial		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL-3.0-only
Type:	BlueSpice	Category:	Communication

Overview			
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	Version:	4.1+

Features

BlueSpiceSocialComments provides the SocialEntity of type *comment*.

Warning! Pages in the namespaces *SocialEntity* and *User* are indexed by search engines by default until version 3.1.13. If you run a public wiki with an earlier version, you should [exclude these namespaces from being searchable](#) unless you want these pages to be indexed by public search engines.

Social entities of type *comment* are automatically displayed with other social entities as a drop-down area by clicking on "Comments".

Not every SocialEntity can be commented (e.g., [profiles](#)). This is defined by the system or by a corresponding customization.

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.36.0
BlueSpiceFoundation: 4.1

- BlueSpiceSocial: 4.1

Integrates into

Special pages

User options

Name	Value
echo-subscriptions-web-bs-social-comment-cat	1

Hooks

- [BSEntityConfigAttributeDefinitions](#)
- [BSEntityGetFullData](#)
- [BSSocialEntityListInitialized](#)
- [BSSocialEntityOutputRenderAfterContent](#)
- [BSSocialModuleDepths](#)

Input files in dialogs

Name	Description	Type/values	Default
<i>text</i>	Content of the comment	Wikitext or reduced VisualEditor, no full parser access	empty

Configuration

In their preferences, users can define if and how they are notified about comments on watched entities.

Reference:BlueSpiceSocialMicroBlog

Extension: BlueSpiceSocialMicroBlog

→ [all extensions](#)

Overview			
Description:	Microblog functionality for BlueSpiceSocial		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL-3.0-only
Type:	BlueSpice	Category:	Communication
	BlueSpice pro, BlueSpice		

Overview			
Edition:	Farm, BlueSpice Cloud	Version:	4.1+
? View user help page			

Features

SocialMicroBlog provides the SocialEntity of type *microblog*.

Warning! Pages in the namespaces *SocialEntity* and *User* are indexed by search engines by default until version 3.1.13. If you run a public wiki with an earlier version, you should [exclude these namespaces from being searchable](#) unless you want these pages to be indexed by public search engines.

Microblog posts can be created on `Special:Timeline` by clicking the "plus" button. In contrast to blog posts, microblog post have no title, but consist only of their content.

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.36.0
BlueSpiceFoundation: 4.1

- BlueSpiceSocial: 4.1

Integrates into

Special pages

Permissions

Name	Description	Role
	Create and edit	commenter, editor, admin,

Name	Description	Role
social-microblog	microblogs	maintenanceadmin
social-microblog-comment	Comment on microblogs	commenter, editor, admin, maintenanceadmin

Input fields in dialogs

Name	Description	Type/values	Default
<i>text</i>	Content of the comment	Wikitext or reduced VisualEditor, no full parser access	empty

Reference:BlueSpiceSocialProfile

Extension: BlueSpiceSocialProfile

→ [all extensions](#)

Overview			
Description:	Profile entity for BlueSpiceSocial		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL-3.0-only
Type:	BlueSpice	Category:	Communication
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	Version:	4.1+

Features

BlueSpiceSocialProfile provides the SocialEntity of type profile. Furthermore, the user page is converted into a complete user profile.

Warning! Pages in the namespaces *SocialEntity* and *User* are indexed by search engines by default until prior to version 3.1.13. If you run a public wiki with an earlier version, you should [exclude these namespaces from being searchable](#) unless you want these pages to be indexed by public search engines.

- the user page is converted into a complete user profile
- the content of the original user page is also shown as a description field below the profile section
- provides the page *Special:SocialProfiles*
- a user profile can be included in a page with the tag `<bs:socialentityprofile username="Testuser" rendertype="Short" />`
- users can update their profile information and upload a profile picture

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.37.0

BlueSpiceAvatars: 4.1

- BlueSpiceFoundation: 4.1 BlueSpiceSocial: 4.1

Integrates into

- BlueSpicePrivacy
- BlueSpiceSMWConnector
- BlueSpiceSocialProfile
- BlueSpiceVisualEditorConnector
- ContentDroplets

Special pages

- SocialProfiles

Permissions

Name	Description	Role
social-editothersprofile	Edit other users' profile	admin, maintenanceadmin

Name	Description	Role
socialprofile-viewspecialpage	View the special page "Profiles"	accountmanager, admin, author, bot, commenter, editor, maintenanceadmin, reader, reviewer, structuremanager

Configuration

Name	Value
BSSocialProfileCustomFields	array ('social-profile-department' => array ('i18n' => 'bs-social-profile-field-department', 'type' => 'string',), 'social-profile-function' => array ('i18n' => 'bs-social-profile-field-function', 'type' => 'string',), 'social-profile-location' => array ('i18n' => 'bs-social-profile-field-location', 'type' => 'string',), 'social-profile-phone' => array ('i18n' => 'bs-social-profile-field-phone', 'type' => 'string',),)
BSSocialProfileFields	array ('social-profile-title' => array ('i18n' => 'bs-social-profile-field-title', 'callback' => '\\BlueSpice\\Social\\Profile\\Field\\Title::getInstance',), 'social-profile-name' => array ('i18n' => 'bs-social-profile-field-name', 'callback' => '\\BlueSpice\\Social\\Profile\\Field\\Name::getInstance',), 'social-profile-email' => array ('i18n' => 'bs-social-profile-field-email', 'callback' => '\\BlueSpice\\Social\\Profile\\Field\\Email::getInstance',),)

User options

Name	Value
bs-social-profile-infoshowemail	false

Hooks

- [ArticleViewHeader](#)
- [BSPageTemplatesModifyTargetUrl](#)
- [BSUserInfoMetaDataFactoryAllKeys](#)
- [BSUserInfoMetaDataFactoryCallback](#)
- [DeleteAccount](#)
- [GetPreferences](#)
- [HtmlPageLinkRendererBegin](#)
- [LocalUserCreated](#)
- [PageSaveComplete](#)
- [UserLoadAfterLoadFromSession](#)
- [UserSaveSettings](#)

Configuration

Name	Description	Type	Default	Scope
<i>bsgBSSocialProfileFields</i>	system-defined profile fields	array	<pre> "social-profile-title" => ["i18n" => "bs-social-profile-field-title", "callback" => "\\BlueSpice\\Social\\Profile\\Field\\Title:: getInstance"], "social-profile-name" => ["i18n" => "bs-social-profile-field-name", "callback" => "\\BlueSpice\\Social\\Profile\\Field\\Name:: getInstance"], "social-profile-email" => ["i18n" => "bs-social-profile-field-email", "callback" => "\\BlueSpice\\Social\\Profile\\Field\\Email:: getInstance"] </pre>	LocalServer / php / Custom
			<pre> "social-profile-department" => ["i18n" => "bs-social-profile-field- department", "type" => "string"], "social-profile-function" => ["i18n" => "bs-social-profile-field- function", "type" => "string"], </pre>	

Name	Description	Type	Default	Scope
<i>bsg</i> BSSocialProfileCustomFields	user-defined profile fields	array	"social-profile-location" => ["i18n" => "bs-social-profile-field- location", "type" => "string"], "social-profile-phone" => ["i18n" => "bs-social-profile-field- phone", "type" => "string"]	LocalSe php
bs-social-profile- infoshowemail	is the email address shown in the profile	bool	false	useropt

Reference:BlueSpiceSocialRating

Extension: BlueSpiceSocialRating

→ [all extensions](#)

Overview			
Description:	Rating functionality for BlueSpiceSocial-entities		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL-3.0-only
Type:	BlueSpice	Category:	Communication
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	Version:	4.1+

Features

SocialRating provides a rating system with recommendations for SocialEntities.

Warning! Pages in the namespaces *SocialEntity* and *User* are indexed by search engines by default until version 3.1.13. If you run a public wiki with an earlier version, you should [exclude these namespaces from being searchable](#) unless you want these pages to be indexed by public search engines.

This extension provides a button that allows to recommend certain types of social entities such as blog entries. It is not possible to recommend social entities of type *profile*.

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.39.0

BlueSpiceFoundation: 4.1

- BlueSpiceRating: 4.1 BlueSpiceSocial: 4.1

Integrates into

- BlueSpiceRating

Special pages

Hooks

- [BSEntityConfigAttributeDefinitions](#)
- [BSEntityConfigDefaults](#)
- [BSEntityGetFullData](#)
- [BSSocialEntityGetActions](#)
- [BSSocialModuleDepths](#)

Reference:BlueSpiceSocialResolve

Extension: BlueSpiceSocialResolve

→ [all extensions](#)

Overview			
Description:	Resolve functionality for BlueSpiceSocial-entities		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL-3.0-only
Type:	BlueSpice	Category:	Communication
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	Version:	4.1+

Features

SocialResolve provides the unresolved/resolved status for SocialEntities. By default, the status functionality is attached to entities of type *topic* (discussion entries).

This extension adds a button to the social entity topic. Clicking it toggles the unresolved/resolved state of the topic. Closed social entities have a green background by default and their view type is changed to "Short". It is not possible to use this extension for social entities of type *profile*.

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.39.0
BlueSpiceFoundation: 4.1

- BlueSpiceSocial: 4.1

Integrates into

Special pages

Permissions

Name	Description	Role
social-resolve	Change the resolve status of entries	editor

API Modules

- `bs-socialresolve-tasks`

Hooks

- [BSEntityConfigAttributeDefinitions](#)
- [BSEntityConfigDefaults](#)
- [BSEntityGetFullData](#)
- [BSEntitySetValuesByObject](#)
- [BSFoundationRendererMakeTagAttribs](#)
- [BSSocialEntityGetActions](#)
- [BSSocialEntityListRenderEntity](#)
- [BSSocialModuleDepths](#)

Reference:BlueSpiceSocialTags

Extension: BlueSpiceSocialTags

→ [all extensions](#)

Overview			
Description:	Adds tagging functionality to social entities		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL-3.0-only
Type:	BlueSpice	Category:	Communication
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	Version:	4.1+

Features

SocialTags provides the option of linked pages to SocialEntities.

Warning! Pages in the namespaces *SocialEntity* and *User* are indexed by search engines by default until prior to version 3.1.13. If you run a public wiki with an earlier version, you should [exclude these namespaces from being searchable](#) unless you want these pages to be indexed by public search engines.

A social entity such as a discussion topic is linked to a wiki page. Users can update these page associations as needed.

The page *Special:SocialTags* shows a filterable list of SocialEntities that share the same tag. The function "watch" is automatically added to all social entities.

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.37.0
BlueSpiceFoundation: 4.1

- BlueSpiceSocial: 4.1

Integrates into

Special pages

- SocialTags

Permissions

Name	Description	Role
social-tagging	Edit linked pages	admin, author, commenter, editor, maintenanceadmin, reviewer

Configuration

Name	Value
SocialTagsTimelineAfterContentNamespaceBlackList	array ()
SocialTagsTimelineAfterContentShow	false

API Modules

- [bs-socialtags-tasks](#)

Hooks

- [BSEntityConfigAttributeDefinitions](#)
- [BSEntityConfigDefaults](#)
- [BSEntityGetFullData](#)
- [BSEntitySetValuesByObject](#)
- [BSFoundationRendererMakeTagAttribs](#)
- [BSSocialEntityGetActions](#)
- [BSSocialEntityListInitialized](#)
- [BSSocialEntityOutputRenderBeforeContent](#)
- [BSSocialModuleDepths](#)
- [ChameleonSkinTemplateOutputPageBeforeExec](#)
- [PageMoveComplete](#)

Entry fields for dialogs

Name	Description	Type	Default value
<i>tags</i>	Linked pages	array	Current page

Configuration

Name	Description	Type	Default	Scope
	Determines in which namespaces			

Name	Description	Type	Default	Scope
<i>bsg</i> SocialTagsTimelineAfterContentNamespaceBlackList	the timeline is displayed below the page content with the current page as tag.	array	[]	LocalSettings.php
<i>bsg</i> SocialTagsTimelineAfterContentShow	Determines if the timeline is displayed below the page content with the current page as tag.	bool	false	LocalSettings.php

Reference:BlueSpiceSocialTimelineUpdate

Extension: BlueSpiceSocialTimelineUpdate

→ [all extensions](#)

Overview			
Description:	Update functionality for BlueSpiceSocialTimeline		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL-3.0-only
Type:	BlueSpice	Category:	Communication
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	Version:	4.1+

Features

SocialTimelineUpdate provides a button that informs a user when new timeline posts have been created since the last page view. The timeline can then be reloaded. The button is automatically added to each timeline menu. A number indicates the number of contributions that have been added since the last call. For performance reasons, no more than 10 new posts will be queried. If there are more changes, it is indicated as "9+".

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.36.0
BlueSpiceFoundation: 4.1

- BlueSpiceSocial: 4.1

Integrates into

Special pages

Hooks

- [BSSocialModuleDepths](#)
- [BsAdapterAjaxPingResult](#)

Reference:BlueSpiceSocialTopics

Extension: BlueSpiceSocialTopics

→ [all extensions](#)

Overview			
Description:	Topic and discussion entities for BlueSpiceSocial		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL-3.0-only
Type:	BlueSpice	Category:	Communication
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	Version:	4.1+

Features

SocialTopics provides the SocialEntity types *discussion* and *topic*.

Warning! Pages in the namespaces *SocialEntity* and *User* are indexed by search engines by default until prior to version 3.1.13. If you run a public wiki with an earlier version, you should [exclude these namespaces from being searchable](#) unless you want these pages to be indexed by public search engines.

At the bottom of each content page, the social entities associated with the page are displayed, filtered by the *topic* type.

The discussion page is completely replaced by the page view of the SocialEntity type *discussion*. It displays a timeline that lists the social entities of type *topic* that belong to this discussion. In addition, free text can be entered at the beginning of the discussion page just like on a standard MediaWiki discussion page.

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.36.0
BlueSpiceFoundation: 4.1

- BlueSpiceSocial: 4.1

Integrates into

Special pages

- Topics

Permissions

Name	Description	Role
social-topics	Create and edit topics	commenter, editor, admin, maintenanceadmin
		commenter, editor, admin,

Name	Description	Role
social-topics-comment	Comment on topics	maintenanceadmin

Configuration

Name	Value
SocialTopicsTalkPageAutoCreate	false
SocialTopicsTimelineAfterContentNamespaceBlackList	array ()
SocialTopicsTimelineAfterContentShow	true

User options

Name	Value
bs-social-topics-skipcreatedialog	true

API Modules

- [bs-socialtopics-tasks](#)

Hooks

- [ArticleViewHeader](#)
- [BSMigrateSettingsFromDeviatingNames](#)
- [BSSocialModuleDepths](#)
- [BSSocialTagsBeforeSetTags](#)
- [ChameleonSkinTemplateOutputPageBeforeExec](#)
- [GetDoubleUnderscoreIDs](#)
- [GetPreferences](#)
- [LoadExtensionSchemaUpdates](#)
- [MWStakeCommonUIRegisterSkinSlotComponents](#)
- [PageSaveComplete](#)

Entry fields for dialogs

Name	DescriptionD	Type	Default value
discussiontitleid	ID of the page to which the discussion topic belongs	integer/choice field	current discussion page

Name	DescriptionD	Type	Default value
topictitle	Title of the discussion topic	str	empty
text	Content of the discussion topic	WikiText or reduced VisualEditor; reduzierter parser scope	empty

Behavior switch

Name	Beschreibung
<code>__NODISCUSSION__</code>	Diskussionen werden auf der seite ausgeblendet

Configuration

Name	Description	Type	Default value	Scope
<i>bsg</i> SocialTopicsTalkPageAutoCreate	Discussion pages are automatically created with a new page. Activating this option si not recommended, because a lot of pages will be created.	bool	false	ConfigManager
<i>bsg</i> SocialTopicsTimelineAfterContentNamespaceBlackList	Determines in what namespaces the timeline with the latest discussion topics should not be shown.	array	[]	LocalSettings.php
	Determines if the timeline with the latest discussion			

Name	Description	Type	Default value	Scope
<i>bsgSocialTopicsTimelineAfterContentShow</i>	topics should be shown at the bottom of a page.	bool	true	LocalSettings.php

Reference:BlueSpiceSocialWatch

Extension: BlueSpiceSocialWatch

→ [all extensions](#)

Overview			
Description:	Watch-functionality for BlueSpiceSocial-entities		
State:	stable	Dependency:	BlueSpice
Developer:	HalloWelt	License:	GPL-3.0-only
Type:	BlueSpice	Category:	Communication
Edition:	BlueSpice pro, BlueSpice Farm, BlueSpice Cloud	Version:	4.1+

Features

SocialWatch provides the monitoring system for SocialEntities.

Warning! Pages in the namespaces *SocialEntity* and *User* are indexed by search engines by default until prior to version 3.1.13. If you run a public wiki with an earlier version, you should [exclude these namespaces from being searchable](#) unless you want these pages to be indexed by public search engines.

This extension is designed to restrict notifications about social entities. So users do not get notifications for all changes to SocialEntities, but only for the SocialEntities they have on their watchlist. When a user creates or comments on a SocialEntity post, that post is automatically added to the user's watchlist. The watch button is automatically attached to all social entities. Not all social entities can be watched.

Technical Information

This information applies to BlueSpice 4. Technical details for BlueSpice Cloud can differ in some cases.

Requirements

MediaWiki: 1.37.0
BlueSpiceFoundation: 4.1

- BlueSpiceSocial: 4.1

Integrates into

Special pages

API Modules

- bs-socialwatch-tasks

Hooks

- [BSEntityConfigDefaults](#)
- [BSEntityGetFullData](#)
- [BSEntitySaveComplete](#)
- [BSSocialEntityGetActions](#)
- [BSSocialModuleDepths](#)

Reference:BlueSpiceSocialWikiPage

Redirect to:

- [Archive:Reference:BlueSpiceSocialWikiPage](#)