Contents

Time Zone

Contents

1 Tips for this Document 3
2 Changing the Time Zone 3

Even if every user can change his time zone himself in the user settings, BlueSpice sets the default time zone "Europe/Berlin" when the user first logs in. This document describes how to change this if necessary.

Tips for this Document

- Please, read this manual completely and work through the single installation steps one after another.
- For editing the configuration files with a text editor, the files must be saved in UTF-8 coding without BOM (Byte Order Mark).
- The placeholder `<installpath-bluespice>` stands for the path to your BlueSpice installation, e.g `C:\inetpub\wwwroot\bluespice` (Windows regarding the documentation "Folder structure under Windows ") or `/var/www/bluespice` (Linux).
- The placeholder `<tomcat-webapps` stands for the path to the webapps directory of your Tomcat server, e.g `C:\Program Files\Apache Software Foundation\Tomcat 8.5\webapps` (Windows) or `/var/lib/tomcat8/webapps` (Linux).

Changing the Time Zone

Copy the file `<installpath-bluespice>`/settings.d/001-DefaultSettings.php to `<installpath-bluespice>`/settings.d/001-DefaultSettings.local.php and open it. In delivery stat, you can find these two lines there:

```
$wgLocaltimezone = 'Europe/Berlin';
$wgDefaultUserOptions['timecorrection'] = 'ZoneInfo|' . (date("I") ? 120 : 60) .
'|Europe/Berlin';
```

Replace "Europe / Berlin" with your time zone. An overview of all possible time zones can be found in the official PHP documentation.
Save and close the file.