

Contents

1. Setup:Installation Guide/Security Settings .....	2
2. Setup:Installation Guide/Security Settings/File System Permissions .....	2
3. Setup:Installation Guide/Security Settings/Save Directories .....	3

## Setup:Installation Guide/Security Settings

The content format pdf is not supported by the content model wikitext.

Return to [Main Page](#).

### View source for Setup:Installation Guide/Security Settings /File System Permissions

You do not have permission to edit this page, for the following reason:

The action you have requested is limited to users in one of the groups: [Users](#), [Administrators](#), [ES\\_editors](#), [editor](#).

---

You can view and copy the source of this page.

{{DISPLAYTITLE:File System Permissions}} \_\_TOC\_\_ For trouble-free usage of your BlueSpice installation<span class="">, the web server requires write permissions to several folders of the file system.</span><span class="">However, it is recommended to keep the rights for all other files and folders to a minimum.</span><span class="">This document shows you the relevant folders and the correct permissions setting.</span>

==Tips for this Document==

\*Please, read this manual completely and work through the single installation steps one after another.

\*For editing the configuration files with a text editor, the files must be saved in UTF-8 coding without BOM (Byte Order Mark).

\*The placeholder `&lt;installpath-bluespice&gt;` stands for the path to your BlueSpice installation, e.g `C:\inetpub\wwwroot\bluespice` (Windows) or `/var/www/bluespice` (Linux).

==Affected Folders==

The folders, which require write permissions, are:

\*`&lt;installpath-bluespice&gt;/cache`

\*`&lt;installpath-bluespice&gt;/images`

\*`&lt;installpath-bluespice&gt;/extensions/BlueSpiceFoundation/config` (only until BlueSpice v. 4.2.x){Bsvs|bsvTo=4.2.x}

\*`&lt;installpath-bluespice&gt;/extensions/BlueSpiceFoundation/data`

\*`&lt;installpath-bluespice&gt;/extensions/Widgets/compiled_templates`
'''(only BlueSpice pro)'''

==Assignment of Permissions with Windows==

Assign "change" rights for this folder for the local user "Everyone".  
  
[[File:Setup:Setup\_windows\_permissions.jpg|center|link=Special:FilePath/Setups:windows\_permissions.jpg]]

==Assignment of Permissions with Linux==

Here you can assign rights much more strictly, which is also recommended. Transfer the directory `&lt;installpath-bluespice&gt;` recursively to the user root (CHMOD for Files 644, CHMOD for Directories 755) and after this, transfer the mentioned directory recursively to the user and the group, under which the Apache Web Server runs (Debian/Ubuntu e.g. "www-data"). In the following, we provide a bash script, which works through this tasks for you with only one command. To do so, create the file `/usr/local/bin/setWikiPerm` and copy the following code into this file:

```
#!/bin/bash
WWW_USER="www-data"
WWW_GROUP="www-data"
WWW_HOME=$(eval echo ~$WWW_USER)
WWW_CFG=$WWW_HOME/.config
if [ $# -eq 0 ]; then echo "You must enter the path of your MediaWiki installation." exit elif [ ! -d $1 ]; then echo "$1 does not exist or is no path." exit fi if [ ! -f $1/LocalSettings.php ]; then echo "$1 contains no LocalSettings.php" exit fi
PATH=$(echo "$1" | sed -e 's#/#/#' /usr/bin/find $PATH -type d -exec /bin/chmod 755 {} \; /usr/bin/find $PATH -type f -exec /bin/chmod 644 {} \; /bin/chown -R root:root $PATH
pathes=( "$PATH/cache" \
"$PATH/images" \
"$PATH/_sf_archive" \
"$PATH/_sf_instances" \
"$PATH/extensions/BlueSpiceFoundation/data" \
"$PATH/extensions/Widgets/compiled_templates" \ )
for i in "${pathes[@]"; do if [ -d $i ]; then /bin/chown -R $WWW_USER:$WWW_GROUP $i fi done
if [ ! -d $WWW_CFG ]; then /bin/mkdir $WWW_CFG fi
/bin/chown -R $WWW_USER:$WWW_GROUP $WWW_CFG
/usr/bin/find $PATH/extensions -iname 'create_pygmentize_bundle' -exec /bin/chmod +x {} \; /usr/bin/find $PATH/extensions -iname 'pygmentize' -exec /bin/chmod +x {} \; /usr/bin/find $PATH/extensions -name 'lua' -type f -exec /bin/chmod 755 {} \;

```

If needed, replace the content of the variables `WWW_USER="www-data"` `WWW_GROUP="www-data"` with the

appropriate user and group of your distribution. After this, assign CHMOD 755 to this file. Now you can run the script and let it do the complete permission setting automatically with the following command: `setWikiPerm &lt;installpath-bluespice&gt;`

{{Messagebox|boxtype=note|Note text=<b>Note that when the update.php is executed on the console, the rights can be partially discarded. For this reason, set the rights to "update.php" again.</b>}}

[[en:{{FULLPAGENAME}}]] [[de:Setup:Installationsanleitung/Sicherheitseinstellungen/Dateisystemrechte]]

Templates used on this page:

- Template:Bsvs (view source)
- Template:Bsvs/styles.css (view source)
- Template:Messagebox (view source)
- Template:Messagebox/styles.css (view source)

Return to [Setup:Installation Guide/Security Settings/File System Permissions](#).

## View source for Setup:Installation Guide/Security Settings /Save Directories

You do not have permission to edit this page, for the following reason:

The action you have requested is limited to users in one of the groups: **Users**, **Administrators**, **ES\_editors**, **editor**.

---

You can view and copy the source of this page.

{{DISPLAYTITLE:Save Directories}}\_\_TOC\_\_  
==Tips for this Document==  
\* Please, read this manual completely and work through the single installation steps one after another.  
\* For editing the configuration files with a text editor, the files must be saved in UTF-8 coding without BOM (Byte Order Mark).  
\* The placeholder `&lt;installpath-bluespice&gt;` stands for the path to your BlueSpice installation, e. g. `C:\inetpub\wwwroot\bluespice` (Windows) or `/var/www/bluespice` (Linux).  
==Explanation for Saving Directories==  
It is highly recommended, to lock several directories to save them from access from external browsers, so that calling up the directory or the content delivers the HTTP status code (Forbidden). To find out how this works with the webserver you are using, please read the documentation of your webserver software. The following directories should be saved:  
\* `&lt;bluespice-url&gt;/cache`  
\* `&lt;bluespice-url&gt;/images`  
Please keep in mind that you need to unblock the subfolder `&lt;bluespice-url&gt;/images/bluespice/flexiskin` afterwards, because this subfolder must be accessible.  
\* `&lt;bluespice-url&gt;/mw-config` [[en:{{FULLPAGENAME}}]][[de:Setup:Installationsanleitung/Sicherheitseinstellungen/Verzeichnisse\_schützen]]

Return to [Setup:Installation Guide/Security Settings/Save Directories](#).