

Setup:Installation Guide/Security Settings/Deactivating installcheck file

Latest revision as of 16:47, 22 December 2021 ([view source](#))

[Margit.link-rodrigue](#) ([talk](#) | [contribs](#))

(Created page with "''{{DISPLAYTITLE:Deactivating installcheck.php}}'' __TOC__ As soon as the setup of BlueSpice is completed, you should prevent the execution of the installcheck.php while using t...")

[Tag: 2017 source edit](#)

(No difference)

Latest revision as of 16:47, 22 December 2021

Contents

1 Tips for this Document	2
2 Deactivating installcheck.php	2

As soon as the setup of BlueSpice is completed, you should prevent the execution of the `installcheck.php` while using the wiki productively.

A short instruction can be found in this document.

Tips for this Document

Please, read this manual completely and work through the single installation steps one after another. For editing the configuration files with a text editor, the files must be saved in UTF-8 coding without BOM (Byte Order Mark).

The placeholder `<installpath-bluespice>` stands for the path to your BlueSpice installation, e.g. `C:\inetpub\wwwroot\bluespice` (Windows) or `/var/www/bluespice` (Linux).

Deactivating `installcheck.php`

Switch to the directory `<installpath-bluespice>` and open the `installcheck.php` file in a text editor.

```
Insert a new line after the first line and insert
```

```
die( 'Deactivated.' );
```

Save and exit the file. The `installcheck.php` is no longer accessible now.

If you need to restore this file at a later time, it is sufficient to temporarily disable inserted line by placing the `#` character at the beginning of the line.