

## Setup:Installation Guide/System Preparation/Linux/PhantomJS

### Contents

1	<a href="#">Download</a>	2
2	<a href="#">Installation</a>	2
3	<a href="#">Completing the system preparation</a>	2

**Note:** PhantomJS is a so-called headless browser that can render screenshots of web pages. This is required for the web page preview in Advanced Search and the Recent Changes Overview in your BlueSpice installation. These are functionalities of BlueSpice pro. For this purpose, the steps listed here are required.

**Important!** In this documentation, we use PhantomJS version 2.1.1. This is just an example of the latest version that you can download at the time of installation.

## Download

---

Go to the [download page of PhantomJS](#) and download the 64-bit version for Linux. Transfer the file to your server.

## Installation

---

Unpack the downloaded bz2 archive on the server with the command `tar xjf phantomjs-2.1.1-linux-x86_64.tar.bz2`. In the unpacked folder `phantomjs-2.1.1-linux-x86_64`, you will find another folder with the name `bin`. Within this folder is the file `phantomjs`. Copy this file into the `/usr/local/bin` folder. Then adjust the rights of the file:

```
chown root:staff /usr/local/bin/phantomjs; \  
chmod +x /usr/local/bin/phantomjs
```

## Completing the system preparation

---

If you have completed all steps successfully, you can now continue with [installing BlueSpice](#).